




Test Data


Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	1.112	30	Pass
NVNT	BLE	2442	Ant1	2.134	30	Pass
NVNT	BLE	2480	Ant1	3.119	30	Pass














-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	limit	Verdic
NVNT	BLE	2402	Ant1	0.693	0.5	Pass
NVNT	BLE	2442	Ant1	0.703	0.5	Pass
NVNT	BLE	2480	Ant1	0.705	0.5	Pass













Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	
NVNT	BLE	2402	Ant1	1.052	
NVNT	BLE	2442	Ant1	1.055	
NVNT	BLE	2480	Ant1	1.06	














Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	-14.416	8	Pass
NVNT	BLE	2442	Ant1	-13.335	8	Pass
NVNT	BLE	2480	Ant1	-12.477	8	Pass













Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-52.47	-20	Pass
NVNT	BLE	2480	Ant1	-58.68	-20	Pass













Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-49.25	-20	Pass
NVNT	BLE	2442	Ant1	-48.96	-20	Pass
NVNT	BLE	2480	Ant1	-41.29	-20	Pass









Tx. Spurious NVNT BLE 2480MHz Ant1 Ref

Mar 20, 2024 11:01:00 PM



