



RF Test Report

For

Applicant Name: Shenzhen Ucalcul Technology Co., Ltd
Address: 401, Building A, Jiewei Industrial City Phase III, Shangmugu, Pinghu Street, Longgang District, Shenzhen
EUT Name: AEROPAD
Brand Name: N/A
Model Number: UNP200
Serial Model Number: UNP100, UNP207, UNP222, UA14P, UA14L, UA14R


Issued By

Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Report Number: BTF240319R00203
Test Standards: 47 CFR Part 15.247

Test Conclusion: Pass
FCC ID: 2BDJ4-UNP200
Test Date: 2024-03-20 to 2024-04-10
Date of Issue: 2024-04-12

Prepared By:


Chris Liu / Project Engineer

Date:

2024-04-12

Approved By:



Date:

Ryan.CJ / EMC Manager
2024-04-12

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2024-04-12	Original

Note: Once the revision has been made, then previous versions reports are invalid.

Table of Contents

1	INTRODUCTION	5
1.1	Identification of Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Announcement	5
2	PRODUCT INFORMATION	6
2.1	Application Information	6
2.2	Manufacturer Information.....	6
2.3	Factory Information	6
2.4	General Description of Equipment under Test (EUT)	6
2.5	Technical Information	6
3	SUMMARY OF TEST RESULTS	7
3.1	Test Standards.....	7
3.2	Uncertainty of Test	7
3.3	Summary of Test Result	7
4	TEST CONFIGURATION	8
4.1	Test Equipment List	8
4.2	Test Auxiliary Equipment	10
4.3	Test Modes.....	10
5	EVALUATION RESULTS (EVALUATION)	11
5.1	Antenna requirement	11
5.1.1	Conclusion:.....	11
6	RADIO SPECTRUM MATTER TEST RESULTS (RF)	12
6.1	Conducted Emission at AC power line	12
6.1.1	E.U.T. Operation:	12
6.1.2	Test Setup Diagram:.....	12
6.1.3	Test Data:	13
6.2	Occupied Bandwidth	15
6.2.1	E.U.T. Operation:	15
6.2.2	Test Setup Diagram:.....	15
6.2.3	Test Data:	15
6.3	Maximum Conducted Output Power	16
6.3.1	E.U.T. Operation:	16
6.3.2	Test Setup Diagram:.....	16
6.3.3	Test Data:	16
6.4	Power Spectral Density	17
6.4.1	E.U.T. Operation:	17
6.4.2	Test Setup Diagram:.....	17
6.4.3	Test Data:	17
6.5	Emissions in non-restricted frequency bands	18
6.5.1	E.U.T. Operation:	18
6.5.2	Test Setup Diagram:.....	18
6.5.3	Test Data:	18
6.6	Band edge emissions (Radiated)	19
6.6.1	E.U.T. Operation:	19
6.6.2	Test Setup Diagram:.....	19
6.6.3	Test Data:	20
6.7	Emissions in frequency bands (below 1GHz)	21
6.7.1	E.U.T. Operation:	21
6.7.2	Test Setup Diagram:.....	21

6.7.3	Test Data:	22
6.8	Emissions in frequency bands (above 1GHz)	24
6.8.1	E.U.T. Operation:	24
6.8.2	Test Setup Diagram:	24
6.8.3	Test Data:	25
7	TEST SETUP PHOTOS	27
8	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	29
	APPENDIX.....	30

1 Introduction

1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

1.2 Identification of the Responsible Testing Location

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130
FCC Registration Number:	518915
Designation Number:	CN1330

1.3 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 Product Information

2.1 Application Information

Company Name:	Shenzhen Ucalcul Technology Co., Ltd
Address:	401, Building A, Jiewei Industrial City Phase III, Shangmugu, Pinghu Street, Longgang District, Shenzhen

2.2 Manufacturer Information

Company Name:	Shenzhen Ucalcul Technology Co., Ltd
Address:	401, Building A, Jiewei Industrial City Phase III, Shangmugu, Pinghu Street, Longgang District, Shenzhen

2.3 Factory Information

Company Name:	Shenzhen Ucalcul Technology Co., Ltd
Address:	401, Building A, Jiewei Industrial City Phase III, Shangmugu, Pinghu Street, Longgang District, Shenzhen

2.4 General Description of Equipment under Test (EUT)

EUT Name:	AEROPAD
Test Model Number:	UNP200
Series Model Number:	UNP100, UNP207, UNP222, UA14P, UA14L, UA14R
Description of Model name differentiation:	Only the model name is different, everything else is the same
Hardware Version:	N/A
Software Version:	N/A

2.5 Technical Information

Power Supply:	DC 7.6V from battery or DC12V from Adapter with AC 120V/60Hz
Power Adaptor:	Model:RJT-AS120300 Input:100-240v~50/60Hz 1.0A Output:12.0V==3.0A 36.0W
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz; 802.11n(HT40): 2422MHz to 2452MHz
Number of Channels:	802.11b/g/n(HT20): 11 Channels; 802.11n(HT40): 7 Channels
Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n(HT20 and HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type:	PIFA ANT, MIMO:2*1
Antenna Gain [#] :	ANT1:1.96dBi ANT2; 2.12dBi
Note:	[#] : The antenna gain provided by the applicant, and the laboratory will not be responsible for the accumulated calculation results which covers the information provided by the applicant.
Bluetooth Version:	5.0

3 Summary of Test Results

3.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

3.2 Uncertainty of Test

Item	Measurement Uncertainty
Conducted Emission (150 kHz-30 MHz)	±2.64dB
Occupied Bandwidth	±69kHz
Transmitter Power, Conducted	±0.87dB
Power Spectral Density	±0.69dB
Conducted Spurious Emissions	±0.95dB
Radiated Spurious Emissions (above 1GHz)	1-6GHz: ±3.94dB 6-18GHz: ±4.16dB
Radiated Spurious Emissions (30M - 1GHz)	±4.12dB

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.3 Summary of Test Result

Item	Standard	Requirement	Result
Antenna requirement	47 CFR Part 15.247	47 CFR 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15.247	47 CFR 15.207(a)	Pass
Occupied Bandwidth	47 CFR Part 15.247	47 CFR 15.247(a)(2)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	47 CFR 15.247(b)(3)	Pass
Power Spectral Density	47 CFR Part 15.247	47 CFR 15.247(e)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass

4 Test Configuration

4.1 Test Equipment List

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Pulse Limiter	SCHWARZBECK	VTSD 9561-F	00953	/	/
Coaxial Switcher	SCHWARZBECK	CX210	CX210	/	/
V-LISN	SCHWARZBECK	NSLK 8127	01073	2023-11-16	2024-11-15
LISN	AFJ	LS16/110VAC	16010020076	2023-11-16	2024-11-15
EMI Receiver	ROHDE&SCHWARZ	ESCI3	101422	2023-11-15	2024-11-14

Occupied Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in non-restricted frequency bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	/	/
RF Sensor Unit	Techy	TR1029-2	/	/	/
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	/	/
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

Band edge emissions (Radiated) Emissions in frequency bands (below 1GHz) Emissions in frequency bands (above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-11-16	2024-11-15
Preamplifier	SCHWARZBECK	BBV9744	00246	/	/
RE Cable	REBES Talent	UF1-SMASMAM-10m	21101566	/	/
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	/	/
RE Cable	REBES Talent	UF1-SMASMAM-1m	21101568	/	/
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	/	/
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2023-11-13	2024-11-12
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI7	101032	2023-11-16	2024-11-15
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2023-11-16	2024-11-15
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Broadband Preamplifier	SCHWARZBECK	BBV9718D	00008	2023-11-16	2024-11-15
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2023-11-16	2024-11-15
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2023-11-13	2024-11-12

4.2 Test Auxiliary Equipment

The EUT was tested as an independent device.

4.3 Test Modes

No.	Test Modes	Description
TM1	802.11b mode	Keep the EUT in 802.11b transmitting mode.
TM2	802.11g mode	Keep the EUT in 802.11g transmitting mode.
TM3	802.11n(HT20) mode	Keep the EUT in 802.11n(HT20) transmitting mode.
TM4	802.11n(HT40) mode	Keep the EUT in 802.11n(HT40) transmitting mode.


5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:

Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

5.1.1 Conclusion:



6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Method:	ANSI C63.10-2013 section 6.2		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
*Decreases with the logarithm of the frequency.			
Procedure:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

6.1.1 E.U.T. Operation:


Operating Environment:	
Temperature:	25.7 °C
Humidity:	48.1 %
Atmospheric Pressure:	1010 mbar

6.1.2 Test Setup Diagram:



6.1.3 Test Data:


TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 20 / Mode:802.11b /Ch:M



No.	Frequency (MHz)	Reading (dBuV)	Factor ()	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2714	34.76	10.56	45.32	51.07	-5.75	AVG	P	
2	0.2760	44.24	10.56	54.80	60.94	-6.14	QP	P	
3	0.4830	39.41	10.09	49.50	56.29	-6.79	QP	P	
4 *	0.4830	31.08	10.09	41.17	46.29	-5.12	AVG	P	
5	0.6585	40.86	10.00	50.86	56.00	-5.14	QP	P	
6	0.6809	25.85	9.99	35.84	46.00	-10.16	AVG	P	
7	1.0230	19.15	10.66	29.81	46.00	-16.19	AVG	P	
8	1.0410	32.35	10.66	43.01	56.00	-12.99	QP	P	
9	2.2830	31.53	10.67	42.20	56.00	-13.80	QP	P	
10	2.2830	17.13	10.67	27.80	46.00	-18.20	AVG	P	
11	18.1770	25.22	11.01	36.23	50.00	-13.77	AVG	P	
12	18.4875	35.18	11.02	46.20	60.00	-13.80	QP	P	

Note:Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 20 / Mode:802.11b; Ch:M



No.	Frequency (MHz)	Reading (dBuV)	Factor ()	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2714	31.72	10.56	42.28	51.07	-8.79	AVG	P	
2	0.2895	45.81	10.56	56.37	60.54	-4.17	QP	P	
3	0.3525	29.19	10.22	39.41	48.90	-9.49	AVG	P	
4	0.3750	40.01	10.19	50.20	58.39	-8.19	QP	P	
5	0.4875	29.38	10.08	39.46	46.21	-6.75	AVG	P	
6 *	0.4965	42.55	10.07	52.62	56.06	-3.44	QP	P	
7	0.8970	26.52	9.78	36.30	46.00	-9.70	AVG	P	
8	0.9015	38.48	10.67	49.15	56.00	-6.85	QP	P	
9	1.8960	39.20	10.68	49.88	56.00	-6.12	QP	P	
10	1.9500	27.63	10.68	38.31	46.00	-7.69	AVG	P	
11	3.9120	26.65	10.67	37.32	46.00	-8.68	AVG	P	
12	4.2000	37.08	10.69	47.77	56.00	-8.23	QP	P	

Note: Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits


6.2 Occupied Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Method:	ANSI C63.10-2013, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Procedure:	<ul style="list-style-type: none"> a) Set RBW = 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.2.1 E.U.T. Operation:

Operating Environment:	
Temperature:	24.3 °C
Humidity:	50 %
Atmospheric Pressure:	1010 mbar

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

Please Refer to Appendix for Details.


6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Method:	ANSI C63.10-2013, section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Procedure:	ANSI C63.10-2013, section 11.9.1 Maximum peak conducted output power

6.3.1 E.U.T. Operation:

Operating Environment:	
Temperature:	24.3 °C
Humidity:	50 %
Atmospheric Pressure:	1010 mbar

6.3.2 Test Setup Diagram:



6.3.3 Test Data:

Please Refer to Appendix for Details.


6.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Method:	ANSI C63.10-2013, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Procedure:	ANSI C63.10-2013, section 11.10, Maximum power spectral density level in the fundamental emission

6.4.1 E.U.T. Operation:

Operating Environment:	
Temperature:	24.3 °C
Humidity:	50 %
Atmospheric Pressure:	1010 mbar

6.4.2 Test Setup Diagram:



6.4.3 Test Data:

Please Refer to Appendix for Details.


6.5 Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d), 15.209, 15.205
Test Method:	ANSI C63.10-2013 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Procedure:	ANSI C63.10-2013 Section 11.11.1, Section 11.11.2, Section 11.11.3

6.5.1 E.U.T. Operation:

Operating Environment:	
Temperature:	24.3 °C
Humidity:	50 %
Atmospheric Pressure:	1010 mbar

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

Please Refer to Appendix for Details.


6.6 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Method:	ANSI C63.10-2013 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>			
Procedure:	ANSI C63.10-2013 section 6.10.5.2		

6.6.1 E.U.T. Operation:

Operating Environment:	
Temperature:	22.7 °C
Humidity:	52.3 %
Atmospheric Pressure:	1010 mbar

6.6.2 Test Setup Diagram:



6.6.3 Test Data:

All mode are tested, and the report only shows the worst mode data of 802.11b

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz /802.11b / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	64.97	-30.59	34.38	74.00	-39.62	peak	P
2 *	2390.000	65.55	-30.49	35.06	74.00	-38.94	peak	P

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz /802.11b / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	65.15	-30.59	34.56	74.00	-39.44	peak	P
2 *	2390.000	65.52	-30.49	35.03	74.00	-38.97	peak	P

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / 802.11b / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2483.500	67.03	-30.39	36.64	74.00	-37.36	peak	P
2	2500.000	65.37	-30.37	35.00	74.00	-39.00	peak	P

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz /802.11b / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2483.500	67.18	-30.39	36.79	74.00	-37.21	peak	P
2	2500.000	66.47	-30.37	36.10	74.00	-37.90	peak	P

Note: :Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits


6.7 Emissions in frequency bands (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>			
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.7.1 E.U.T. Operation:


Operating Environment:	
Temperature:	22.7 °C
Humidity:	52.3 %
Atmospheric Pressure:	1010 mbar

6.7.2 Test Setup Diagram:



6.7.3 Test Data:


TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / Mode:802.11b / BW:20M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	32.6340	37.67	-18.50	19.17	40.00	-20.83	QP	P
2	58.2030	28.54	-18.20	10.34	40.00	-29.66	QP	P
3	91.8161	44.04	-29.58	14.46	43.50	-29.04	QP	P
4	164.3300	41.94	-27.65	14.29	43.50	-29.21	QP	P
5	264.2820	42.83	-25.73	17.10	46.00	-28.90	QP	P
6 *	545.1825	47.25	-21.61	25.64	46.00	-20.36	QP	P

Note: Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / Mode:802.11b / BW:20M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	31.5645	42.18	-20.71	21.47	40.00	-18.53	QP	P
2	64.5460	34.13	-20.08	14.05	40.00	-25.95	QP	P
3	92.1386	45.73	-29.52	16.21	43.50	-27.29	QP	P
4	135.7440	43.07	-27.91	15.16	43.50	-28.34	QP	P
5	239.9873	43.42	-25.94	17.48	46.00	-28.52	QP	P
6	541.3723	45.91	-21.57	24.34	46.00	-21.66	QP	P

N Note:Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits


6.8 Emissions in frequency bands (above 1GHz)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>			
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.8.1 E.U.T. Operation:

Operating Environment:	
Temperature:	22.7 °C
Humidity:	52.3 %
Atmospheric Pressure:	1010 mbar

6.8.2 Test Setup Diagram:



6.8.3 Test Data:

All mode are tested, and the report only shows the worst mode data of 802.11b

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / 802.11b / CH: L

No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	P/F
1	4824.000	62.54	-27.73	34.81	74.00	-39.19	peak	P
2	7236.000	62.25	-24.84	37.41	74.00	-36.59	peak	P
3	9648.000	63.69	-23.74	39.95	74.00	-34.05	peak	P

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz /802.11b / CH: L

No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	P/F
1	4824.000	65.45	-27.73	37.72	74.00	-36.28	peak	P
2	7236.000	68.27	-24.84	43.43	74.00	-30.57	peak	P
3	9648.000	69.17	-23.74	45.43	74.00	-28.57	peak	P

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / 802.11b / CH: M

No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	P/F
1	4874.000	63.10	-27.73	35.37	74.00	-38.63	peak	P
2	7311.000	62.81	-24.84	37.97	74.00	-36.03	peak	P
3	9748.000	64.25	-23.74	40.51	74.00	-33.49	peak	P

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / 802.11b / CH: M

No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	P/F
1	4874.000	66.01	-27.73	38.28	74.00	-35.72	peak	P
2	7311.000	68.83	-24.84	43.99	74.00	-30.01	peak	P
3	9748.000	69.73	-23.74	45.99	74.00	-28.01	peak	P

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / 802.11b / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	4924.000	63.56	-27.37	36.19	74.00	-37.81	peak	P
2	7386.000	63.27	-24.68	38.59	74.00	-35.41	peak	P
3	9848.000	64.71	-23.99	40.72	74.00	-33.28	peak	P


TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / 802.11b / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	4924.000	66.41	-27.37	39.04	74.00	-34.96	peak	P
2	7386.000	69.23	-24.68	44.55	74.00	-29.45	peak	P
3	9848.000	70.13	-23.99	46.14	74.00	-27.86	peak	P

Note: Reading=Receiver reading
Factor=Antenna factor+Cable loss
Level=Reading+Factor
Limit=Limit stated in standard
Margin=Measurement-Limits

7 Test Setup Photos

Conducted Emission at AC power line



Band edge emissions (Radiated)
Emissions in frequency bands (above 1GHz)



Emissions in frequency bands (below 1GHz)



8 EUT Constructional Details (EUT Photos)

Please refer to the test report No. BTF240319R00201

Appendix


1. Duty Cycle

1.1 Ant1


1.1.1 Test Result

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	8.353	8.400	99.44	0.02	0.04
		2437	8.350	8.396	99.45	0.02	0.04
		2462	8.350	8.396	99.45	0.02	0.04
802.11g	SISO	2412	0.192	0.240	80.00	0.97	0.43
		2437	0.192	0.239	80.33	0.95	0.06
		2462	0.192	0.240	80.00	0.97	0.55
802.11n (HT20)	SISO	2412	0.213	0.261	81.61	0.88	0.46
		2437	0.215	0.259	83.01	0.81	0.20
		2462	0.213	0.260	81.92	0.87	0.26
802.11n (HT40)	SISO	2422	0.201	0.248	81.05	0.91	0.20
		2437	0.200	0.247	80.97	0.92	0.20
		2452	0.200	0.247	80.97	0.92	0.23
802.11n (HT20)	MIMO	2412	0.212	0.260	81.54	0.89	0.33
		2437	4.017	4.064	98.84	0.05	0.03
		2462	4.016	4.063	98.84	0.05	0.04
802.11n (HT40)	MIMO	2422	3.993	4.041	98.81	0.05	0.03
		2437	3.993	4.042	98.79	0.05	0.07
		2452	3.992	4.039	98.84	0.05	0.03


1.1.2 Test Graph




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV





802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV








802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV







802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV




2. Bandwidth

2.1 OBW


2.1.1 Test Result

Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	13.407	/	Pass
		2437	1	13.403	/	Pass
		2462	1	13.426	/	Pass
802.11g	SISO	2412	1	17.439	/	Pass
		2437	1	17.496	/	Pass
		2462	1	17.420	/	Pass
802.11n (HT20)	SISO	2412	1	18.401	/	Pass
		2437	1	18.354	/	Pass
		2462	1	18.486	/	Pass
802.11n (HT40)	SISO	2422	1	36.263	/	Pass
		2437	1	36.220	/	Pass
		2452	1	36.211	/	Pass
802.11n (HT20)	MIMO	2412	1	18.481	/	Pass
		2437	1	18.431	/	Pass
		2462	1	18.482	/	Pass
802.11n (HT40)	MIMO	2422	1	36.271	/	Pass
		2437	1	36.262	/	Pass
		2452	1	36.224	/	Pass


2.1.2 Test Graph




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV





802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV







802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV




2.2 6dB BW


2.2.1 Test Result

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	10.153	>=0.5	Pass
		2437	1	10.146	>=0.5	Pass
		2462	1	10.152	>=0.5	Pass
802.11g	SISO	2412	1	15.167	>=0.5	Pass
		2437	1	15.167	>=0.5	Pass
		2462	1	15.170	>=0.5	Pass
802.11n (HT20)	SISO	2412	1	15.168	>=0.5	Pass
		2437	1	15.167	>=0.5	Pass
		2462	1	15.174	>=0.5	Pass
802.11n (HT40)	SISO	2422	1	35.133	>=0.5	Pass
		2437	1	35.136	>=0.5	Pass
		2452	1	35.129	>=0.5	Pass
802.11n (HT20)	MIMO	2412	1	15.166	>=0.5	Pass
		2437	1	15.166	>=0.5	Pass
		2462	1	15.174	>=0.5	Pass
802.11n (HT40)	MIMO	2422	1	35.088	>=0.5	Pass
		2437	1	35.094	>=0.5	Pass
		2452	1	35.105	>=0.5	Pass


2.2.2 Test Graph




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV





802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV







802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV




3. Maximum Conducted Output Power



3.1 Power

3.1.1 Test Result


Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)				Verdict
			ANT1	ANT2	MIMO	Limit	
802.11b	SISO	2412	15.21	14.25	/	<=30	Pass
		2437	15.28	13.87	/	<=30	Pass
		2462	15.16	14.03	/	<=30	Pass
802.11g	SISO	2412	14.22	13.37	/	<=30	Pass
		2437	14.25	12.98	/	<=30	Pass
		2462	14.20	13.10	/	<=30	Pass
802.11n (HT20)	SISO	2412	13.90	13.13	/	<=30	Pass
		2437	14.00	12.69	/	<=30	Pass
		2462	13.86	12.80	/	<=30	Pass
802.11n (HT40)	SISO	2422	14.68	13.60	/	<=30	Pass
		2437	14.58	13.66	/	<=30	Pass
		2452	14.61	13.54	/	<=30	Pass
802.11n (HT20)	MIMO	2412	13.82	13.03	16.45	<=30	Pass
		2437	13.85	12.68	16.31	<=30	Pass
		2462	13.76	12.83	16.33	<=30	Pass
802.11n (HT40)	MIMO	2422	14.59	13.66	17.16	<=30	Pass
		2437	14.44	13.64	17.07	<=30	Pass
		2452	14.50	13.52	17.05	<=30	Pass
Note1: Antenna Gain: Ant1: 1.96dBi; Ant2: 2.12dBi;							
Note2: Directional Gain: Uncorrelated(Directional Gain = Ant Gain)							

3.1.2 Test Graph







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant2 (SISO)_NTNV





802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV








802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV







802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant2 (SISO)_NTNV





802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (SISO)_NTNV







802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant2 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant2 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant2 (MIMO)_NTNV



4. Maximum Power Spectral Density


4.1 PSD



4.1.1 Test Result



Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)				Verdict
			ANT1	ANT2	MIMO	Limit	
802.11b	SISO	2412	-9.95	-11.35	/	<=8	Pass
		2437	-10.79	-12.85	/	<=8	Pass
		2462	-10.60	-11.43	/	<=8	Pass
802.11g	SISO	2412	-18.12	-18.75	/	<=8	Pass
		2437	-19.23	-19.26	/	<=8	Pass
		2462	-19.44	-19.68	/	<=8	Pass
802.11n (HT20)	SISO	2412	-18.94	-19.02	/	<=8	Pass
		2437	-17.97	-19.79	/	<=8	Pass
		2462	-18.92	-18.66	/	<=8	Pass
802.11n (HT40)	SISO	2422	-21.68	-22.63	/	<=8	Pass
		2437	-20.48	-22.87	/	<=8	Pass
		2452	-21.19	-22.40	/	<=8	Pass
802.11n (HT20)	MIMO	2412	-18.17	-19.56	-17.10	<=8	Pass
		2437	-19.29	-20.28	-17.56	<=8	Pass
		2462	-18.75	-20.00	-16.86	<=8	Pass
802.11n (HT40)	MIMO	2422	-21.71	-21.47	-19.44	<=8	Pass
		2437	-21.53	-21.93	-19.84	<=8	Pass
		2452	-21.57	-21.67	-19.47	<=8	Pass

Note1: Antenna Gain: Ant1: 1.96dBi; Ant2: 2.12dBi;
Note2: Directional Gain: Uncorrelated(Directional Gain = Ant Gain)


4.1.2 Test Graph









802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant2 (SISO)_NTNV





802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV









802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV





802.11n(HT20)_MCH_2437MHz_Ant2 (SISO)_NTNV












802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant2 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_MIMO_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_MIMO_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_MIMO_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV





802.11n(HT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_MIMO_NTNV







802.11n(HT40)_MCH_2437MHz_MIMO_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant2 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_MIMO_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands


5.1 Ref



5.1.1 Test Result

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
802.11b	SISO	2412	1	-7.69
			2	-7.72
		2437	1	-7.55
			2	-7.70
		2462	1	-7.61
			2	-7.55
802.11g	SISO	2412	1	-8.22
			2	-8.05
		2437	1	-8.31
			2	-8.02
		2462	1	-7.74
			2	-8.23
802.11n (HT20)	SISO	2412	1	-8.37
			2	-8.01
		2437	1	-8.13
			2	-8.35
		2462	1	-8.21
			2	-8.57
802.11n (HT40)	SISO	2422	1	-8.50
			2	-9.78
		2437	1	-8.68
			2	-9.46
		2452	1	-8.48
			2	-9.18
802.11n (HT20)	MIMO	2412	1	-8.37
			2	-8.48
		2437	1	-8.34
			2	-8.35
		2462	1	-8.00
			2	-8.41
802.11n (HT40)	MIMO	2422	1	-8.55
			2	-9.28
		2437	1	-8.39
			2	-9.05
		2452	1	-8.89
			2	-9.61


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.

5.1.2 Test Graph







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant2 (SISO)_NTNV





802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV







802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant2 (SISO)_NTNV





802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (SISO)_NTNV







802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant2 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant2 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant2 (MIMO)_NTNV




5.2 CSE

5.2.1 Test Result


Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	1	-7.55	-27.55	Pass
			2	-7.55	-27.55	Pass
		2437	1	-7.55	-27.55	Pass
			2	-7.55	-27.55	Pass
		2462	1	-7.55	-27.55	Pass
			2	-7.55	-27.55	Pass
802.11g	SISO	2412	1	-7.74	-27.74	Pass
			2	-8.02	-28.02	Pass
		2437	1	-7.74	-27.74	Pass
			2	-8.02	-28.02	Pass
		2462	1	-7.74	-27.74	Pass
			2	-8.02	-28.02	Pass
802.11n (HT20)	SISO	2412	1	-8.13	-28.13	Pass
			2	-8.01	-28.01	Pass
		2437	1	-8.13	-28.13	Pass
			2	-8.01	-28.01	Pass
		2462	1	-8.13	-28.13	Pass
			2	-8.01	-28.01	Pass
802.11n (HT40)	SISO	2422	1	-8.48	-28.48	Pass
			2	-9.18	-29.18	Pass
		2437	1	-8.48	-28.48	Pass
			2	-9.18	-29.18	Pass
		2452	1	-8.48	-28.48	Pass
			2	-9.18	-29.18	Pass
802.11n (HT20)	MIMO	2412	1	-8.00	-28.00	Pass
			2	-8.35	-28.35	Pass
		2437	1	-8.00	-28.00	Pass
			2	-8.35	-28.35	Pass
		2462	1	-8.00	-28.00	Pass
			2	-8.35	-28.35	Pass
802.11n (HT40)	MIMO	2422	1	-8.39	-28.39	Pass
			2	-9.05	-29.05	Pass
		2437	1	-8.39	-28.39	Pass
			2	-9.05	-29.05	Pass
		2452	1	-8.39	-28.39	Pass
			2	-9.05	-29.05	Pass

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.


5.2.2 Test Graph




802.11b_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11b_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV







802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV









802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV







802.11n(HT20)_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (SISO)_NTNV









802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant2 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant2 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant2 (MIMO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant2 (MIMO)_NTNV



6. Form731

6.1 Form731

6.1.1 Test Result

Lower Freq (MHz)	High Freq (MHz)	MAX Power (W)	MAX Power (dBm)
2412	2462	0.0442	16.45
2422	2452	0.0520	17.16



Test Report Number: BTF240319R00203



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, China

www.btf-lab.com

-- END OF REPORT --