



<b>Prüfbericht-Nr.:</b> <i>Test report no.:</i>	CN24F839 001	<b>Auftrags-Nr.:</b> <i>Order no.:</i>	48243464	Seite 1 von 28 Page 1 of 28
<b>Kunden-Referenz-Nr.:</b> <i>Client reference no.:</i>	N/A	<b>Auftragsdatum:</b> <i>Order date:</i>	2024-01-29	
<b>Auftraggeber:</b> <i>Client:</i>	HP Inc. 3390 East Harmony Road, Fort Collins, CO 80528, USA			
<b>Prüfgegenstand:</b> <i>Test item:</i>	Wireless Keyboard			
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type no.:</i>	HXKB234			
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	FCC Part 15C Test report (BLE)			
<b>Prüfgrundlage:</b> <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247			
<b>Wareneingangsdatum:</b> <i>Date of sample receipt:</i>	2024-01-04			
<b>Prüfmuster-Nr.:</b> <i>Test sample no.:</i>	A003636709-032 A003636709-029			
<b>Prüfzeitraum:</b> <i>Testing period:</i>	2024-01-12 - 2024-02-06			
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	EMC/RF Taipei Testing Site			
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	Taipei Testing Laboratories			
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass			
<b>zusammengestellt von:</b> <i>compiled by:</i>	 Ryan Chen	<b>genehmigt von:</b> <i>authorized by:</i>	 Brenda Chen	
<b>Datum:</b> <i>Date:</i>	2024-03-01	<b>Ausstellungsdatum:</b> <i>Issue date:</i>	2024-03-01	
<b>Stellung / Position:</b>	Senior Project Manager	<b>Stellung / Position:</b>	Senior Project Manager	
<b>Sonstiges / Other:</b>				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend N/A = nicht anwendbar	4 = ausreichend N/T = nicht getestet
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory N/A = not applicable	4 = sufficient N/T = not tested
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN24F839 001  
Test report no.:

Seite 2 von 28  
Page 2 of 28

**Anmerkungen**  
Remarks

1	<p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>
2	<p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: <a href="http://go.tuv.com/digital-signature">go.tuv.com/digital-signature</a></p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: <a href="http://go.tuv.com/digital-signature">go.tuv.com/digital-signature</a></i></p>
3	<p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>
4	<p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>

Prüfbericht-Nr.: CN24F839 001  
Test report no.:Seite 3 von 28  
Page 3 of 28

## TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.247(b) & 15.203	Antenna Requirement	Pass
5.1.2	15.247(b)(3)	Peak Output Power	Pass
5.1.3	15.247(a)(2)	6 dB Bandwidth	Pass
5.1.3	2.1049	99% Occupied Bandwidth	Pass
5.1.4	15.247(e)	Power Spectral Density	Pass
5.1.5	15.247(d)	Conducted Spurious Emissions and Band Edges	Pass
5.1.6	15.247(d) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass
5.2.1	15.207	Mains Conducted Emission	Pass

**Note:** Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

**Prüfbericht-Nr.: CN24F839 001**  
*Test report no.:*

 Seite 4 von 28  
 Page 4 of 28

## Contents

<b>HISTORY OF THIS TEST REPORT .....</b>	<b>6</b>
<b>1. GENERAL REMARKS .....</b>	<b>7</b>
<b>1.1 COMPLEMENTARY MATERIALS.....</b>	<b>7</b>
<b>1.2 DECISION RULE OF CONFORMITY .....</b>	<b>7</b>
<b>2. TEST SITES .....</b>	<b>8</b>
<b>2.1 TEST LABORATORY .....</b>	<b>8</b>
<b>2.2 TEST FACILITY.....</b>	<b>8</b>
<b>2.3 TRACEABILITY .....</b>	<b>9</b>
<b>2.4 CALIBRATION .....</b>	<b>9</b>
<b>2.5 MEASUREMENT UNCERTAINTY .....</b>	<b>9</b>
<b>3. GENERAL PRODUCT INFORMATION.....</b>	<b>10</b>
<b>3.1 PRODUCT FUNCTION AND INTENDED USE .....</b>	<b>10</b>
<b>3.2 SYSTEM DETAILS AND RATINGS.....</b>	<b>10</b>
<b>3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS .....</b>	<b>11</b>
<b>3.4 SUBMITTED DOCUMENTS.....</b>	<b>11</b>
<b>4. TEST SET-UP AND OPERATION MODES .....</b>	<b>12</b>
<b>4.1 PRINCIPLE OF CONFIGURATION SELECTION .....</b>	<b>12</b>
<b>4.2 CARRIER FREQUENCY AND CHANNEL.....</b>	<b>12</b>
<b>4.3 TEST OPERATION AND TEST SOFTWARE.....</b>	<b>13</b>
<b>4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....</b>	<b>14</b>
<b>4.5 TEST SETUP DIAGRAM .....</b>	<b>15</b>
<b>5. TEST RESULTS .....</b>	<b>16</b>
<b>5.1 TRANSMITTER REQUIREMENT &amp; TEST SUITES .....</b>	<b>16</b>
5.1.1 <i>Antenna Requirement .....</i>	<i>16</i>
5.1.2 <i>Peak Output Power .....</i>	<i>17</i>
5.1.3 <i>6 dB Bandwidth and 99% Occupied Bandwidth.....</i>	<i>19</i>
5.1.4 <i>Power Spectral Density.....</i>	<i>20</i>
5.1.5 <i>Conducted Spurious Emissions and Frequency Band Edges Measured in 100kHz Bandwidth .....</i>	<i>21</i>
5.1.6 <i>Radiated Spurious Emissions and Band Edges .....</i>	<i>22</i>
<b>5.2 MAINS EMISSION .....</b>	<b>27</b>
5.2.1 <i>Mains Conducted Emission.....</i>	<i>27</i>

Prüfbericht-Nr.: **CN24F839 001**  
Test report no.:

Seite 5 von 28  
Page 5 of 28

**APPENDIX A - TEST RESULT OF CONDUCTED**

**APPENDIX B - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION**

**APPENDIX SP - PHOTOGRAPHS OF TEST SETUP**

**APPENDIX EP - PHOTOGRAPHS OF EUT**

Prüfbericht-Nr.: **CN24F839 001**  
Test report no.:

Seite 6 von 28  
Page 6 of 28

## HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
R01	Original Release	2024-03-01

Prüfbericht-Nr.: **CN24F839 001**  
Test report no.:Seite 7 von 28  
Page 7 of 28

# 1. General Remarks

## 1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

**Appendix A - Test Result of Conducted**

**Appendix B - Test Result of Radiated Emissions & Mains Conducted Emission**

**Appendix SP - Photographs of Test Setup**

**Appendix EP - Photographs of EUT**

### Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart C Section 15.247
FCC 47CFR Part 2: Subpart J Section 2.1049
ANSI C63.10:2013
KDB 558074 D01 15.247 Meas Guidance v05r02

## 1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

Prüfbericht-Nr.: **CN24F839 001**  
Test report no.:

Seite 8 von 28  
Page 8 of 28

## 2. Test Sites

### 2.1 Test Laboratory

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.  
Taipei City 105  
Taiwan (R.O.C.)

### 2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,  
New Taipei City 244  
Taiwan (R.O.C.)  
FCC Registration No.: 180491  
ISED Registration No.: 25563



Prüfbericht-Nr.: **CN24F839 001**  
Test report no.:Seite 9 von 28  
Page 9 of 28

## 2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95% level of confidence.

### Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	$\pm 1.15$ dB
Radiated Emission (30 MHz ~ 200 MHz)	$\pm 1.30$ dB
Radiated Emission (200 MHz ~ 1 GHz)	$\pm 1.30$ dB
Radiated Emission (1 GHz ~ 18 GHz)	$\pm 1.54$ dB
Radiated Emission (18 GHz ~ 40 GHz)	$\pm 2.52$ dB
Mains Conducted Emission	$\pm 1.65$ dB

Prüfbericht-Nr.: CN24F839 001  
Test report no.:Seite 10 von 28  
Page 10 of 28

### 3. General Product Information

#### 3.1 Product Function and Intended Use

The EUT is a Wireless Keyboard. It contains a Bluetooth compatible module enabling the user to communicate data through a Wireless interface.

For details refer to the User Guide, Data Sheet and Circuit Diagram.

#### 3.2 System Details and Ratings

##### Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	Wireless Keyboard
Type Identification	HXKB234
FCC ID	B94-HXKB234

##### Technical Specification of EUT

Item	EUT information
Operating Frequency	2402 MHz ~ 2480 MHz
Channel Number	40
Data Rate	1Mbps, 2Mbps
Operation Voltage	3.8 Vdc
Modulation	GFSK
Maximum Output Power (mW)	0.96
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.4

Prüfbericht-Nr.: **CN24F839 001**  
Test report no.:

Seite 11 von 28  
Page 11 of 28

### **3.3 Noise Generating and Noise Suppressing Parts**

Refer to the Circuit Diagram.

### **3.4 Submitted Documents**

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

## 4. Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

#### Table for Parameters of Test Software Setting

Frequency (MHz)	Power Setting
2402	0
2440	0
2480	0

### 4.2 Carrier Frequency and Channel

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

**Prüfbericht-Nr.: CN24F839 001**  
*Test report no.:*

 Seite 13 von 28  
 Page 13 of 28

### 4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	nRF
---------------	-----

The samples were used as follows:

A003636709-032

A003636709-029

Full test was applied on all test modes, but only worst case was shown.

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
-	√	√	√	√	-

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when position on **Y-plane**.
2. "-" means no effect.

#### Antenna Port Conducted Measurement

- Pre-Scan full test was applied on all test modes, but only worst case was shown.
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402, 2440, 2480	1
-	2402 to 2480	2402, 2440, 2480	2

#### Radiated Spurious Emissions (Above 1 GHz)

- Pre-Scan full test was applied on all test modes, but only worst case was shown.
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402, 2440, 2480	1
-	2402 to 2480	2402, 2440, 2480	2

#### Radiated Spurious Emissions (Below 1 GHz)

- Pre-Scan full test was applied on all test modes, but only worst case was shown.
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402	1

#### Mains Conducted Emission

- Pre-Scan full test was applied on all test modes, but only worst case was shown.
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402	1

**Prüfbericht-Nr.: CN24F839 001**  
*Test report no.:*

 Seite 14 von 28  
 Page 14 of 28

**Test Condition**

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	23.5-25.2 °C	57.7-60.2 %	Blake Wang / Andy Chen
Radiated Spurious Emissions above 1 GHz	23.4-25.8 °C	55-59 %	Chuan Chu
Radiated Spurious Emissions below 1 GHz	23.4-25.8 °C	55-59 %	Chuan Chu
Mains Conducted Emission	19.1-25.9 °C	50.2-58.9 %	Roger Liao

## 4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

**Accessory of EUT**


No.	Product	Brand	Model	Description
-	Li-ion Battery	EVERPOWER	5455137V-R01	3.8 Vdc, 6000 mAh
A	USB Cable	SIYOTO	623-00291-00A	--
-	HyperX Pulsefire Haste 2 Mini USB Wireless Dongle	HYPERX	PF011WA	--

**Support Unit**


Support Unit					
No.	Description	Brand	Model	S/N	Remark
1	Adapter	OPPO	VC56JACH	J119492AC1009359	--

## 4.5 Test Setup Diagram

<Radiated Spurious Emissions mode>



<Mains Conducted Emission mode>



Prüfbericht-Nr.: **CN24F839 001**  
Test report no.:Seite 16 von 28  
Page 16 of 28

## 5. Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

**Requirement** Use of approved antennas only

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 3.26 dBi. The antenna is FPC antenna with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.  
Refer to EUT photo for details.




**Prüfbericht-Nr.: CN24F839 001**  
*Test report no.:*

 Seite 17 von 28  
 Page 17 of 28

### 5.1.2 Peak Output Power

**Limit** 1 watt (30 dBm)

**Kind of Test Site** Shielded room

**Test Setup**

**Test Instruments**

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2023/03/17	2024/03/16	2024/1/12	2024/2/6
Power Sensor	Anritsu	MA2411B	1725269	2023/03/17	2024/03/16	2024/1/12	2024/2/6

**Test Procedures**

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

**Prüfbericht-Nr.: CN24F839 001**  
*Test report no.:*
**Test Result**
**Peak Output Power**
**<1Mbps>**

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2402	-0.18	0.96	30
Middle Channel	2440	-0.78	0.84	30
High Channel	2480	-1.44	0.72	30

**<2Mbps>**

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2402	-0.23	0.95	30
Middle Channel	2440	-0.81	0.83	30
High Channel	2480	-1.45	0.72	30

**Average Power**
**<1Mbps>**

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2402	-0.41	0.91
Middle Channel	2440	-0.99	0.80
High Channel	2480	-1.68	0.68

**<2Mbps>**

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2402	-0.41	0.91
Middle Channel	2440	-0.99	0.80
High Channel	2480	-1.68	0.68


**Prüfbericht-Nr.: CN24F839 001**  
*Test report no.:*

 Seite 19 von 28  
 Page 19 of 28

### 5.1.3 6 dB Bandwidth and 99% Occupied Bandwidth

**Limit** The minimum 6 dB bandwidth shall be at least 500 kHz.

**Kind of Test Site** Shielded room

**Test Setup**

**Test Instruments**

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101512	2023/02/23	2024/02/22	2024/1/12	2024/2/6

**Test Procedure**

- a. Set resolution bandwidth (RBW) = 100 kHz
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- f. For 99% occupied bandwidth measurement, the transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

**Test Results**

Please refer to Appendix A.

**Prüfbericht-Nr.: CN24F839 001**  
*Test report no.:*


 Seite 20 von 28  
 Page 20 of 28

### 5.1.4 Power Spectral Density

**Limit**

The power spectral density shall not be greater than 8 dBm in any 3 kHz band.

**Kind of Test Site**                      Shielded room

**Test Setup**

**Test Instruments**

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101512	2023/02/23	2024/02/22	2024/1/12	2024/2/6

**Test Procedure**

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d. Set the VBW  $\geq 3 \times \text{RBW}$ .
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

**Test Results**

Please refer to Appendix A.

**Prüfbericht-Nr.: CN24F839 001**  
*Test report no.:*


 Seite 21 von 28  
 Page 21 of 28

### 5.1.5 Conducted Spurious Emissions and Frequency Band Edges Measured in 100kHz Bandwidth

**Limit**

20dB (below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.)

**Kind of Test Site**                      Shielded room

**Test Setup**

**Test Instruments**

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101512	2023/02/23	2024/02/22	2024/1/12	2024/2/6

**Test Procedure**

Measurement procedure REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Measurement procedure OOBE

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

**Test Results**

Please refer to Appendix A.

### 5.1.6 Radiated Spurious Emissions and Band Edges

#### Limit


Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.247(d).


**Kind of Test Site**                      3m Semi-Anechoic Chamber

#### Test Setup


##### <Radiated Emissions below 30 MHz>



##### <Radiated Emissions 30 MHz to 1 GHz>



<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

**Prüfbericht-Nr.: CN24F839 001**  
*Test report no.:*
**Test Instruments**

Test Period: 2024-02-02 ~ 2024-02-05

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Above 1 GHz					
Signal Analyzer	R&S	FSV40	101509	2023/4/26	2024/4/24
Horn Antenna	ETS-Lindgren	3117	00218931	2023/2/24	2024/2/23
HF-AMP + AC source	EMCI	EM01G18GA	980633	2024/1/24	2025/1/22
HF-AMP + AC source	EMCI	EMC184045SE	980657	2024/1/24	2025/1/22
Horn Antenna	SCHWARZBECK	BBHA 9170	00890	2023/5/4	2024/5/2
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A
30 MHz ~ 1 GHz					
Receiver	R&S	ESR7	102109	2023/2/24	2024/2/23
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2023/3/31	2024/3/29
LF-AMP	Agilent	8447D	2944A107722	2023/3/22	2024/3/20
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A
Below 30 MHz					
Receiver	R&S	ESR7	102109	2023/2/24	2024/2/23
Loop Antenna	SCHWARZBECK	FMZB 1519B	00215	2024/1/4	2025/1/3
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A



Prüfbericht-Nr.: **CN24F839 001**  
Test report no.:Seite 25 von 28  
Page 25 of 28**Test Procedures****For Radiated Emissions below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

## Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

**For Radiated Emissions above 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

## Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98 %) or 10 Hz (Duty cycle  $\geq 98$  %) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H) and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.
6. The emission levels of other frequencies (including the 10th harmonic of the highest fundamental frequency) are very lower than the limit and are not shown in the test report.

Prüfbericht-Nr.: **CN24F839 001**  
Test report no.:

Seite 26 von 28  
Page 26 of 28

### Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)

Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix B.

**Prüfbericht-Nr.: CN24F839 001**  
*Test report no.:*

 Seite 27 von 28  
 Page 27 of 28


## 5.2 Mains Emission

### 5.2.1 Mains Conducted Emission

**Limit**

Mains Conducted Emission as defined in §15.207 must comply with the mains conducted emission limits.

**Kind of Test Site**                      Shielded room

**Test Setup**

**Test Instruments**

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Two-Line V-Network	Rohde & Schwarz	ENV216	101938	2023/10/23	2024/10/21
EMI Test Receiver	R&S	ESCI	100797	2023/7/21	2024/7/19

Prüfbericht-Nr.: **CN24F839 001**  
Test report no.:

Seite 28 von 28  
Page 28 of 28

#### Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.

#### Test Results


Please refer to Appendix B.

## Appendix A: Test Results of Conducted Test

### Test Result of 6 dB Bandwidth


#### BLE\_1M

Channel	Channel Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2402	0.70	> 0.5	Pass
Middle Channel	2440	0.70	> 0.5	Pass
High Channel	2480	0.71	> 0.5	Pass



**BLE\_2M**


Channel	Channel Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2402	1.13	> 0.5	Pass
Middle Channel	2440	1.13	> 0.5	Pass
High Channel	2480	1.13	> 0.5	Pass



## Test Result of 99% Occupied Bandwidth


### BLE\_1M

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2402	1.05
Middle Channel	2440	1.05
High Channel	2480	1.05



**BLE\_2M**

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2402	2.04
Middle Channel	2440	2.05
High Channel	2480	2.05






## Test Result of Power Spectral Density


### BLE\_1M

Channel	Channel Frequency (MHz)	Power Density (dBm)	Limit (dBm)	Result
Low Channel	2402	-16.60	8	Pass
Middle Channel	2440	-17.07	8	Pass
High Channel	2480	-17.75	8	Pass




**BLE\_2M**


Channel	Channel Frequency (MHz)	Power Density (dBm)	Limit (dBm)	Result
Low Channel	2402	-19.14	8	Pass
Middle Channel	2440	-19.63	8	Pass
High Channel	2480	-20.25	8	Pass



### Test Result of Conducted Spurious Emissions


BLE\_1M




**BLE\_2M**


## Test Result of Conducted Band Edge

### BLE\_1M



### BLE\_2M



# Appendix B: Test Results of Radiated Spurious Emissions & Mains

## Conducted Emission Test

### Band Edges, 2.31GHz ~ 2.9GHz


#### BLE\_1M

##### Low Channel (Horizontal) Peak

##### Low Channel (Vertical) Peak




TÜV Rheinland Taiwan Ltd.  
No. 438-18, Sec. 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
1	Level	Read	Level	Factor	Limit	Over	Limit	APos	TPos	Remark	Pol/Phase	Note			
1	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg							
1	2366.76	52.66	15.39	37.27	74.00	-21.34	120	10	Peak	Horizontal					
2	2402.00	96.66	59.27	37.39	74.00	22.66	120	18	Peak	Horizontal					
3	2551.31	53.97	16.36	37.61	74.00	-20.03	120	10	Peak	Horizontal					



TÜV Rheinland Taiwan Ltd.  
No. 438-18, Sec. 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
1	Level	Read	Level	Factor	Limit	Over	Limit	APos	TPos	Remark	Pol/Phase	Note			
1	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg							
1	2348.47	52.53	15.32	37.21	74.00	-21.47	103	298	Peak	Vertical					
2	2402.00	92.58	55.19	37.39	74.00	18.58	103	298	Peak	Vertical					
3	2539.98	54.07	16.44	37.63	74.00	-19.93	103	298	Peak	Vertical					


BLE\_1M

Low Channel (Horizontal) Average

Low Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.  
No. 438-18, Sec 2, Penfiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2365.93	40.75	3.40	37.27	54.00	-13.25	120	10 Average	Horizontal	
2 *	2402.00	95.61	58.22	37.39	54.00	41.61	120	10 average	Horizontal	
3	2799.82	41.61	4.05	37.56	54.00	-12.39	120	10 Average	Horizontal	



TÜV Rheinland Taiwan Ltd.  
No. 438-18, Sec 2, Penfiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2355.55	40.42	3.18	37.24	54.00	-13.58	103	298 Average	Vertical	
2 *	2402.00	91.57	54.18	37.39	54.00	37.57	103	298 Average	Vertical	
3	2838.17	41.60	3.86	37.74	54.00	-12.40	103	298 Average	Vertical	


BLE\_1M

Middle Channel (Horizontal) Peak

Middle Channel (Vertical) Peak




TUV Rheinland Taiwan Ltd.  
No. 438-18, Sec 2, Fenfiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2374.19	52.44	15.14	37.30	74.00	-21.56	288	9	Peak	Horizontal	
2 *	2448.00	97.22	59.65	37.57	74.00	23.22	288	9	Peak	Horizontal	
3	2846.78	54.04	16.25	37.79	74.00	-19.96	288	9	Peak	Horizontal	



TUV Rheinland Taiwan Ltd.  
No. 438-18, Sec 2, Fenfiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2347.52	52.62	15.41	37.21	74.00	-21.38	111	300	Peak	Vertical	
2 *	2448.00	92.31	54.74	37.57	74.00	18.31	111	300	Peak	Vertical	
3	2507.06	54.65	16.98	37.67	74.00	-19.35	111	300	Peak	Vertical	




BLE\_1M

Middle Channel (Horizontal) Average

Middle Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.  
No. 438-18, Sec 2, Penfiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2385.28	40.02	3.49	37.33	54.00	-13.18	288	9 Average	Horizontal
2 *	2440.00	96.19	50.62	37.57	54.00	42.19	288	9 average	Horizontal
3	2893.98	41.68	3.48	38.20	54.00	-12.32	288	9 Average	Horizontal



TÜV Rheinland Taiwan Ltd.  
No. 438-18, Sec 2, Penfiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2385.05	40.67	3.34	37.33	54.00	-13.33	111	300 Average	Vertical
2 *	2440.00	91.24	53.67	37.57	54.00	37.24	111	300 Average	Vertical
3	2550.48	41.64	4.02	37.62	54.00	-12.36	111	300 Average	Vertical



BLE\_1M

High Channel (Horizontal) Peak

High Channel (Vertical) Peak

TÜVRheinland  
TUV Rheinland Taiwan Ltd.  
No. 438-18, Sec 2, Penfiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322

TÜVRheinland  
TUV Rheinland Taiwan Ltd.  
No. 438-18, Sec 2, Penfiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	2389.06	53.06	15.00	37.26	74.00	-20.94	186	299	Peak	Horizontal		
2 *	2488.00	96.94	59.29	37.65	74.00	22.94	186	299	Peak	Horizontal		
3	2615.74	54.23	16.64	37.59	74.00	-19.77	186	299	Peak	Horizontal		

Peak	Freq	Level	Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	dB	cm	deg			
1	2383.51	53.28	16.02	37.26	74.00	-20.72	353	293	Peak	Vertical		
2 *	2480.00	91.94	54.29	37.65	74.00	17.94	353	293	Peak	Vertical		
3	2627.30	54.29	16.76	37.53	74.00	-19.71	353	293	Peak	Vertical		


BLE\_1M

High Channel (Horizontal) Average

High Channel (Vertical) Average




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2371.12	39.66	2.41	37.25	54.00	-14.34	186	299 Average	Horizontal	
2 *	2480.00	95.95	58.30	37.65	54.00	41.95	186	299 Average	Horizontal	
3	2544.11	40.96	3.34	37.62	54.00	-13.04	186	299 Average	Horizontal	



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322





Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2349.53	39.68	2.45	37.23	54.00	-14.32	353	293 Average	Vertical	
2 *	2480.00	90.92	53.27	37.65	54.00	36.92	353	293 Average	Vertical	
3	2898.23	40.81	2.67	38.14	54.00	-13.19	353	293 Average	Vertical	

BLE\_2M

Low Channel (Horizontal) Peak

Low Channel (Vertical) Peak



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Level Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2341.39	53.59	16.42	37.17	74.00	-20.41	210	11	Peak	Horizontal	
2 *	2402.00	96.84	59.55	37.29	74.00	22.84	210	11	Peak	Horizontal	
3	2584.59	54.49	16.84	37.65	74.00	-19.51	210	11	Peak	Horizontal	

Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Level Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2333.13	53.30	16.19	37.11	74.00	-20.70	185	296	Peak	Vertical	
2 *	2402.00	92.95	55.66	37.29	74.00	18.95	185	296	Peak	Vertical	
3	2529.72	54.57	16.93	37.64	74.00	-19.43	185	296	Peak	Vertical	


BLE\_2M

Low Channel (Horizontal) Average

Low Channel (Vertical) Average




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2370.38	39.04	2.59	37.25	54.00	-14.16	210	11 Average	Horizontal	
2 *	2482.00	93.96	56.67	37.29	54.00	39.96	210	11 Average	Horizontal	
3	2847.14	40.92	3.04	37.88	54.00	-13.08	210	11 Average	Horizontal	



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2372.66	39.85	2.60	37.25	54.00	-14.15	185	296 Average	Vertical	
2 *	2482.00	90.22	52.93	37.29	54.00	36.22	185	296 Average	Vertical	
3	2843.95	40.93	3.08	37.85	54.00	-13.07	185	296 Average	Vertical	


BLE\_2M

Middle Channel (Horizontal) Peak

Middle Channel (Vertical) Peak




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2323.69	53.45	16.41	37.04	74.00	-20.55	358	336	Peak	Horizontal	
2 *	2440.00	98.31	60.76	37.55	74.00	24.31	358	336	Peak	Horizontal	
3	2791.79	54.72	17.24	37.48	74.00	-19.28	358	336	Peak	Horizontal	



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2388.71	52.64	15.38	37.26	74.00	-21.36	100	303	Peak	Vertical	
2 *	2440.00	95.61	58.06	37.55	74.00	21.61	100	303	Peak	Vertical	
3	2630.49	54.23	16.71	37.52	74.00	-19.77	100	303	Peak	Vertical	


BLE\_2M

Middle Channel (Horizontal) Average

Middle Channel (Vertical) Average




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2366.05	39.76	2.52	37.24	54.00	-14.24	358	336 Average	Horizontal	
2 *	2440.00	95.53	57.98	37.55	54.00	41.53	338	336 Average	Horizontal	
3	2899.76	40.98	2.83	38.15	54.00	-13.02	358	336 Average	Horizontal	



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2373.96	39.70	2.45	37.25	54.00	-14.30	100	303 Average	Vertical	
2 *	2440.00	92.82	55.27	37.55	54.00	38.82	100	303 Average	Vertical	
3	2892.92	40.90	2.78	38.12	54.00	-13.10	100	303 Average	Vertical	


BLE\_2M

High Channel (Horizontal) Peak

High Channel (Vertical) Peak




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2365.34	52.98	15.74	37.24	74.00	-21.02	186	299	Peak	Horizontal	
2 *	2480.00	96.99	59.34	37.65	74.00	22.99	186	299	Peak	Horizontal	
3	2483.58	54.61	16.96	37.65	74.00	-19.39	186	299	Peak	Horizontal	



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2355.67	53.43	16.20	37.23	74.00	-20.57	362	304	Peak	Vertical	
2 *	2480.00	92.48	54.83	37.65	74.00	18.48	362	304	Peak	Vertical	
3	2624.23	54.11	16.57	37.54	74.00	-19.89	362	304	Peak	Vertical	




BLE\_2M

High Channel (Horizontal) Average

High Channel (Vertical) Average




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2367.58	39.72	2.48	37.24	54.00	-14.28	186	299 Average	Horizontal	
2 *	2480.00	94.23	56.58	37.65	54.00	40.23	186	299 Average	Horizontal	
3	2483.50	42.59	4.94	37.65	54.00	-11.41	186	299 Average	Horizontal	



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2377.05	39.70	2.45	37.25	54.00	-14.30	362	304 Average	Vertical	
2 *	2480.00	89.71	52.06	37.65	54.00	35.71	362	304 Average	Vertical	
3	2483.50	41.12	3.47	37.65	54.00	-12.88	362	304 Average	Vertical	

Spurious Emissions, Tx Mode, 9kHz ~ 30MHz


BLE\_1M

Low Channel (Open) 9kHz~150kHz

Low Channel (Open) 150kHz~30MHz




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Level Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	PoL/Phase	Note
1	0.01	50.26	31.97	18.29	127.72	-77.46	100	152	Peak	Open	
2	0.03	57.60	38.05	19.55	119.13	-61.53	100	152	Peak	Open	
3	0.04	42.46	22.73	19.73	116.58	-74.12	100	152	Peak	Open	
4	0.06	42.41	23.12	19.29	111.82	-69.41	100	204	Peak	Open	
5	0.09	36.67	17.85	18.82	108.99	-72.32	100	168	Peak	Open	
6	0.11	34.70	16.15	18.55	106.82	-72.12	100	222	Peak	Open	




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Level Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	PoL/Phase	Note
1	0.15	43.37	24.72	18.65	104.00	-60.71	100	139	Peak	Open	
2	0.45	41.09	21.97	19.12	94.57	-53.48	100	158	Peak	Open	
3	7.76	34.64	14.08	20.56	69.50	-34.86	100	252	Peak	Open	
4	14.33	36.00	14.19	21.81	69.50	-33.50	100	255	Peak	Open	
5	21.58	36.22	13.62	22.60	69.50	-33.28	100	210	Peak	Open	
6	29.13	36.89	14.00	22.89	69.50	-32.61	100	263	Peak	Open	

**Spurious Emissions, Tx Mode, 30MHz ~ 1GHz**
**BLE\_1M**
**Low Channel (Horizontal)**
**Low Channel (Vertical)**



TÜV Rheinland Taiwan Ltd.  
 No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
 Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Level Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	67.83	27.01	36.38	-9.37	48.00	-12.99	480	50	Peak	Horizontal	
2	127.97	30.90	40.36	-9.46	43.50	-12.60	380	85	Peak	Horizontal	
3	221.09	28.53	38.07	-9.54	46.00	-17.47	100	329	Peak	Horizontal	
4	352.04	30.69	36.23	-5.54	46.00	-15.31	100	184	Peak	Horizontal	
5	740.04	32.62	30.30	2.32	46.00	-13.38	200	361	Peak	Horizontal	
6	845.77	35.67	31.97	3.70	46.00	-10.33	200	289	Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.  
 No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
 Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Level Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	30.00	30.66	39.56	-8.90	40.00	-9.34	180	78	Peak	Vertical	
2	67.83	33.89	43.26	-9.37	40.00	-6.11	180	103	Peak	Vertical	
3	100.81	38.64	50.78	-11.94	43.50	-4.66	200	344	Peak	Vertical	
4	114.39	27.47	38.20	-10.73	43.50	-16.03	100	206	Peak	Vertical	
5	709.00	32.26	30.54	1.72	46.00	-13.74	100	218	Peak	Vertical	
6	845.77	34.99	31.29	3.70	46.00	-11.01	200	280	Peak	Vertical	

Spurious Emissions, Tx Mode, 1GHz ~ 26.5GHz


BLE\_1M

Low Channel (Horizontal)

Low Channel (Vertical)




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2
4894.00	4894.00
43.01	59.17
53.01	60.17
-10.00	-10.00
54.00	74.00
-10.99	-23.83
300	300
55	55
Average	Peak
Horizontal	Horizontal



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2
4894.00	4894.00
39.07	48.34
49.07	58.34
-10.00	-10.00
54.00	74.00
-14.13	-25.66
400	400
360	360
Average	Peak
Vertical	Vertical


BLE\_1M

Middle Channel (Horizontal)

Middle Channel (Vertical)




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	4							
Level	Level	Level	Level							
Factor	Factor	Factor	Factor							
Limit	Limit	Limit	Limit							
Line	Line	Line	Line							
Over	Over	Over	Over							
Limit	Limit	Limit	Limit							
APos	APos	APos	APos							
TPos	TPos	TPos	TPos							
Remark	Remark	Remark	Remark							
Pol/Phase	Pol/Phase	Pol/Phase	Pol/Phase							
Note	Note	Note	Note							
4880.00	43.04	52.90	-9.86	54.00	-18.96	180	2	Average	Horizontal	
4880.00	50.54	60.40	-9.86	74.00	-23.46	180	2	Peak	Horizontal	
7320.00	39.64	47.48	-7.84	54.00	-14.36	200	22	Average	Horizontal	
7320.00	50.92	58.76	-7.84	74.00	-23.08	200	22	Peak	Horizontal	



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	4							
Level	Level	Level	Level							
Factor	Factor	Factor	Factor							
Limit	Limit	Limit	Limit							
Line	Line	Line	Line							
Over	Over	Over	Over							
Limit	Limit	Limit	Limit							
APos	APos	APos	APos							
TPos	TPos	TPos	TPos							
Remark	Remark	Remark	Remark							
Pol/Phase	Pol/Phase	Pol/Phase	Pol/Phase							
Note	Note	Note	Note							
4880.00	40.25	50.11	-9.86	54.00	-13.75	200	58	Average	Vertical	
4880.00	48.59	58.45	-9.86	74.00	-25.41	200	58	Peak	Vertical	
7320.00	38.21	46.05	-7.84	54.00	-15.79	100	18	Average	Vertical	
7320.00	49.84	57.68	-7.84	74.00	-24.16	100	18	Peak	Vertical	

BLE\_1M

High Channel (Horizontal)



High Channel (Vertical)



TÜV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	4								
Level	Level	Level	Level								
Factor	Factor	Factor	Factor								
Limit	Limit	Limit	Limit								
Line	Line	Line	Line								
Over	Over	Over	Over								
Limit	Limit	Limit	Limit								
APos	APos	APos	APos								
TPos	TPos	TPos	TPos								
Remark	Remark	Remark	Remark								
Pol/Phase	Pol/Phase	Pol/Phase	Pol/Phase								
Note	Note	Note	Note								
Freq	Level	Read	Level								
MHz	dBuV/m	Level	Factor								
		dBuV	dB/m								
		dBuV/m	dB								
		dBuV/m	dB								
		cm	deg								
1	4968.00	42.53	52.09	-9.56	54.00	-11.47	180	368	Average	Horizontal	
2	4968.00	50.49	60.05	-9.56	74.00	-23.51	180	368	Peak	Horizontal	
3	7448.00	41.31	49.14	-7.83	54.00	-12.69	193	25	Average	Horizontal	
4	7448.00	52.85	60.68	-7.83	74.00	-21.15	193	25	Peak	Horizontal	

1	2	3	4								
Level	Level	Level	Level								
Factor	Factor	Factor	Factor								
Limit	Limit	Limit	Limit								
Line	Line	Line	Line								
Over	Over	Over	Over								
Limit	Limit	Limit	Limit								
APos	APos	APos	APos								
TPos	TPos	TPos	TPos								
Remark	Remark	Remark	Remark								
Pol/Phase	Pol/Phase	Pol/Phase	Pol/Phase								
Note	Note	Note	Note								
Freq	Level	Read	Level								
MHz	dBuV/m	Level	Factor								
		dBuV	dB/m								
		dBuV/m	dB								
		cm	deg								
1	4968.00	40.95	50.51	-9.56	54.00	-13.05	180	337	Average	Vertical	
2	4968.00	49.23	58.79	-9.56	74.00	-24.77	180	337	Peak	Vertical	
3	7448.00	40.05	47.88	-7.83	54.00	-13.95	200	8	Average	Vertical	
4	7448.00	51.22	59.05	-7.83	74.00	-22.78	200	8	Peak	Vertical	


BLE\_2M

Low Channel (Horizontal)

Low Channel (Vertical)




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2									
Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
4894.00	36.40	45.40	-10.00	54.00	-17.60	180		1 Average	Horizontal	
4894.00	49.77	59.77	-10.00	74.00	-24.23	180		1 Peak	Horizontal	



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2									
Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
4894.00	34.58	44.58	-10.00	54.00	-19.42	378	360	1 Average	Vertical	
4894.00	48.05	58.05	-10.00	74.00	-25.95	378	360	1 Peak	Vertical	


BLE\_2M

Middle Channel (Horizontal)

Middle Channel (Vertical)




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4880.00	37.14	47.00	-9.86	54.00	-16.86	180	360 Average	Horizontal
2	4880.00	50.39	60.25	-9.86	74.00	-23.61	180	360 Peak	Horizontal
3	7320.00	37.37	45.21	-7.84	54.00	-16.63	200	24 Average	Horizontal
4	7320.00	50.82	58.66	-7.84	74.00	-23.18	200	24 Peak	Horizontal



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Read	Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4880.00	36.63	45.49	-9.86	54.00	-17.37	289	31 Average	Vertical
2	4880.00	50.16	60.02	-9.86	74.00	-23.84	289	31 Peak	Vertical
3	7320.00	37.44	45.28	-7.84	54.00	-16.56	103	23 Average	Vertical
4	7320.00	50.64	58.48	-7.84	74.00	-23.36	103	23 Peak	Vertical




BLE\_2M

High Channel (Horizontal)

High Channel (Vertical)




TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	4							
Level	Level	Level	Level							
Factor	Factor	Factor	Factor							
Limit	Limit	Limit	Limit							
Over	Over	Over	Over							
Line	Line	Line	Line							
Limit	Limit	Limit	Limit							
APos	APos	APos	APos							
TPos	TPos	TPos	TPos							
Remark	Remark	Remark	Remark							
Pol/Phase	Pol/Phase	Pol/Phase	Pol/Phase							
Note	Note	Note	Note							
4968.00	36.71	46.27	-9.56	54.00	-17.29	183	368	Average	Horizontal	
4968.00	59.16	59.72	-9.56	74.00	-23.84	183	368	Peak	Horizontal	
7440.00	38.35	46.18	-7.83	54.00	-15.65	200	30	Average	Horizontal	
7440.00	51.70	59.53	-7.83	74.00	-22.30	200	30	Peak	Horizontal	



TUV Rheinland Taiwan Ltd.  
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	4							
Level	Level	Level	Level							
Factor	Factor	Factor	Factor							
Limit	Limit	Limit	Limit							
Over	Over	Over	Over							
Line	Line	Line	Line							
Limit	Limit	Limit	Limit							
APos	APos	APos	APos							
TPos	TPos	TPos	TPos							
Remark	Remark	Remark	Remark							
Pol/Phase	Pol/Phase	Pol/Phase	Pol/Phase							
Note	Note	Note	Note							
4968.00	36.76	46.32	-9.56	54.00	-17.24	295	32	Average	Vertical	
4968.00	59.53	60.09	-9.56	74.00	-23.47	295	32	Peak	Vertical	
7440.00	38.68	46.71	-7.83	54.00	-15.12	100	26	Average	Vertical	
7440.00	52.68	60.51	-7.83	74.00	-21.32	100	26	Peak	Vertical	

Mains Conducted Emission, 150kHz ~ 30MHz


Worst Band

(Line)

(Neutral)



TÜV Rheinland Taiwan Ltd.  
No. 458-18, Sec. 2, Fenhiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322




Trace: 1

Line	Freq	Level	Read Level	Factor	Limit	Over	Remark	Pol/Phase	Note
	MHz	dBuV	dBuV	dB	dBuV	dB			
1	0.22	15.14	5.52	9.62	52.85	-37.71	Average	line1	
2	0.22	26.47	16.85	9.62	62.85	-36.38	QP	line1	
3	0.47	25.39	15.76	9.63	46.44	-21.05	Average	line1	
4	0.47	30.79	21.16	9.63	56.44	-25.65	QP	line1	
5	1.34	16.30	6.66	9.64	46.00	-29.70	Average	line1	
6	1.34	19.76	10.12	9.64	56.00	-36.24	QP	line1	
7	3.59	13.95	4.27	9.68	46.00	-32.05	Average	line1	
8	3.59	17.99	8.31	9.68	56.00	-38.01	QP	line1	
9	8.72	18.51	8.77	9.74	50.00	-31.49	Average	line1	
10	8.72	23.54	13.80	9.74	60.00	-36.46	QP	line1	
11	13.58	24.02	14.26	9.76	50.00	-25.98	Average	line1	
12	13.58	29.23	19.47	9.76	60.00	-30.77	QP	line1	



TÜV Rheinland Taiwan Ltd.  
No. 458-18, Sec. 2, Fenhiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)  
Tel: +886-2172-1000 Fax: +886-2172-1322



Trace: 1

Line	Freq	Level	Read Level	Factor	Limit	Over	Remark	Pol/Phase	Note
	MHz	dBuV	dBuV	dB	dBuV	dB			
1	0.22	17.92	8.30	9.62	52.94	-35.02	Average	neutral	
2	0.22	26.67	17.05	9.62	62.94	-36.27	QP	neutral	
3	0.47	27.80	18.17	9.63	46.48	-18.68	Average	neutral	
4	0.47	32.39	22.76	9.63	56.48	-24.09	QP	neutral	
5	0.92	18.09	8.45	9.64	46.00	-27.91	Average	neutral	
6	0.92	21.59	11.95	9.64	56.00	-34.41	QP	neutral	
7	2.07	16.78	7.12	9.66	46.00	-29.22	Average	neutral	
8	2.07	20.64	10.98	9.66	56.00	-35.36	QP	neutral	
9	4.86	13.68	3.97	9.71	46.00	-32.32	Average	neutral	
10	4.86	19.75	10.04	9.71	56.00	-36.25	QP	neutral	
11	13.51	25.88	16.07	9.81	50.00	-24.12	Average	neutral	
12	13.51	31.22	21.41	9.81	60.00	-28.78	QP	neutral	