

Exhibit #3

Airbus DS Government Solutions, Inc. - Satcom Terminal Technical Specifications

Terminal Name	Antenna Size (meters)	Antenna Gain (dBi)	Input Power at Flange (Watts)	EIRP (dBW)
Ranger 1m	1.0			
	Ka-Band (29.0 - 31.0 GHz)	47.7	50	64.7
	X-Band (7900-8400 MHz)	36.3	100	56.3
	Ku-Band (14000-14500 MHz)	41.6	40	57.6
Ranger 1.2m	1.2			
	Ka-Band (29.0 - 31.0 GHz)	49.7	50	66.7
	X-Band (7900-8400 MHz)	38.2	100	58.2
	Ku-Band (14000-14500 MHz)	43.6	80	62.6
	C-Band (5925-6425 MHz)	37.1	100	57.1
Ranger 1.5m	1.5			
	Ka-Band (29.0 - 31.0 GHz)	51.0	50	68.0
	X-Band (7900-8400 MHz)	39.6	100	59.6
	Ku-Band (14000-14500 MHz)	45.0	80	64.0
	C-Band (5925-6425 MHz)	38.5	100	58.5
Ranger 1.8m	1.8			
	Ka-Band (29.0 - 31.0 GHz)	52.7	100	72.7
	X-Band (7900-8400 MHz)	41.6	200	64.6
	Ku-Band (14000-14500 MHz)	47.1	100	67.1
	C-Band (5925-6425 MHz)	39.7	100	59.7
Ranger 2.4m	2.4			
	Ka-Band (29.0 - 31.0 GHz)	54.9	100	74.9
	X-Band (7900-8400 MHz)	43.7	200	66.7
	Ku-Band (14000-14500 MHz)	49.1	100	69.1
	C-Band (5925-6425 MHz)	42.0	100	62.0
Airbus RCT 4m	4.0			
	Ka-Band (29.0 - 31.0 GHz)	59.4	50	76.4
	X-Band (7900-8400 MHz)	48.8	400	74.8
	Ku-Band (14000-14500 MHz)	53.4	250	77.4
	C-Band (5925-6425 MHz)	47.2	200	70.2