

NTIA Space record data form

NTIA requires the following data for space related experiments using government shared spectrum. For each transmit frequency, please provide the data for both ends of the transmit-receive link. Use Part A to describe the satellite to ground information. Part B is for all ground to space transmit links.

**Part A: Space to Earth Downlink Data**

Satellite Transmitter Data

Transmit Frequency: 468 MHz		
Satellite Name: SORTIE		
Data Field	Data Answer	Description/Comments
Polarization (XAP)	XAP = J	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Orientation (XAZ)	XAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Antenna Dimension (XAD)	ANTENNA GAIN <u>  3  </u> BEAMWIDTH <u>  360°  </u> XAD =	(NTIA format (XAD), EXAMPLE, XAD01 16G030B)
Type of satellite (State = SP) (City = geo or non)	Type = Nongeostationary	Choose either: Geostationary or Nongeostationary
For Geostationary	Longitude = N/A	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>  51.6  </u> , APOGEE IN KILOMETERS <u>  407  </u> , PERIGEE IN KILOMETERS <u>  403  </u> , ORBITAL PERIOD IN HOURS <u>  1  </u> AND FRACTIONS OF HOURS IN DECIMAL <u>  0.54  </u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>  1  </u> , <i>Note: CubeSat Deployed from ISS</i> ORB = <u>51.6IN00407AP00403PE001.54H01NRT01</u>	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01

<b>Earth Station Data (Receiver)</b>		
State (RSC)	RSC = <a href="#">Virginia</a>	
City Name (RAL)	RAL = <a href="#">Wallops Island</a>	
Latitude (DDMMSS)	Lat = <a href="#">37° 51' 20.6208" N</a> <a href="#">375120N</a>	
Longitude (DDMMSS)	Lon = <a href="#">75° 30' 43.3152" W</a> <a href="#">0753043W</a>	
Antenna Polarization (RAP)	RAP = <a href="#">R</a>	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Antenna Azimuth (RAZ)	RAZ = <a href="#">Azimuth Range 0-360</a> <a href="#">Elevation Range 0-90</a>	THE EARTH STATION RECEIVER ANTENNA AZIMUTH (RAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, RAZ01 V00
Antenna Dimensions (RAD)	ANTENNA GAIN <a href="#">30</a> , BEAMWIDTH <a href="#">3°</a> , AZIMUTHAL RANGE <a href="#">0-360</a> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <a href="#">5</a> THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <a href="#">10</a>  <a href="#">XAD = 30G003B000-360A00005H010</a>	EXAMPLE ASSUMING NONGEOSTATIONARY, RAD01 16G030B000-360A00357H006
FCC notes: <ol style="list-style-type: none"> <li>Use S-Note S945.</li> <li>REM AGN, Cubesat, <a href="#">SORTIE</a></li> </ol>		

**Part B: Ground Stations, Earth to Space link data:**

Earth Station Transmitter Data

Transmit Frequency: 450 MHz		
State (XSC)	XSC = Virginia	
City Name (XAL)	XAL = Wallops Island	
Latitude (DDMMSS)	Lat = 37° 51' 20.6208" N 375120N	
Longitude (DDMMSS)	Lon = 75° 30' 43.3152" W 0753043W	
Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Antenna Azimuth (XAZ)	XAZ = Azimuth Range 0-360 Elevation Range 0-90	THE EARTH STATION Transmitter ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, XAZ01 V00
Antenna Dimensions (XAD)	ANTENNA GAIN _____ 30 _____, BEAMWIDTH _____ 3° _____, AZIMUTHAL RANGE _____ 0-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 5 _____ THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 10 _____  XAD = 30G003B000-360A00005H010	EXAMPLE ASSUMING NONGEOSTATIONARY, XAD01 16G030B000-360A00357H006
<b>Satellite Receive Specifications</b>		
Polarization (RAP)	RAP = J	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Azimuth (RAZ)	RAZ = Fixed Antenna, 360° Beamwidth	STATION RECEIVER ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, RAZ01 V00
Dimension (RAD)	ANTENNA GAIN _____ 3 _____ BEAMWIDTH _____ 360° _____ RAD =	(NTIA format (RAD), EXAMPLE, RAD01 16G030B)
Type of satellite (State = SP) City = G/No	Type = Nongeostationary	Choose either: Geostationary or Nongeostationary

For Geostationary	Longitude = N/A	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>51.6</u> , APOGEE IN KILOMETERS <u>407</u> , PERIGEE IN KILOMETERS <u>403</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.54</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , <i>Note: CubeSat Deployed from ISS</i> ORB = <u>51.6IN00407AP00403PE001.54H01NRT01</u>	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01