



UHF Antenna,
UHF Body Antenna,
UHF Antenna,
GSM/Cellular/PCS/UHF-Band Antenna,
PCS/L-Band Antenna,
S-Band Antenna,
S-Band Antenna2,

P/N: XXX-X-0.22-0.40-Ant (Item 307Tx, Sx, Bx, Nx, NBx),
P/N: XXX-X-0.22-0.40-Ant-Body (Item 307bTx, Sx, Bx, Nx, NBx),
P/N: XXX-X-0.31-0.45-Ant (Item 307T, S, B, N, NB),
P/N: XXX-X-0.81-1.99-Ant (Item 308T, S, B, N, NB),
P/N: XXX-X-1.20-2.50-Ant (Item 309T, S, B, N, NB),
P/N: XXX-X-1.50-2.50-Ant (Item 310T, S, B, N, NB) Center @ 2.5 GHz

P/N: XXX-X-2.02-2.07-Ant (Item 310GT, GS, GB) Giza, C-Band Antenna, P/N: XXX-X-4.40-5.85-Ant (Item 341T, S, B, N, NB)



ISO 9001:2008/FAA Approved Facility Antenna Mounts/Adapters: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501, USA . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

6

5

4

3

2

1

DRAWING NO. REV. 1

REVISIONS

ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

ELECTRICAL:

	UHF	L-BAND	L/S-BAND	S-BAND	C-BAND
FREQUENCY (MHz):	SEE PART NUMBER BELOW				
PATTERN:	OMNIDIRECTIONAL				
POLARIZATION:	VERTICAL				
ANTENNA GAIN :	> 2 dB				
VSWR:	2.0:1				
OUTPUT IMPEDANCE:	50 Ω				
POWER HANDLING:	>50 watts (Without LNA)				
LNA OPTION:	GAIN: 20 dB, NF: 4.1 dB, OP1dB: +18dB, OIP3: +33dB DC: (5 to 24) Volt @ <70mA				

MECHANICAL:

SIZE: DIAMETER: < 0.2 in
HEIGHT: SEE PART NUMBER BELOW

WEIGHT: UHF: 0.7 oz. (19g); L-Band: 0.3 oz. (9g); S-Band: 0.2 oz. (7g);
C-Band: 0.2 oz. (7g).

COLOR: BLACK

CONNECTOR: SMA FEMALE BULKHEAD (SMA, TNC, N, AND OTHERS ARE OPTIONAL)

ENVIRONMENTAL:

TEMPERATURE: -67°F TO +185°F [-55°C TO +85°C]
ALTITUDE: 70,000 ft.
VIBRATION: >10 G's
LEAKAGE: HERMETICALLY SEALED

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: DO-160D, MIL-C-5541, MIL-E-5400, MIL-I-45208A, AND MIL-STD-810E

CONNECTOR:

CONNECTOR:	FREQUENCY:	HEIGHT:
SMA-FB; SMA-M	0.31-0.40: (310-400) MHz	9.40in
MCX; MCX-FB	0.35-0.40: (350-400) MHz	9.40in
N; N-FB	0.40-0.45: (400-450) MHz	9.40in
TNC-M; TNC- FB	0.81-1.99: (810-960) MHz	3.50in
	0.87-1.99: (870-1990) MHz	2.65in
	1.20-2.50: (1200-2500) MHz	2.65in
	1.33-1.54: (1332-1540) MHz	2.19in
	1.61-1.85: (1610-1850) MHz	2.19in
	1.50-2.50: (1500-2500) MHz	1.86in
	1.80-1.99: (1800-1990) MHz	1.86in
	2.40-2.50: (2400-2500) MHz	1.86in
	4.40-5.85: (4400-5850) MHz	1.86in
	X.XX - Y.YY: (X.XX - Y.YY) GHz	1.86in

HEIGHT: See Part Number Below

Dimensions: .182 [4.62], .408 [10.38]

Item 307N, Item 307NB, Item 307T, Item 309S, Item 308T, Item 309T, Item 310B, Item 310T, Item 310N, Item 307B

NOTICE OF PROPRIETARY RIGHTS: THIS DOCUMENT CONTAINS CONFIDENTIAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM. ANY DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONDITIONED UPON YOUR ASSENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY (AND DOES NOT INCLUDE MANUFACTURE OR PROCESSING USES). ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

ANTCOM CORP. TORRANCE CALIFORNIA

UHF, L, L/S, S, or C-BAND ACTIVE/PASSIVE OMNI ANTENNA

P/N: SMA-FB-X.XX-Y.YY-ANT

SCALE 1/1 SHEET 1 OF 1

NMO Connector Option is Now Available for Some Antennas