



## Request for Experimental Authorization

Blue Sky Network, LLC herein requests experimental authority to demonstrate and test earth station facilities in connection with Iridium Satellite LLC’s non-geostationary satellite orbit space station constellation (Call Sign S2110) in the manner described below. Blue Sky Network, LLC seeks authority for a period of twenty-four (24) months.

This single earth station terminal is an experimental proto-type terminal at a single location, fixed to the building. The antennas are low-gain omni-directional antennas with a hemispheric coverage having a maximum +3 dBi gain.

### Necessary Bandwidth Description

The necessary bandwidth is determined by the frequency channelization that Iridium uses and is filed with other Iridium licenses. The frequency of a center of an Iridium channel can be calculated by this equation. There are 270 channels numbered 1 to 270 for transmit and 7 more that are receive only.

$$chan_{frequency} = 1616 \times 10^6 + \left( (41.6666 \times 10^3) \times ((chan_{number} - 1) + 0.5) \right) MHz$$

### Ground Station Locations

- Applied Satellite Engineering HQ
- 33-38-07, -111-52-53
- 16559 n 92nd Street, Suite 101,  
Scottsdale, AZ 85260
- 460m
- 12m

**Table 1: Particulars of Operation**

Lower Freq MHz	Upper Freq MHz	Input Power (watts) <sup>1</sup>	ERP (watts) <sup>2</sup>	Mean /Peak	Freq. Tolerance (%)	Station Class
1618.725	1626.0	1.8	4.8	M	0.0021	FX
1618.725	1626.0	1.8	4.8	M	0.0021	FX
1618.725	1626.0	1.8	4.8	M	0.0021	FX
1618.725	1626.0	6.0	9.0	M	0.0021	FX

<sup>1</sup> **NOTE:** defined as the nominal mean power input from the 9770 into the antenna

<sup>2</sup> **NOTE:** ERP(dBW) = EIRP(dBW) – 2.15 dB.

The information in this document is proprietary to Iridium Satellite LLC. It may not be used, reproduced, or disclosed without written approval from Iridium Satellite LLC.



**Table 2: Emission Data**

Emission Designator	Modulating Signal	Necessary Bandwidth (KHz)
41K7Q7W	25,000	41.7
41K7Q7W	30,000	41.7
83K0Q7W	60,000	83.0
333KQ7W	175,000	333.33

**Table 3: Waveforms and types of antennas used as well as the number of carriers**

Waveform	Modulation Scheme	Antenna Type	Number of Carriers
B1 (Block 1)	DEQPSK	LGA	1
C1 (NEXT)	QPSK	LGA	1
C2 (NEXT)	QPSK	LGA	1
1XC8 (NEXT)	QPSK	LGA	1

**Table 4: Beamwidth and Antenna Gain**

	3dB Beamwidth (degrees)	Gain (dBi)
Transmit	Hemisphere Omni	3.0
Receive	Hemisphere Omni	3.0