

Sempra Renewables 3550-3650 GHz MHz Experiment Proposal

1 Introduction

Sempra Renewables (NYSE:SRE) is a leading developer of clean energy solutions in markets throughout the U.S. Together with its partners, Sempra Renewables owns and operates nearly 2,400 megawatts of renewable generating capacity fueled by the sun and wind, enough to power approximately 600,000 homes and businesses. Its more than \$3 billion investment in clean energy has created about 4,000 jobs, while providing an economic boost to communities and landowners in 11 states. With proven capabilities in the development, design, construction, and operation of large-scale renewable energy projects, Sempra Renewables has the experience needed to develop customized energy solutions for today and tomorrow. Core to its mission, Sempra Renewables collaborates closely with customers, partners, and the communities in which it operates to safely and responsibly deliver clean energy solutions. For more information please visit our website: http://www.semprarenewables.com/

2 Experiment Description

Sempra is working with partner companies NOKIA and Qualcomm to evaluate and trial a LTE system operating in the frequency range of 3550-3650 MHz.

This trial will consist of up to 4 fixed site base stations and will be located inside the geographic region described in Section 2. Note: this trial area is outside the exclusion zone defined by NTIA (TR-15-517r1). Up to 15 mobile devices will operate in the areas of the fixed base stations. All base station equipment is prototype hardware, controlled and owned by NOKIA and will be removed after the conclusion of the trial.

The intent is to operate the LTE uplink/downlink 24 hours per day 7 days per week.

3 Transmitter Information

One or two 20 MHz LTE RF channels per base station will be operated within the requested frequency range at any one time.

The maximum EIRP for mobile and fixed sites is listed in Table 1. The fixed sites support MIMO and the defined power is the maximum radiated power for an individual antenna. A directional antenna may be used but it's listed as OMNI to not restrict orientation.

Table 2 defines the deployment radiuses where all fixed cell sites will be located within during the testing.

Туре	Transmit Frequency (MHz)	Conducted TX Power (dBm)	Maximum Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	ERP (dBm)	ERP (W)	Maximum Transmission Bandwidth (MHz)	Emissions Designator			
Fixed	3550-3650	40	18	58	631	55.85	385	20	20M0W7W			
Mobile	3550-3650	23	0	23	0.2	20.15	0.12	20	20M0W7W			

Table 1 Transmitter Information



Table 2 Tixed one Eccation Madids and mobile operational Madids										
	Operationa	al Center Point	Fixed Site Location and Mobile Operational Radius							
Location Description	Location #	Lat	Long	Miles	km					
Broken Bow, Nebraska Met3 tower	1	41°32'49.25"N	99°34'11.97"W	2.5	4					
Broken Bow, Nebraska Main station	2	41°29'52.14"N	99°35'15.37"W	2.5	4					

Table 2 Fixed Site Location Radius and Mobile Operational Radius

4 Interference Coordination

Immediate requests for Sempra Renewables to stop transmission should be emailed to <u>RemoteOperationsCenter@sempraglobal.com</u>. Alternatively, a shutdown requested can be submitted through Leonardo Prosperi who can be contacted at 619-696-4873 or <u>Iprosperi@sempraglobal.com</u>