NTIA Space record data form

NTIA requires the following data for space related experiments using government shared spectrum. For each transmit frequency, please provide the data for both ends of the transmit-receive link. Use Part A to describe the satellite to ground information. Part B is for all ground to space transmit links.

Part A: Space to Earth Downlink Data

Satellite Transmitter Data

Transmit Frequency	<i>y</i> :	
437.800		
Satellite Name:		
IRVINE01		
Data Field	Data Answer	Description/Comments
Polarization (XAP)	XAP = J	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Orientation (XAZ)	XAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Antenna Dimension (XAD)	ANTENNA GAIN0 BEAMWIDTH360 XAD =	(NTIA format (XAD), EXAMPLE, XAD01 16G030B)
Type of satellite (State = SP) (City = geo or non)	Type = non	Choose either: Geostationary or Nongeostationary
For Geostationary	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE 97.7 , APOGEE IN KILOMETERS 714 , PERIGEE IN KILOMETERS 598 , ORBITAL PERIOD IN HOURS 1 _ AND FRACTIONS OF HOURS IN DECIMAL 0.5 , THE NUMBER OF SATELLITES IN THE SYSTEM 1 , ORB =	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01

Earth Station Data (Receiver)				
State (RSC)	RSC = CA			
City Name (RAL)	RAL = San Luis Obispo, CA			
Latitude	Lat = 351808N			
(DDMMSS)				
Longitude	Lon = 1203955W			
(DDDMMSS)				
Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION		
Antenna Azimuth	RAZ =	THE EARTH STATION RECEIVER ANTENNA		
(RAZ)	Azimuth range 0-360	AZIMUTH (RAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, RAZ01 V00		
	Elevation range 0-90	, , , , , , , , , , , , , , , , , , , ,		
Antenna Dimensions (RAD)	ANTENNA GAIN18.9, BEAMWIDTH 21° ,	EXAMPLE ASSUMING NONGEOSTATIONARY, RAD01 16G030B000-360A00357H006		
Difficusions (NAD)	AZIMUTHAL RANGE 0-360 ,			
	THE SITE ELEVATION ABOVE MEAN SEA			
	LEVEL IN METERS 1636			
	THE ANTENNA HEIGHT ABOVE TERRAIN			
	IN METERS 10			
	RAD =			

FCC notes:

- 1. Use S-Note S945.
- 2. REM AGN, Cubesat, (insert name)

Part B: Ground Stations, Earth to Space link data:

Earth Station Transmitter Data

Transmit Frequency	y: ALL DATA IN SECTION B IS IDENTICAL TO S	ECTION A		
State (XSC)	XSC =			
City Name (XAL)	XAL =			
Latitude	Lat =			
(DDMMSS)				
Longitude	Lon =			
(DDDMMSS)				
Antenna	XAP =	POLARIZATIONS INCLUDE :		
Polarization (XAP)		H = HORIZONTAL, V = VERTICAL.		
		S = HORIZONTAL AND VERTICAL,		
		L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR,		
		T = RIGHT AND LEFT HAND CIRCULAR,		
		J = LINEAR POLARIZATION		
Antenna Azimuth	XAZ =	THE EARTH STATION Transmitter ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF		
(XAZ)		ELEVATION, V00 TO V90, EXAMPLE, XAZ01 V00		
		EXAMPLE ASSUMING NONGEOSTATIONARY,		
Antenna	ANTENNA GAIN,	XAD01 16G030B000-360A00357H006		
Dimensions (XAD)	BEAMWIDTH,			
	AZIMUTHAL RANGE,			
	THE SITE ELEVATION ABOVE MEAN SEA			
	LEVEL IN METERS			
	THE ANTENNA HEIGHT ABOVE TERRAIN			
	IN METERS			
	XAD =			
Catallita Bassiva Cr				
Satellite Receive Specifications				
Polarization (RAP)	RAP =	POLARIZATIONS INCLUDE :		
Totalization (ivii)	10 11	H = HORIZONTAL,		
		V = VERTICAL, S = HORIZONTAL AND VERTICAL,		
		L = LEFT HAND CIRCULAR,		
		R = RIGHT HAND CIRCULAR,		
		T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION		
Azimuth (RAZ)	RAZ =	STATION RECEIVER ANTENNA AZIMUTH (XAZ),		
		THE MINIMUM ANGLE OF ELEVATION, VOO TO V90, EXAMPLE, RAZ01 V00		
		ELEVATION, VOO TO V90, EXAMIFEE, NAZOT VOO		
Dimension (RAD)	ANTENNA GAIN	(NTIA format (RAD), EXAMPLE, RAD01 16G030B)		
	BEAMWIDTH			
	RAD =			
Type of satellite	Type =	Choose either:		
(State = SP)		Geostationary or Nongeostationary		
City = G/No		,		

For Geostationary For Nongeostationary (Orbital Data)	INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURSAND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM,	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG). IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REMO4 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL
		*ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01