NTIA Space record data form

NTIA requires the following data for space related experiments using government shared spectrum. For each transmit frequency, please provide the data for both ends of the transmit-receive link. Use Part A to describe the satellite to ground information. Part B is for all ground to space transmit links.

Part A: Space to Earth Downlink Data

Satellite Transmitter Data

Transmit Frequency	<i>r</i> :	
437.15		
Satellite Name:		
ExoCube 2		
Data Field	Data Answer	Description/Comments
Polarization (XAP)	XAP = J	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Orientation (XAZ)	XAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Antenna Dimension (XAD)	ANTENNA GAIN 2.15 BEAMWIDTH 360 XAD =	(NTIA format (XAD), EXAMPLE, XAD01 16G030B)
Type of satellite (State = SP) (City = geo or non)	Type = non	Choose either: Geostationary or Nongeostationary
For Geostationary	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE61, APOGEE IN KILOMETERS500, PERIGEE IN KILOMETERS500, ORBITAL PERIOD IN HOURS1AND FRACTIONS OF HOURS IN DECIMAL57, THE NUMBER OF SATELLITES IN THE SYSTEM1, ORB =	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01

Earth Station Data (Receiver)				
State (RSC)	RSC = CA			
City Name (RAL)	RAL = San Luis Obispo			
Latitude	Lat = 351808N			
(DDMMSS)				
Longitude	Lon = 1203955W			
(DDDMMSS)				
Antenna	RAP = R	POLARIZATIONS INCLUDE:		
Polarization (RAP)		H = HORIZONTAL, V = VERTICAL,		
		S = HORIZONTAL AND VERTICAL,		
		L = LEFT HAND CIRCULAR,		
		R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR.		
		J = LINEAR POLARIZATION		
Antenna Azimuth	RAZ =	THE EARTH STATION RECEIVER ANTENNA		
(RAZ)	Azimuth range 0-360	AZIMUTH (RAZ), THE MINIMUM ANGLE OF ELEVATION, VOO TO V90, EXAMPLE, RAZ01 V00		
,	Elevation range 0-90	ELEVATION, VOU TO V90, ENAIVIFIL, NAZOI V00		
Antenna	ANTENNA GAIN18.9,	EXAMPLE ASSUMING NONGEOSTATIONARY,		
Dimensions (RAD)	BEAMWIDTH,	RAD01 16G030B000-360A00357H006		
	AZIMUTHAL RANGE0-360,			
	THE SITE ELEVATION ABOVE MEAN SEA			
	LEVEL IN METERS100			
	THE ANTENNA HEIGHT ABOVE TERRAIN			
	IN METERS10			
	RAD =			
FCC notes:				

FCC notes:

- 1. Use S-Note S945.
- 2. REM AGN, Cubesat, (insert name)

Part B: Ground Stations, Earth to Space link data:

Earth Station Transmitter Data

Transmit Frequency	y: ALL DATA IN SECTION B IS IDENTICAL TO SI	ECTION A		
State (XSC)	XSC =			
City Name (XAL)	XAL =			
Latitude	Lat =			
(DDMMSS)				
Longitude	Lon =			
(DDDMMSS)				
Antenna	XAP =	POLARIZATIONS INCLUDE :		
Polarization (XAP)		H = HORIZONTAL, V = VERTICAL.		
		S = HORIZONTAL AND VERTICAL,		
		L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR,		
		T = RIGHT AND LEFT HAND CIRCULAR,		
		J = LINEAR POLARIZATION		
Antenna Azimuth	XAZ =	THE EARTH STATION Transmitter ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF		
(XAZ)		ELEVATION, V00 TO V90, EXAMPLE, XAZ01 V00		
Antenna	ANTENNA GAIN,	EXAMPLE ASSUMING NONGEOSTATIONARY, XAD01 16G030B000-360A00357H006		
Dimensions (XAD)	BEAMWIDTH,			
	AZIMUTHAL RANGE,			
	THE SITE ELEVATION ABOVE MEAN SEA			
	LEVEL IN METERS			
	THE ANTENNA HEIGHT ABOVE TERRAIN			
	IN METERS			
	VA D			
Catallita Bassia C	XAD =			
Satellite Receive Specifications				
Polarization (RAP)	RAP =	POLARIZATIONS INCLUDE :		
,		H = HORIZONTAL, V = VERTICAL,		
		S = HORIZONTAL AND VERTICAL,		
		L = LEFT HAND CIRCULAR,		
		R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR,		
		J = LINEAR POLARIZATION		
Azimuth (RAZ)	RAZ =	STATION RECEIVER ANTENNA AZIMUTH (XAZ),		
		THE MINIMUM ANGLE OF ELEVATION, VOO TO V90, EXAMPLE, RAZ01 V00		
		2227711014, 400 10 430, 230 1011 22, 17/201 400		
Dimension (RAD)	ANTENNA GAIN	(NTIA format (RAD), EXAMPLE, RAD01 16G030B)		
	BEAMWIDTH			
	RAD =			
Type of satellite	Type =	Choose either:		
(State = SP)		Geostationary or Nongeostationary		
City = G/No				

For Geostationary For Nongeostationary (Orbital Data)	INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURSAND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG). IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
	THE NUMBER OF SATELLITES IN THE SYSTEM,	