

# **Capella Whitney-1 Orbital Debris Assessment Report (ODAR)**

Lucas Riggi\*

E-mail: [lucas@capellaspace.com](mailto:lucas@capellaspace.com)

This report is presented in compliance with NASA-STD-8719.14, APPENDIX A.

Report Version: 1, 04/01/2020

Document Data is Not Restricted.

This document contains no proprietary, ITAR, or export controlled information.

DAS Software Version Used In Analysis: v2.1.1



---

**VERSION APPROVAL and/or FINAL APPROVAL:**

Duncan Eddy, Space Operations

**PREPARED BY:**

Lucas Riggi, Mission Design

---

## Table of Contents

Self-assessment of the ODAR	4
1. Mission Overview	5
2. Spacecraft Description	5
3. Spacecraft Debris Released during Normal Operations	8
4. Spacecraft Intentional Breakups and Potential for Explosions	9
5. Spacecraft Potential for On-Orbit Collisions	13
6. Spacecraft Post-mission Disposal Plans and Procedures	15
7. Spacecraft Reentry Debris Casualty Risks	17
8. Collision risk posed by tether systems	19



# Self-assessment of the ODAR

This ODAR follows the format recommended in NASA-STD-8719.14, Appendix A.1, sections 1 through 8 for the Capella satellite. Sections 9 through 14 apply to the launch vehicle ODAR and are not covered here.

## Orbital Debris Self-Assessment Report Evaluation: Capella Mission

(based upon ODAR version 1, dated April 1, 2020)

Reqm #	Launch Vehicle				Spacecraft			Comments
	Compliant	Not Compliant	Incomplete	Standard Not Compliant	Compliant or N/A	Not Compliant	Incomplete	
4.3-1.a	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.3-1.b	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.3-2	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.4-1	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.4-2	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.4-3	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.4-4	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.5-1	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.5-2	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.6-1.a	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.6-1.b	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.6-1.c	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.6-2	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.6-3	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.6-4	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.7-1	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4.8-1					<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	

Figure 1: ODAR Review Check sheet

# 1. Mission Overview

**Project Manager:** Duncan Eddy

**Mission Overview:** The Whitney-1 satellite will be launched in 2020, no earlier than June. It will be launched in a mid-inclination (45) orbit at an average altitude of 525 km. It will be operated for a tentative minimum of 3 years. For the purpose of this document, the worst case altitude in terms of lifetime of 530 km will be used.

**ODAR Summary:** All the debris generated in orbit are compliant with Requirements 4.3, there is no credible scenario for breakups, the collision probability with other objects is compliant with NASA standards, the estimated nominal decay lifetime due to atmospheric drag is under, in every scenario, much less than 25 years following operations (as calculated by DAS 2.1.1).

**Launch:** Whitney-1 is currently planned to be launched on a Rocket Lab Electron rocket from New Zealand, in June 2020.

**Mission Duration:** Maximum Nominal Operations: 3 years, Post-Operations Orbit lifetime: 2 year until reentry via atmospheric orbital decay (worst case 5 years in total).

**Orbit Profile:** Whitney-1 will deploy from the launch vehicle into its near-circular mid-inclination orbit at an altitude of 525 km. There is no transfer or parking orbit. It will maintain an altitude between 500 and 530 km using a xenon-based RF propulsion system for 3 years.

---

## 2. Spacecraft Description

**Physical Description of the Spacecraft:** Capella satellites have a launch mass between 90 kg and 120 kg. Two 500mm x 900mm deployable solar arrays, a 8  $m^2$  deployable antenna and a 3m long boom deploy from the principal bus structure.

All deployables use a frangibolt and motor based deployment system from which no debris will be generated.

Power storage is provided by Lithium-Ion cells. The batteries will be recharged by solar cells mounted on on the two deployable solar panels.

Capella attitude is estimated with an accuracy of 50 arcsec using filtering of sensor data from 2 star trackers, an IMU, sun sensors and a magnetometer. Capella attitude will be controlled by 3 reaction wheels for nominal operation and a 3-axis magnetorquer during detumbling and for wheel desaturation.

**Total satellite mass at launch, including all propellants and fluids:** 90 - 120 kg for all launches.

**Dry mass of satellites at launch, excluding solid rocket motor propellants:** 90 - 120 kg for all launches.

**Description of all propulsion systems (cold gas, mono-propellant, bi-propellant, electric, nuclear):** Whitney-1 will be equipped with a propulsion system for station keeping. The baseline system is a xenon-based RF magnetic thruster from Phase Four. It is an electromagnetic electric propulsion system that accelerates the xenon propellant using magnetic mechanisms. It uses 1  $kg$  of xenon for a maximum thrust force of 6  $mN$ .

**Identification, including mass and pressure, of all fluids (liquids and gases) planned to be on board and a description of the fluid loading plan or strate-**

---

**gies, excluding fluids in sealed heat pipes:** On Whitney-1, the only fluid will be in the propulsion system tank. There will be 1.0 *kg* of xenon propellant. Xenon will be loaded onto the system to a target density which equates approximately 1,175 *psia* at room temperature (25C). The maximum operating pressure (MEOP) that the system will experience is 3,000 *psia* at 75C assuming a full propellant load. The propulsion system can be filled with propellant either as a standalone system or while integrated into the satellite bus via external-facing fluid and electronic interface locations. Phase Four has designed and built ground support equipment to achieve the desired xenon density load. The design has been verified using the approach described in MIL-STD-1522A, approach B (page 28).

**Fluids in Pressurized Batteries:** None. Capella uses unpressurized standard Lithium-Ion battery cells. Each battery has a height of 65mm, a diameter of 18mm.

**Description of attitude control system and indication of the nominal attitude of the spacecraft:** Capella uses 3 magnetic rods to despin the satellite during the initial tumbling phase. 3 reaction wheels oriented in the direction of the principal axes allow 3-axis control during nominal operation. The magnetorquers are also used for desaturation of the wheels. The nominal attitude will be with the solar panels in the radial direction (R for radial) and the SAR antenna pointing in the nadir direction (-R). At the end of operations, the 3-axis controller can be used to rotate the satellite into maximum drag configuration, with the SAR antenna in the opposite direction of the velocity (-T for tangential), to accelerate orbital decay.

### **3. Spacecraft Debris Released during Normal Operations**

#### **Requirement 4.3-1: Debris passing through LEO, released debris with diameters of 1mm or larger**

No release of debris will occur during the lifetime of Capella satellites. All deployments use a frangibolt and motor based system that does not generate any debris. Additionally, there is no probable scenario for unintentional debris generation.

**Result for Requirement 4.3-1: COMPLIANT**

#### **Requirement 4.3-2: Debris passing near GEO**

There will be no intentional release of debris during the lifetime of the mission, as Capella's mission is contained in Low Earth Orbit.

**Result for Requirement 4.3-2: COMPLIANT**



---

## 4. Spacecraft Intentional Breakups and Potential for Explosions

### **Requirement 4.4-1: Limiting the risk to other space systems from accidental explosions during deployment and mission operations while in orbit about Earth or the Moon**

The probability of battery or pressurized tank explosion is very low, believed to be much less than 0.001 and, due to the small mass of the satellite and its short orbital lifetime, the long-term effects of an unlikely explosion on the LEO environment are negligible. During the development process, the heat pipes have been space qualified through pressure testing, burst pressure testing, vibration testing and thermal vacuum cycling. At the end of the 3 years of nominal operations, any leftover propellant can be used to accelerate the reentry of the satellite.

**Failure mode 1:** Internal short circuit.

*Mitigation 1:* Qualification and acceptance shock, vibration, thermal cycling, and vacuum tests followed by maximum system rate-limited charge and discharge will prove that no internal short circuit sensitivity exists.

*Combined faults required for realized failure:* Environmental testing AND functional charge / discharge tests must both be ineffective in discovery of the failure mode.

**Failure mode 2:** Internal thermal rise due to high load discharge rate.

*Mitigation 2:* Cells will be tested in lab for high load discharge rates in a variety of flight like configurations to determine if the feasibility of an out of control thermal rise in the cell. Cells will also be tested in a hot environment to test the upper limit of the cells capability.

*Combined faults required for realized failure:* Spacecraft thermal design must be incorrect

---

AND external over current detection and disconnect function must fail to enable this failure mode.

**Failure mode 3:** Excessive discharge rate or short circuit due to external device failure or terminal contact with conductors not at battery voltage levels (due to abrasion or inadequate proximity separation).

*Mitigation 3:* This failure mode will be negated by a) qualification tested short circuit protection on each external circuit, b) design of battery packs and insulators such that no contact with nearby board traces is possible without being caused by some other mechanical failure, c) obviation of such other mechanical failures by proto-qualification and acceptance environmental tests (shock, vibration, thermal cycling, and thermal-vacuum tests).

*Combined faults required for realized failure:* An external load must fail/short-circuit AND external over-current detection and disconnect function must all occur to enable this failure mode.

**Failure mode 4:** Inoperable vents.

*Mitigation 4:* Battery vents are not inhibited by the battery holder design or the spacecraft.

*Combined faults required for realized failure:* The manufacturer fails to install proper venting.

**Failure mode 5:** Crushing.

*Mitigation 5:* This mode is negated by spacecraft design. There are no moving parts in the proximity of the batteries.

*Combined faults required for realized failure:* A catastrophic failure must occur in an external system AND the failure must cause a collision sufficient to crush the batteries leading to an internal short circuit AND the satellite must be in a naturally sustained orbit at the time the crushing occurs.

---

**Failure mode 6:** Low level current leakage or short-circuit through battery pack case or due to moisture-based degradation of insulators.

*Mitigation 6:* These modes are negated by a) battery holder/case design made of non-conductive plastic, and b) operation in vacuum such that no moisture can affect insulators.

*Combined faults required for realized failure:* Abrasion or piercing failure of circuit board coating or wire insulators AND dislocation of battery packs AND failure of battery terminal insulators AND failure to detect such failures in environmental tests must occur to result in this failure mode.

**Failure mode 7:** Excess temperatures due to orbital environment and high discharge combined.

*Mitigation 7:* The spacecraft thermal design will negate this possibility. Thermal rise will be analyzed in combination with space environment temperatures showing that batteries do not exceed normal allowable operating temperatures which are well below temperatures of concern for explosions.

*Combined faults required for realized failure:* Thermal analysis AND thermal design AND mission simulations in thermal-vacuum chamber testing AND over-current monitoring and control must all fail for this failure mode to occur.

**Result for Requirement 4.4-1:** COMPLIANT

## **Requirement 4.4-2: Design for passivation after completion of mission operations while in orbit about Earth or the Moon**

Passivation will happen naturally at the end of mission by depletion of any remaining energy contained in the batteries (either through uncontrolled tumbling in case of ADCS failure or attitude control in case of nominal ADCS operations) and natural orbit decay and re-entry within 3 years.

---

**Result for Requirement 4.4-2: COMPLIANT**

**Requirement 4.4-3. Limiting the long-term risk to other space systems from planned breakups**

There are no planned breakup during the mission.

**Result for Requirement 4.4-3: COMPLIANT**

**Requirement 4.4-4: Limiting the short-term risk to other space systems from planned breakups**

There are no planned breakup during the mission.

**Result for Requirement 4.4-4: COMPLIANT**

---

## 5. Spacecraft Potential for On-Orbit Collisions

Since the orientation of the spacecraft during operations will vary, the probability of collision with other objects is computed in the worst case scenario of the SAR antenna being in the direction tangential to the velocity. DAS v2.1.1 is used for orbit and collision analysis. It is to be noted that Capella's on-orbit collision avoidance scheme has already been implemented and TESTED SUCCESSFULLY on orbit.

### **Requirement 4.5-1. Limiting debris generated by collisions with large objects when operating in Earth orbit**

The worst case initial orbit of the spacecraft is a circular orbit at an altitude of 530 km and an inclination of 45.0 degrees. The area/mass ratio of the spacecraft is  $0.035 \text{ m}^2/\text{kg}$ . The computed probability of collision with large objects is for a single satellite is 0.00001, below the maximum acceptable probability of 0.01.

**Result for Requirement 4.5-1: COMPLIANT**

### **Requirement 4.5-2. Limiting the probability of damage from small objects when operating in Earth or lunar orbit**

The component critical for post-mission operations are the communication hardware, the attitude control system, the solar panels and the batteries. The results for each critical subsystem, for a Capella satellite at 530 km are given in the table below. satellite is computed to be 0.000036, below the 0.01 requirement.



Table 1: Small Object Damage Analysis at 530 km

<b>Critical Surface</b>	<b>Probability of Penetration</b>
ADCS	0.000000
COMS	0.000000
Solar Panels	0.000036
Batteries	0.000000
<b>Probability of PMD Failure</b>	<b>0.000036</b>

**Result for Requirement 4.5-2: COMPLIANT**

---

## 6. Spacecraft Post-mission Disposal Plans and Procedures

The orbit of the satellites will decay because of atmospheric drag and the satellites will eventually naturally de-orbit by atmospheric reentry. At the end of the mission operations, the attitude control system can orient the satellites into a maximum drag configuration with the solar panels and SAR antenna in the direction of the velocity, accelerating the orbital decay. Even in the case of ADCS failure and tumbling spacecraft at end of life, the satellites will de-orbit well within the maximum allowable 25 year lifetime. In the case where some leftover propellant is available at the end of the 3-year nominal mission lifetime, propulsion can be used to further decrease the duration of atmospheric reentry. However, the following analysis has been done assuming natural orbital decay.

### **Requirement 4.6-1. Disposal for space structures in or passing through LEO**

The altitude of the satellites are computed from their worst case initial circular orbits at the altitude of 530 km, in its end of mission configuration. The average area to mass ratio for the tumbling spacecraft is used ( $0.035 \text{ m}^2/\text{kg}$ ). The lifetime of the satellite with no orbit maintenance is computed by DAS to be 1.8 years, for a maximum orbital lifetime, after 3 years of operations, of 4.8 years, much below the 25 year orbital lifetime threshold.

**Result for Requirement 4.6-1: COMPLIANT**

### **Requirement 4.6-2. Disposal for space structures near GEO**

There are no space structures near GEO involved in this mission.

**Result for Requirement 4.6-2: COMPLIANT**

### **Requirement 4.6-3. Disposal for space structures between LEO and GEO**

There are no space structures between LEO and GEO involved in this mission.

**Result for Requirement 4.6-3: COMPLIANT**

### **Requirement 4.6-4. Reliability of post-mission disposal operations in Earth orbit**

The above analysis has been performed with an average area to mass ratio, which means that even in the case of massive power or ADCS failure, a tumbling spacecraft, the spacecraft will deorbit in a worst case of 4.8 years.

**Result for Requirement 4.6-4: COMPLIANT**



## 7. Spacecraft Reentry Debris Casualty Risks

### Requirement 4.7-1. Limit the risk of human casualty

The risk of human casualty was computed by DAS v2.1.1 for an uncontrolled reentry to be 1:100000000 for the Sequoia satellite. The spacecraft model and results are summarized in the tables below.

Table 2: Spacecraft Model

Component	Subcomponent
Bus	Batteries Reaction Wheels Avionics Propulsion Tanks Radio Stack 1 Radio Stack 2
SAR Antenna	
Solar Array	
Torque Rods	
Star Trackers	
Thruster	
Antennae	
Payload	

Table 3: Human Casualty Risk Analysis

Component	Qty	Material	Shape	Mass (kg)	Dem. Alt. (km)	Cas. Area (m <sup>2</sup> )	En. (J)
Bus Structure	1	Aluminum	Box	24	62.8	0	0
Batteries	64	Aluminum	Cylinder	0.0625	76.4	0	0
Reaction Wheels	3	Aluminum	Cylinder	3.2	63.0	0	0
Avionics	1	Aluminum	Box	24.7	62.1	0	0
Tanks	1	Titanium	Box	0.5	73.8	0	0
Radio Stack 1	1	Aluminum	Box	1	71.3	0	0
Radio Stack 2	1	Aluminum	Box	2.5	63.0	0	0
SAR Antenna	40	Aluminum	Cylinder	0.5	74.9	0	0
Solar Array	2	Aluminum	Flat Plate	2.4	74.7	0	0
Torque Rods	3	Copper	Cylinder	0.6	71.9	0	0
Star Trackers	2	Aluminum	Box	0.3	74.7	0	0
Thruster	1	Aluminum	Box	2.5	63.0	0	0
Payload	1	Aluminum	Box	4	64.8	0	0



---

**Result for Requirement 4.7-1: COMPLIANT**

## 8. Collision risk posed by tether systems

### Requirement 4.8-1. Mitigate the collision hazards of space tethers in Earth or Lunar orbits

No tethers are to be used in Capella missions.

**Result for Requirement 4.8-1: COMPLIANT**

**END OF ODAR FOR CAPELLA**

**Approved:** Lucas Riggi  
Constellation Architect  
04/03/2020  
*Lucas Riggi*