



LMO7270

4G/LTE/3G/2G MIMO

Omni Antenna

Features

- ◆ Multiband MIMO Omni Antenna
- ◆ Covers LTE, 4G, 3G and GSM bands
- ◆ Dual Polarisation - Dual Ports
- ◆ Optional Mount Bracket for wall or pole

Specifications

Frequency range	690-800/800-960 / 1710-2170 / 2500-2700 MHz
Peak Gain - Element 1	1.4 / 2.0 / 3.0 / 3.3 dBi
Peak Gain - Element 2	2.8 / 3.0 / 3.9 / 3.9 dBi
Polarisation	Dual Polarised
Impedance	50 Ohm
VSWR	<2:1
Power rating	10W
Operating Temp.	-30 to +70 degrees C
Cable / Connector	2 x 15cm Pigtails - connectors SMA
Dimensions	187 x 106 (h x d) excluding bracket

Popular Ordering Options

LMO7270-NB-SMSM	LMO7270 antenna No Bracket 2 x 10cm pigtails 2 x SMA-Male
LMO7270-WB-SMSM	LMO7270 antenna With Bracket 2 x 10cm pigtails 2 x SMA-Male
LMO7270-WB-D5M195-SM	LMO7270 antenna With Bracket 2 x 5M BWL195 cables 2 x SMA-Male
LMO7270-WB-D10M195-SM	LMO7270 antenna With Bracket 2 x 10M BWL195 cables 2 x SMA-Male

* Antenna should not be mounted on metal surface

Specifications subject to change without notice.

5 Little Balmer
Buckingham Industrial Park
Buckingham
MK18 1TF
UK

Tel: +44 (0)1280 824055
Fax: +44 (0)1280 817179
Email: sales@ead-ltd.com
Web: www.ead-ltd.com

EAD 
embedded antenna design ltd
Delivering Antenna Innovation