



## LNX-6515DS-VTM | LNX-6515DS-A1M

**Andrew® Antenna, 698–896 MHz, 65° horizontal beamwidth, RET compatible**

- Excellent choice to maximize both coverage and capacity in suburban and rural applications
- Fully compatible with Andrew remote electrical tilt system for greater OpEx savings
- Exceptional horizontal pattern roll-off and strong front-to-back ratio
- Extended bandwidth allows one antenna to serve multiple frequency allocations
- Great solution to maximize network coverage and capacity
- The RF connectors are designed for IP67 rating and the radome for IP56 rating

### Electrical Specifications

Frequency Band, MHz	698–806	806–896
Gain, dBi	16.7	17.6
Beamwidth, Horizontal, degrees	65	64
Beamwidth, Vertical, degrees	9.7	8.6
Beam Tilt, degrees	0–8	0–8
USLS (First Lobe), dB	17	17
Front-to-Back Ratio at 180°, dB	32	27
CPR at Boresight, dB	24	27
CPR at Sector, dB	15	13
Isolation, dB	30	30
VSWR   Return Loss, dB	1.4   15.6	1.4   15.6
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153
Input Power per Port, maximum, watts	400	400
Polarization	±45°	±45°
Impedance	50 ohm	50 ohm

### Electrical Specifications, BASTA\*

Frequency Band, MHz	698–806	806–896
Gain by all Beam Tilts, average, dBi	16.6	16.9
Gain by all Beam Tilts Tolerance, dB	±0.4	±0.3
	0 °   16.6	0 °   17.0
Gain by Beam Tilt, average, dBi	4 °   16.6	4 °   17.0
	8 °   16.4	8 °   16.8
Beamwidth, Horizontal Tolerance, degrees	±1	±0.9
Beamwidth, Vertical Tolerance, degrees	±0.6	±0.4
USLS, beampeak to 20° above beampeak, dB	18	18
Front-to-Back Total Power at 180° ± 30°, dB	25	23
CPR at Boresight, dB	24	27
CPR at Sector, dB	15	13

\* CommScope® supports NGMN recommendations on Base Station Antenna Standards (BASTA). To learn more about the benefits of BASTA, [download the whitepaper Time to Raise the Bar on BSAs.](#)

### General Specifications

Antenna Brand	Andrew®
Antenna Type	DualPol®
Band	Single band
Brand	DualPol®

LNX-6515DS-VTM | LNX-6515DS-A1M

Operating Frequency Band	698 – 896 MHz
Performance Note	Outdoor usage

## Mechanical Specifications

Color	Light gray
Lightning Protection	dc Ground
Radiator Material	Aluminum
Radome Material	Fiberglass, UV resistant
RF Connector Interface	7-16 DIN Female
RF Connector Location	Bottom
RF Connector Quantity, total	2
Wind Loading, maximum	878.0 N @ 150 km/h 197.4 lbf @ 150 km/h
Wind Speed, maximum	241 km/h   150 mph

## Dimensions

Depth	180.5 mm   7.1 in
Length	2453.0 mm   96.6 in
Width	301.0 mm   11.9 in
Net Weight, without mounting kit	19.8 kg   43.7 lb

## Remote Electrical Tilt (RET) Information

Model with Factory Installed AISG 2.0 Actuator LNX-6515DS-A1M

## Packed Dimensions

Depth	284.0 mm   11.2 in
Length	2765.0 mm   108.9 in
Width	411.0 mm   16.2 in
Shipping Weight	38.6 kg   85.1 lb

## Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant by Exemption
China RoHS SJ/T 11364-2006	Above Maximum Concentration Value (MCV)
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



## Included Products

DB380-3 — Pipe Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Used for wide panel antennas. Includes three clamp sets.

DB5083D — Downtilt Mounting Kit for 2.4"-4.5" (60-115 mm) OD round members. Consists of two DB5083 heavy-duty,

---

LNx-6515DS-VTM | LNx-6515DS-A1M

galvanized steel downtilt mounting brackets. This kit is compatible with the DB380-3 pipe mount for panel antennas with three mounting points.

## \* **Footnotes**

---

Performance Note      Severe environmental conditions may degrade optimum performance