

MA-WA48-DP23

4.4-5.1 GHz Dual Polarization/Dual Slant Subscriber Antenna

Antenna Features:

- Dual slant if mounted diagonally.
- Efficient and stable performance.
- High gain/size ratio.
- Light weight and durable construction.
- UV protected radome made of polycarbonate suitable for harsh weather installations.
- Easy mounting allowing Az/EI adjustment and 45deg. turn installation.



Specifications

Electrical

Frequency range	4.4-5.1 GHz
GAIN	23 ± 1 dBi
VSWR, max.	1.7 : 1
Polarization	Linear, Vertical & Horizontal
3 dB Beam-Width, H-Plane, typ.	9°
3 dB Beam-Width, E-Plane, typ.	9°
Side Lobes, min.	-12 dB
Cross Polarization, min.	-20 dB
Port to Port Isolation, typ.	-35 dB
Front to Back Ratio, min.	-35 dB
Input power, max.	10 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	370 x 370 x 40 mm (14.5" x 14.5" x 1.6")
Weight	2.1 kg.
Connector	2 x N-Type Female
Back Plane	Aluminum protected through chemical passivation
Radome	UV Protected, Polycarbonate
Mount	See ordering options

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11

Ordering Options

MA-WA48-DP23	Antenna Suited for MNT-22 (optional wall/pole adjustable mount)
MA-WA48-DP23B	Antenna with MNT-22 mount

Patterns are available on our website

Mars Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 58861, P.O.Box 5 AZOR 58008, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com