RF Radiation Safety Calculations

Spreadsheet Copyright by Tim Shroyer, General Dynamics C4 Systems 2005 RF Safety Calculations based on OET Bulletin 65 for Parabolic Reflectors.

Calculations are based on Bulletin 65 Equations 11 through 18.

Input Values

| Frequency of Operation | 14200 MHz |
|------------------------|-------------|
| Reflector Diameter | 0.50 Meters |
| Gain of Antenna | 33.8 dBi |
| Input Power to Antenna | 13 dBW |
| Input Power to Antenna | 19.95 Watts |

| Resultant EIRP | 46.80 dBW |
|----------------|----------------|
| | 47863.01 Watts |

Power Density At Antenna Surface

(From Bulletin 65 Equation 11)

| Maximum Power Density At Antenna Surface = Maximum Power Density At Antenna Surface = Maximum Power Density At Antenna Surface = | 406.47 W/m ² 40.65 mW/cm ² 16.09 dBW/cm ² |
|--|--|
| Is this Compliant With Limits? For Occupational/Controlled Exposure (5 mW/cm²)= | NO |
| For General Population/Uncontrolled Exposure (5 mW/cm²)= | NO NO |

Power Density in the Near-Field Region

| Extent of the Near-Field = (From Bulletin 65 Equation 12) | 2.96 Meters |
|---|---|
| Aperture Efficiency = (From Bulletin 65 Equation 14) | 0.434 Units |
| On-Axis Near-Field Power Density = (From Bulletin 65 Equation 13) | 176.38 W/m ² 17.64 mW/cm ² |
| Is this Compliant With Limits? | |
| For Occupational/Controlled Exposure (5 mW/cm ²)= | NO |
| For General Population/Uncontrolled Exposure (1 mW/cm ²)= | NO |

Power Density in the Transition Region

| Beginning of Far-Field (From Bulletin 65 Equa | • | | 7.10 | Meters | |
|---|--|-----------------------------|--------|--------------------|--|
| Transition Region Pow (From Bulletin 65 Equal In the Transition Regio | ation 17) | | | | |
| Powe | er Density = | 17.64 mW/cm ² at | 2.96 | Meters | |
| Powe | er Density = | 7.35 mW/cm ² at | 7.10 | Meters | |
| Is the Full Transition Re | Is the Full Transition Region Compliant With Limits? | | | | |
| For Occupational/Controlled Exposure (5 mW/cm ²)= | | NO | | | |
| For General Population/Uncontrolled Exposure (1 mW/cm²)= | | NO | | | |
| At What Range Is Power Density Compliant With Limits? | | | | | |
| For Occupational/Controlled Exposure (5 mW/cm²)= | | Too Many | | | |
| For General Population/Uncontrolled Exposure (1 mW/cm ²)= | | Too Many | Meters | | |
| Power Density in the Far-Field Region | | | | | |
| Far-Field Starts at = | | | 7.10 | Meters | |
| Power Density at the st | tart of Far-Field Re | egion = | 7.56 | mW/cm ² | |
| (From Bulletin 65 Equa | | .g.c | | | |
| At What Range Is Pow | | | | | |
| For Occupational/Cont | rolled Exposure (5 | mW/cm ²)= | 8.73 | Meters | |
| For General Population | | | 19.52 | Meters | |
| • | | , | | | |