

Per CFR 47, section 1.1307.b(1), Table 1, all applications for experimental operations with an ERP greater than 100 watts require evaluation for compliance with human exposure limits defined in section 1.1310, and if exceeded require submission of an Environmental Assessment as defined in section 1.1311.

The below calculations define the minimum safe working distance for both Occupational and General Public, which are based on the maximum permissible exposure limits of 5 mW/cm<sup>2</sup> and 1 mW/cm<sup>2</sup> respectively.

The antenna directional antenna operated in a controlled area, and will be directed towards the aircraft in flight. Only authorized occupational workers will be allowed access to the area of operation. In addition the transmitter will be secured prior to conducting maintenance, and the area will be monitored during the operation to ensure that personnel are clear of any radiation hazard area.

Transmitter Peak Power (Watts):	.7
Maximum Antenna Gain (dBi):	26.5
Duty Cycle (%):	1
Transmitter Power (dBm):	28.451
EIRP (dBm):	54.951
Non-dimensional Antenna Gain:	446.6836
Transmitter Avg Power (Watts):	0.007
EIRP Watts:	312.6785
Avg EIRP Watts:	3.1268

**Minimum Safe Distance**

Occupational

General Public

Meters:

Feet:

**0.0705**

**0.1577**

**0.2314**

**0.5175**