



Technical Brief Intellicom Location

April 27, 2019



ITC Document No:
20190427m01v01.0_Tech_Brief_ITC.docx

Prepared by
Intellicom Technologies, Inc.

Approved by:

Paul Moller
Vice-President, Intellicom Technologies Inc.

This document contains confidential Technical Data considered to be a commercially valuable resource. This data is provided strictly in support of obtaining an FCC license. The document is provided to satellite operators and the FCC in support of the licensing process. The document shall not be distributed to any party that is not supporting evaluation of the license application.



1 TABLE OF CONTENTS

- 1 TABLE OF CONTENTS.....2
- 2 INTRODUCTION4
- 3 SYSTEM DESCRIPTION.....5
 - 3.1 Satellites (Points of Communication)5
 - 3.2 Earth Stations6
 - 3.3 Points of Contact7
- 4 Antenna Patterns - AVL Model 13158
 - 4.1 Summary8
 - 4.2 Tx LHCP Azimuth9
 - 4.3 Tx RHCP Azimuth12
 - 4.4 Tx LHCP Elevation15
 - 4.5 Tx RHCP Elevation.....18
- 5 Antenna Patterns - AVL/Viasat BAT-60021
 - 5.1 Summary21
 - 5.2 Tx LHCP Azimuth22
 - 5.3 Tx RHCP Azimuth23
 - 5.4 Tx LHCP Elevation24
 - 5.5 Tx RHCP Elevation.....25



Revision History

Revision History:	Date	Document Revision Description
V01.0	2019 04 27	Initial Release



2 INTRODUCTION

We are seeking an FCC experimental license for testing, evaluation, and certification of fixed earth stations.

As a commercial entity we are seeking a license to transmit within 28.5 to 31 GHz. Transmissions will be coordinated and approved in advance with the commercial and government satellite operators.

Since the 30-31 GHz band is assigned for federal use, we anticipate that FCC will need to coordinate with the NTIA via the IRAC Interdepartmental Radio Advisory Committee. The earth stations will be owned and tested and certified by a commercial entity. Future ARSTRAT certified earth stations will be manufactured and sold to the US Government for their use. We are including a statement of US government interest and a government point of contact supporting this activity.

The earth stations are compliant with **47CFR §25.209**.

Please contact the following for additional information, comments, or clarifications:

Paul Moller
Intellicom Technologies, Inc.
480-993-2220
PMoller@ITCcom.net
www.ITCcom.net



3 SYSTEM DESCRIPTION

This section provides a description of the SATCOM system.

3.1 Satellites (Points of Communication)

We are requesting a license for U.S. licensed space stations.

Satellites include:

- Only with authorization from ARSTRAT
 - WGS5 at 52.5W
 - WGS6 at 135W
- Only with authorization from Inmarsat
 - Inmarsat I-5 F2 (55W)



3.2 Earth Stations

Location	Intellicom Technologies 3215 N Arizona Ave, Suite B18 Chandler, Az 85225
Coordinates	33°21'06" N 111°50'24" W
Elevation Range	16 to 44 degrees
Azimuth Range	108 to 218 degrees

Earth Station Attributes															
ID	Band	Terminal	Model	Antenna	HPA psat (dBm)	HPA sat (watts)	WG Loss (dB)	Power Into Feed (dBm)	Power Into Feed (watts)	Gtx (dBi)	EIRP (dBW)	EIRP kW	Grx (dBi)	G/T (dB/K)	Description
1	ka	AVL/Viasat	BAT-600 MMT	60cm	42.9	19.4	0.67	42.2	16.6	44.4	56.6	457	40.2	17	First Article
2	ka	AVL	Model 1315	130cm	41.3	13.5	0	41.3	13.5	50.9	62.2	1660	46.2	22	First Article

Earth Station Pointing Angles			
20190329m12v01.0_Terminal_Specs.xlsx			
Intellicom, Chandler			
33.351715N			
111.840019W			
			Earth Station Pointing
Satellites	Location (degrees)	Elevation (degrees)	True Azimuth (degrees)
WGS5 at 52.5W	52.5W	16.9	108.1
Inmarsat I-5 F2 (55W)	55W	19.0	109.8
WGS6 at 135W	135W	43.9	217.9
	Min	16	108
	Max	44	218



3.3 Points of Contact

Primary Contact:

Paul Moller
PMoller@ITCcom.net
Office: 480.993.2220
Cell: 480.226.1493
Intellicom Technologies, Inc

Secondary Contact:

Jesse Hindemith
JHindemith@ITCcom.net
Office: 858.486.1115
Cell: 858.663.4520
Intellicom Technologies, Inc



4 Antenna Patterns - AVL Model 1315

4.1 Summary

Transmit Gain and Axial Ratio			
	30.000 GHz	30.500 GHz	31.000 GHz
Gain, dBi LHCP	50.6	50.7	50.9
Gain, dBi RHCP	50.6	50.7	50.9
Axial Ratio, (dB) LHCP	0.8	0.9	0.7
Axial Ratio, (dB) RHCP	0.8	0.9	0.7



3 dB beamwidth in Azimuth is +/-0.3 or 0.6 degrees



The antenna is compliant with:



- CFR-2010-title47-vol2-sec25-209
- Mil-Std-188-164



4.2 Tx LHCP Azimuth















4.3 Tx RHCP Azimuth















4.4 Tx LHCP Elevation















4.5 Tx RHCP Elevation









5 Antenna Patterns - AVL/Viasat BAT-600

5.1 Summary

Transmit Gain and Axial Ratio			
	30.0GHz	30.5GHz	31.0GHz
Gain,dBi LHCP	43.9	43.9	44.4
Gain,dBi RHCP	44.1	43.9	44.2
Axial Ratio,dB LHCP	0.51	0.45	0.69
Axial Ratio, dB RHCP	0.42	0.49	0.77


3 dB beamwidth in Azimuth is 0.9 degrees

The antenna is compliant with:

- CFR-2010-title47-vol2-sec25-209
- Mil-Std-188-164






5.2 Tx LHCP Azimuth








5.3 Tx RHCP Azimuth





5.4 Tx LHCP Elevation





5.5 Tx RHCP Elevation

