Request for Experimental Authorization

McQ Inc. herein requests experimental authority to demonstrate and test earth station facilities in connection with Iridium Satellite LLC's non-geostationary satellite orbit space station constellation (Call Sign S2110) in the manner described below. McQ Inc. seeks authority for a period of twenty-four (24) months.

The 3 earth station terminals are experimental proto-type terminals at a single location, mounted near ground level. The antennas are low- gain omni-directional antennas with a hemispheric coverage having a maximum +3 dBi gain.

Necessary Bandwidth Description

The necessary bandwidth is determined by the frequency channelization that Iridium uses and is filed with other Iridium licenses. The frequency of a center of an Iridium channel can be calculated by this equation. There are 270 channels numbered 1 to 270 for transmit and 7 more that are receive only.

 $chan_{frequency} = 1616 \times 10^{6} + ((41.6666 \times 10^{3}) \times ((chan_{number} - 1) + 0.5)) MHz$

Ground Station Locations

- McQ Inc Engineering Building
- 38°21'24.67"N 77°27'27.49"W
- 1551 Forbes St, Fredericksburg, VA 22405
- Antenna Elevation: 30meters above mean sea level
- Antenna Elevation: 1 meter above ground level

| Lower Freq MHz | Upper Freq MHz | Input Power (watts) ¹ | ERP (watts) ² | Mean /Peak | Freq. Tolerance (%) | Station Class |
|-------------------|----------------------|--|-----------------------------|---------------|---------------------------|------------------|
| 1618.725 | 1626.0 | 1.8 | 4.8 | М | 0.0021 | FX |
| 1618.725 | 1626.0 | 1.8 | 4.8 | М | 0.0021 | FX |
| 1618.725 | 1626.0 | 1.8 | 4.8 | М | 0.0021 | FX |
| 1618.725 | 1626.0 | 6.0 | 9.0 | М | 0.0021 | FX |

Table 1: Particulars of Operation

¹ **NOTE**: defined as the nominal mean power input from the 9770 into the antenna

²**NOTE**: ERP(dBW) = EIRP(dBW) - 2.15 dB.

Table 2: Emission Data

| Emission Designator | Modulating Signal | Necessary Bandwidth (KHz) |
|---------------------|-------------------|---------------------------|
| 41K7Q7W | 25,000 | 41.7 |
| 41K7Q7W | 30,000 | 41.7 |
| 83K0Q7W | 60,000 | 83.0 |
| 333KQ7W | 175,000 | 333.33 |

Table 3: Waveforms and types of antennas used as well as the number of carriers

| Waveform | Modulation Scheme | Antenna Type | Number of Carriers |
|--------------|-------------------|--------------|--------------------|
| B1 (Block 1) | DEQPSK | LGA | 1 |
| C1 (NEXT) | QPSK | LGA | 1 |
| C2 (NEXT) | QPSK | LGA | 1 |
| 1XC8 (NEXT) | QPSK | LGA | 1 |

Table 4: Beamwidth and Antenna Gain

| | 3dB Beamwidth (degrees) | Gain (dBi) |
|----------|-------------------------|------------|
| Transmit | Hemisphere Omni | 3.0 |
| Receive | Hemisphere Omni | 3.0 |