

ThinSat-2 NTIA Space record data form

NTIA requires the following data for space related experiments using government shared spectrum. For each transmit frequency, please provide the data for both ends of the transmit-receive link. Use Part A to describe the satellite to ground (or to other satellite) information. Part B is for all ground to space transmit links.

Part A: Space to Earth Space Downlink Data (From THINSAT-2 to the Globalstar Constellation)

Satellite Simplex Transmitter Data

Transmit Frequency: 1616.25 MHz		
Satellite Name: THINSAT-2		
Data Field	Data Answer	Description/Comments
Polarization (XAP)	XAP = XAP01 L	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Orientation (XAZ)	XAZ = XAZ01 NB	NB= NARROWBEAM EC = EARTH COVERAGE
Antenna Dimension (XAD)	ANTENNA GAIN <u> 5 </u> BEAMWIDTH <u> 100 </u> XAD = XAD01 05G100B	(NTIA format (XAD), EXAMPLE, XAD01 16G030B)
Type of satellite (State = SP) (City = geo or non)	Type = non	Choose either: Geostationary or Nongeostationary
For Geostationary	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).

For Nongeostationary (Orbital Data)	INCLINATION ANGLE_____51.6_____, APOGEE IN KILOMETERS_____260_____, PERIGEE IN KILOMETERS_____180_____, ORBITAL PERIOD IN HOURS __1____ AND FRACTIONS OF HOURS IN DECIMAL_.48__, THE NUMBER OF SATELLITES IN THE SYSTEM____1_____, ORB = ORB,51.6IN00260AP00180PE001.48H01NRT01 ORB,52.0IN01414AP01414PE001.90H48NRR01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRT01
-------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (THINSAT-2)

Receiver Data Globalstar Satellite

Satellite Receive Specifications		
Polarization (RAP)	RAP = RAP 01 T	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Azimuth (RAZ)	RAZ = NB	NB= NARROWBEAM EC = EARTH COVERAGE
Dimension (RAD)	ANTENNA GAIN_____12_____ BEAMWIDTH _____037_____ RAD = RAD01 12G037B	(NTIA format (RAD), EXAMPLE, RAD01 16G030B)
Type of satellite (State = SP) City = G/No	Type = Non	Choose either: Geostationary or Nongeostationary

For Geostationary	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
----------------------	-------------	---------------------------------------------------------------------------------------------------------------------------------------------

For Nongeostationary (Orbital Data)	INCLINATION ANGLE_____52_____, APOGEE IN KILOMETERS_____1414_____, PERIGEE IN KILOMETERS_____1414_____, ORBITAL PERIOD IN HOURS __1____ AND FRACTIONS OF HOURS IN DECIMAL_.90____, THE NUMBER OF SATELLITES IN THE SYSTEM_____48_____, ORB = ORB,52.0IN01414AP01414PE001.90H48NRR01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
-------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Part B: Ground Station, Earth to THINSAT-2 S Band Receiver, Up link data:

Earth Station Transmitter Data

Transmit Frequency: MHz		
State (XSC)	XSC = IN	
City Name (XAL)	XAL = UPLAND	
Latitude (DDMMSS)	Lat = 402553	
Longitude (DDDMMSS)	Lon = 0853030	
Antenna Polarization (XAP)	XAP = XAP01 L	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Antenna Azimuth (XAZ)	Min Elevation is 60 degrees XAZ = XAZ01 V60	THE EARTH STATION Transmitter ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, XAZ01 V00
Antenna Dimensions (XAD)	ANTENNA GAIN_____30_____, BEAMWIDTH_____5_____, AZIMUTHAL RANGE___0 - 360_____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _276_____ THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____2_____ XAD =	EXAMPLE ASSUMING NONGEOSTATIONARY, XAD01 16G030B000-360A00357H006

Satellite Receive Specification, S Band Uplink		
Polarization (RAP)	RAP = RAP 01 L	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Azimuth (RAZ)	RAZ = NB	NB= NARROWBEAM EC = EARTH COVERAGE
Dimension (RAD)	ANTENNA GAIN__5____ BEAMWIDTH __80____ RAD = RAD01 05G080B	(NTIA format (RAD), EXAMPLE, RAD01 16G030B)
Type of satellite (State = SP) City = G/No	Type = Non	Choose either: Geostationary or Nongeostationary

For Geostationary	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE____51.6____, APOGEE IN KILOMETERS____260____, PERIGEE IN KILOMETERS____180____, ORBITAL PERIOD IN HOURS __1____ AND FRACTIONS OF HOURS IN DECIMAL_.48____, THE NUMBER OF SATELLITES IN THE SYSTEM____1____, ORB = ORB,51.6IN00260AP00180PE001.48H01NRR01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01