## 8 FOOT HIGH GAIN ANTENNA COLLINS GROUND BASED DOPPLER WEATHER RADAR SYSTEM

**RECEIVER/TRANSMITTER** WRT-701CG

Signal Processor Pulse Pair

Ground Clutter Suppression Based on Pulse-to-Pulse amplitude

signature recognition of Doppler

spectrum width

Maximum Precipitation Detection 320 Nautical miles

Maximum Doppler Turbulence 50 Nautical miles

and Mean Velocity Detection

Doppler Detection Pulse pair variances:

turbulence 5 to 12 meters per second

(m/s) in 1 m/s increments 4 bit Mean Velocity <u>+</u> 20 m/s in

2.5 m/s increments

Operating Frequency Range 5350 - 5460 MHz

Output Power 200 Watts peak (nominal)

Pulse Repetition Frequency 181/362 precipitation

1448 Doppler turbulence

Pulse Width 2 to 20 microseconds, variable

Measured Field Power <1.5 mw/cm<sup>2</sup>

Doppler Mode Pulse Width 6.8 microseconds

RF Power, Peak 170-250 Watts (peak)

**ANTENNA** 

Antenna Type 8 foot parabolic dish with horizontally

polarized feed

Beam Width 1.75 degrees maximum

Gain 38 dB minimum

1st Side Lobe -25dB maximum referenced to

main lobe

Effective Radiated Power 985 kw