

**EXHIBIT 3
TECHNICAL INFORMATION**

Applicant Name: Rearden LLC
Applicant FRN: 0028363158

Contact Details

Name of Contact:	Cindy Ievers
Contact Mailing Address:	Rearden LLC

Transmitter Equipment

Equipment Manuf / PN:	Rearden LLC Custom Remote Radio Head Commercial LTE user devices
------------------------------	---

Frequency Range /Tolerance		High (MHz)	Low (MHz)		
		3550.0000	3400.0000		
Frequency Range / Tolerance	Modulation	Emission Designator	Bandwidth (MHz)	Power Out (Watts)	ERP
	Digital	50M0W7W	50	100 mW	3.000000 W
Antenna Details					
Type			Custom Remote Radio Head Antenna		
Quantity			Not to exceed 100		
Gain			17 dBi		
Beam Width at Half-Power Point			90°		
Orientation in Horizontal Plane			NA		
Orientation in Vertical Plane			NA		

Frequency Range /Tolerance		High (MHz)	Low (MHz)		
		3700.0000	3650.0000		
Frequency Range / Tolerance	Modulation	Emission Designator	Bandwidth (MHz)	Power Out (Watts)	ERP
	Digital	50M0W7W	50	100 mW	3.000000 W
Antenna Details					
Type			Custom Remote Radio Head Antenna		
Quantity			Not to exceed 100		

EXHIBIT 3- TECHNICAL INFORMATION

Gain	17 dBi
Beam Width at Half-Power Point	90°
Orientation in Horizontal Plane	NA
Orientation in Vertical Plane	NA

Frequency Range /Tolerance		High (MHz)		Low (MHz)	
		3550.0000		3400.0000	
Frequency Range / Tolerance	Modulation	Emission Designator	Bandwidth (MHz)	Power Out (Watts)	ERP
	Digital	50M0W7W	50	100 mW	1.000000 W
Antenna Details					
Type		Custom Remote Radio Head Antenna			
Quantity		Not to exceed 100			
Gain		12 dBi			
Beam Width at Half-Power Point		60°			
Orientation in Horizontal Plane		NA			
Orientation in Vertical Plane		NA			

Frequency Range /Tolerance		High (MHz)		Low (MHz)	
		3700.0000		3650.0000	
Frequency Range / Tolerance	Modulation	Emission Designator	Bandwidth (MHz)	Power Out (Watts)	ERP
	Digital	50M0W7W	50	100 mW	1.000000 W
Antenna Details					
Type		Custom Remote Radio Head Antenna			
Quantity		Not to exceed 100			
Gain		12 dBi			
Beam Width at Half-Power Point		60°			
Orientation in Horizontal Plane		NA			
Orientation in Vertical Plane		NA			

EXHIBIT 3- TECHNICAL INFORMATION

Frequency Range /Tolerance		High (MHz)		Low (MHz)	
		3550.0000		3400.0000	
Frequency Range / Tolerance	Modulation	Emission Designator	Bandwidth (MHz)	Power Out (Watts)	ERP
	Digital	50M0W7W	50	100 mW	1.000000 W
Antenna Details					
Type			Custom Remote Radio Head Antenna		
Quantity			Not to exceed 100		
Gain			12 dBi		
Beam Width at Half-Power Point			360°		
Orientation in Horizontal Plane			NA		
Orientation in Vertical Plane			NA		

Frequency Range /Tolerance		High (MHz)		Low (MHz)	
		3700.0000		3650.0000	
Frequency Range / Tolerance	Modulation	Emission Designator	Bandwidth (MHz)	Power Out (Watts)	ERP
	Digital	50M0W7W	50	100 mW	1.000000 W
Antenna Details					
Type			Custom Remote Radio Head Antenna		
Quantity			Not to exceed 100		
Gain			12 dBi		
Beam Width at Half-Power Point			360°		
Orientation in Horizontal Plane			NA		
Orientation in Vertical Plane			NA		

Stations Details

Number of Fixed Terminals	100
----------------------------------	-----

Location of Terminal (Lat / Long. NAD 83)

Station Location #	Latitude	Longitude
1	North 37 23 11	West 122 03 48
2	North 37 19 58	West 121 54 05