

## NTIA Space record data form

NTIA requires the following data for space related experiments using government shared spectrum. For each transmit frequency, please provide the data for both ends of the transmit-receive link. Use Part A to describe the satellite to ground information. Part B is for all ground to space transmit links.

### Part A: Space to Earth Downlink Data

#### Satellite Transmitter Data

Transmit Frequency: <span style="color: blue;">137.950 MHz</span>		
Satellite Name: <span style="color: blue;">BEE</span>		
Data Field	Data Answer	Description/Comments
Polarization (XAP)	XAP = <span style="color: blue;">V</span>	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Orientation (XAZ)	XAZ = <span style="color: blue;">EC</span>	NB= NARROWBEAM EC = EARTH COVERAGE
Antenna Dimension (XAD)	ANTENNA GAIN = <span style="color: blue;">2.17 dBi</span> BEAMWIDTH = <span style="color: blue;">Toroidal</span> HPBW = <span style="color: blue;">90 x 360 degrees.</span> XAD = <span style="color: blue;">XAD01 02G090B</span>	(NTIA format (XAD), EXAMPLE, XAD01 16G030B)
Type of satellite (State = SP) (City = geo or non)	Type = <span style="color: blue;">Nongeostationary</span> State = <span style="color: blue;">SP</span> City = <span style="color: blue;">non</span>	Choose either: Geostationary or Nongeostationary
For Geostationary	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <span style="color: blue;">97.7</span> , APOGEE IN KILOMETERS <span style="color: blue;">580</span> , PERIGEE IN KILOMETERS <span style="color: blue;">580</span> , ORBITAL PERIOD IN HOURS <span style="color: blue;">1</span> AND FRACTIONS OF HOURS IN DECIMAL <span style="color: blue;">0.605</span> , THE NUMBER OF SATELLITES IN THE SYSTEM <span style="color: blue;">4</span> ,  ORB = <span style="color: blue;">ORB,097.7IN00580AP00580PE0001.6H04 NNRT01</span>	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01

<b>Earth Station Data (Receiver) #1</b>		
State (RSC)	RSC = CA	
City Name (RAL)	RAL = Los Altos	
Latitude (DDMMSS)	Lat = 37 22 54 N	
Longitude (DDMMSS)	Lon = 122 05 50 W	
Antenna Polarization (RAP)	RAP = V	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Antenna Azimuth (RAZ)	RAZ = 0-360 V00 to V90 (Azimuth = 0 to 360, Elevation 0 to 90)	THE EARTH STATION RECEIVER ANTENNA AZIMUTH (RAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, RAZ01 V00
Antenna Dimensions (RAD)	ANTENNA GAIN _____ 4.50 _____, BEAMWIDTH _____ 180 _____, AZIMUTHAL RANGE __ 0 to 360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 48 _____ THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 3 _____  RAD = RAD01 05G038B	EXAMPLE ASSUMING NONGEOSTATIONARY, RAD01 16G030B000-360A00357H006
FCC notes:		
1. Use S-Note S945. 2. REM AGN, Cubesat, (insert name)		

<b>Earth Station Data (Receiver) #2</b>		
State (RSC)	RSC = GA	
City Name (RAL)	RAL = Buford	
Latitude (DDMMSS)	Lat = 34 05 05 N	
Longitude (DDMMSS)	Lon = 083 56 51 W	
Antenna Polarization (RAP)	RAP = V	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Antenna Azimuth (RAZ)	RAZ = 0-360 V00 to V90	THE EARTH STATION RECEIVER ANTENNA AZIMUTH (RAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, RAZ01 V00

	(Azimuth = 0 to 360, Elevation 0 to 90)	
Antenna Dimensions (RAD)	ANTENNA GAIN_____4.5_____, BEAMWIDTH_____180_____, AZIMUTHAL RANGE__0 to 360_____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____48_____ THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____3_____  RAD = RAD01 05G038B	EXAMPLE ASSUMING NONGEOSTATIONARY, RAD01 16G030B000-360A00357H006
FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (insert name)		

## Part B: Ground Stations, Earth to Space link data:

### Earth Station Transmitter Data #1

Transmit Frequency: 137.950 MHz		
State (XSC)	XSC = CA	
City Name (XAL)	XAL = Los Altos	
Latitude (DDMMSS)	Lat = 37 22 54 N	
Longitude (DDDMMSS)	Lon = 122 5 50 W	
Antenna Polarization (XAP)	XAP = V	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Antenna Azimuth (XAZ)	XAZ = 0-360 V00 to V90 (Azimuth = 0 to 360, Elevation 0 to 90)	THE EARTH STATION Transmitter ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, XAZ01 V00
Antenna Dimensions (RAD)	ANTENNA GAIN _____ 4.5 _____, BEAMWIDTH _____ 180 _____, AZIMUTHAL RANGE__ 0 to 360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 48 _____ THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 3 _____  RAD = RAD01 05G038B	EXAMPLE ASSUMING NONGEOSTATIONARY, XAD01 16G030B000-360A00357H006
<b>Satellite Receive Specifications</b>		
Polarization (RAP)	RAP = V	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Azimuth (RAZ)	RAZ = EC	STATION RECEIVER ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, RAZ01 V00
Dimension (XAD)	ANTENNA GAIN = 2.17 dBi BEAMWIDTH = Toroidal HPBW = 90 x 360 degrees. XAD = XAD01 02G090B	(NTIA format (RAD), EXAMPLE, RAD01 16G030B)
Type of satellite (State = SP)	Type = Nongeostationary State = SP	Choose either: Geostationary or Nongeostationary

City = G/No	City = non	
For Geostationary	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.7</u> , APOGEE IN KILOMETERS <u>580</u> , PERIGEE IN KILOMETERS <u>580</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.605</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>4</u> ,  ORB = <u>ORB,097.7IN00580AP00580PE0001.6H04NNRR01</u>	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01

#### Earth Station Transmitter Data #2

Transmit Frequency: 137.950 MHz		
State (XSC)	XSC = GA	
City Name (XAL)	XAL = Buford	
Latitude (DDMMSS)	Lat = 34 05 05 N	
Longitude (DDDMMSS)	Lon = 083 56 51 W	
Antenna Polarization (XAP)	XAP = V	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Antenna Azimuth (XAZ)	XAZ = 0-360 V00 to V90 (Azimuth = 0 to 360, Elevation 0 to 90)	THE EARTH STATION Transmitter ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, XAZ01 V00
Antenna Dimensions (RAD)	AANTENNA GAIN <u>4.5</u> , BEAMWIDTH <u>180</u> , AZIMUTHAL RANGE <u>0 to 360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>48</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>3</u> ,  RAD = RAD01 05G038B	EXAMPLE ASSUMING NONGEOSTATIONARY, XAD01 16G030B000-360A00357H006
<b>Satellite Receive Specifications</b>		

Polarization (RAP)	RAP = V	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Azimuth (RAZ)	RAZ = EC	STATION RECEIVER ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, RAZ01 V00
Dimension (XAD)	ANTENNA GAIN = 2.17 dBi BEAMWIDTH = Toroidal HPBW = 90 x 360 degrees. XAD = XAD01 02G090B	(NTIA format (RAD), EXAMPLE, RAD01 16G030B)
Type of satellite (State = SP) City = G/No	Type = Nongeostationary State = SP City = non	Choose either: Geostationary or Nongeostationary
For Geostationary	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE 97.7 , APOGEE IN KILOMETERS 580 , PERIGEE IN KILOMETERS 580 , ORBITAL PERIOD IN HOURS 1 AND FRACTIONS OF HOURS IN DECIMAL 0.605 , THE NUMBER OF SATELLITES IN THE SYSTEM 4 ,  ORB = ORB,097.7IN00580AP00580PE0001.6H04 NNRR01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01