

Per CFR 47, section 1.1307.b(1), Table 1, all applications for experimental operations with an ERP greater than 100 watts require evaluation for compliance with human exposure limits defined in section 1.1310, and if exceeded require submission of an Environmental Assessment as defined in section 1.1311.

The below calculations define the minimum safe working distance for both Occupational and General Public, which are based on the maximum permissible exposure limits of 5 mW/cm² and 1 mW/cm² respectively.

The antenna is a AN/ASC-24(V)4 - Thinkom Ka2517 antenna array. The antenna will be operated in a controlled area. Only authorized occupational workers will be allowed access to the area of operation. In addition the transmitter will be secured prior to conducting maintenance, and the area will be monitored during the operation to ensure that personnel are clear of any radiation hazard area.



Transmitter Peak Power (Watts):	1.1611
Maximum Antenna Gain (dBi):	50.5
Duty Cycle (%):	100
Transmitter Power (dBm):	30.6487
EIRP (dBm):	81.1487
Non-dimensional Antenna Gain:	112201.8454
Transmitter Avg Power (Watts):	1.1611
EIRP Watts:	97724
Avg EIRP Watts:	97724

Minimum Safe Distance

	Occupational	General Public
Meters:	14.3994	32.1981
Feet:	47.2416	105.6354