

Technical Description

The Boeing Company

Submitted: 10/29/2018

By Allen Lindsay, SR

Frequency Manager

Global Spectrum Management MC: 1K-105

P.O. Box 3707

Seattle, WA 98124-2207

(425)237-9168

Start Date: 11/14/2018

Stop Date: 05/14/2019

8.3.28 Use of Fixed Devices That Re-Radiate Signals Received From the Global Positioning System

Except as otherwise authorized under Section 7.14, federal agencies and departments may, under the following conditions, operate fixed devices that re-radiate signals received from the GPS.

Individual authorization is for indoor use only, and is required for each device at a specific site.

Boeing is requesting use for a hangar with exterior doors. Boeing will apply for licenses for all devices.

a. Applications for frequency assignment should be applied for as an XT station class with a note indicating the device is to be used as an "Experimental RNSS Test Equipment for the purpose of testing GPS receivers" and describing how the device will be used.

Experimental RNSS Test Equipment for the purpose of testing GPS receivers for aircraft within a Boeing Hangar.

b. Approved applications for frequency assignment will be entered in the GMF.

Boeing Concurs

c. The maximum length of the assignment will be two years, with possible renewal.

The Boeing Company is requesting a Special Temporary Authorization (STA) at this time.

d. The area of potential interference to GPS reception (e.g., military or contractor facility) has to be under the control of the user. Areas beyond the range for potential interference are protected by the maximum power calculation described in f. below, and thus no further record notes are required for frequency assignments.

Application is for a Boeing owned hangar on Boeing owned property.

e. The equivalent isotropically radiated power (EIRP) must be such that the emissions are no greater than -140 dBm/24 MHz as received by an isotropic antenna at a distance of 100 feet (30 meters) from the building where the test is being conducted. The calculation for maximum EIRP shall be based on free space propagation with no allowance for additional attenuation (e.g., building attenuation) as shown below.

Technical Description

$PT_{max} = PR + 20\log_{10}f + 20\log_{10}(30+d) - 27.55$ Where: PT_{max} is the maximum permissible EIRP in dBm.

PR is the power received at 30 meters from the building (i.e. -140 dBm/24 MHz)

f is frequency in MHz (i.e. 1575.42 for L1, 1227.60 for L2)

d is the distance between the radiator and the closest exterior wall of the building in meters. PT_{max} can then be converted to picowatts by using the formula: $PT_{m}(pW) = 10^{(PT_{max} - 10)/10}$ Applications requesting power greater than the PT_{max} calculated at $d = 0$ meters (i.e. 39.3 pW for L1, 23.8pW for L2) must provide the distance from the transmit antenna to the nearest exterior wall so that reviewing agencies can determine if the requested power meets the maximum EIRP described above.

Application is for 39.3 pW for L1, 23.8pW for L2. Analysis will be performed to ensure that equipment does not exceed the power limits provided should application be granted.

f. GPS users in the area of potential interference to GPS reception must be notified that GPS information may be impacted for periods of time.

Signs will be posted at all entrances to hangar.

g. The use is limited to activity for the purpose of testing RNSS equipment/systems.

Boeing Concur

h. A "Stop Buzzer" point of contact for the authorized device must be identified and available at all times during GPS re-radiator operations.

Stop Buzzer for Everett is: Christina M, Westover, 425-342-7015

Manufacturer:	GPS Networking Inc
Model:	L1GPSA-N; LA20RPDC; F12
Frequencies:	1227.6 MHz
Emissions:	24M0G1D
ERP:	23.8 pW

Frequencies:	1575.42 MHz
Emissions:	24M0G1D
ERP:	39.3 pW

Locations:

Building: 47-173

Lat/Lon: 47 56 17 N; 122 16 10 W

Everett, WA