

7/24/2015

• • •

George R. Blake University of Kansas 1530 W. 15th Street Learned Hall Room 2120 Lawrence, KS 66045

Federal Communications Commission 445 12th Street, SW Washington, DC 20554

Applicant:	University of Kansas
File Number:	0417-EX-PL-2015
Correspondence Reference Number:	28830
Date of Original Email:	07/23/2015

In response to the above mentioned correspondence, we offer the following information:

8.3.28 Use of Fixed Devices that Re-Radiate Signals Received from a GPS Antenna

8.3.28 Use of Fixed Devices That Re-Radiate Signals Received from the Global Positioning System Except as otherwise authorized under Part 7.14, federal agencies and departments may, under the following conditions, operate fixed devices that re-radiate signals received from the Global Positioning System (GPS).

1. Individual authorization is for indoor use only, and is required for each device at a specific site. <u>YES</u>

2. Applications for frequency assignment should be applied for as an XT station class with a note indicating the device is to be used as an Experimental RNSS Test Equipment for the purpose of testing GPS receivers" and describing how the device will be used. <u>YES</u>

3. Approved applications for frequency assignment will be entered in the GMF. YES

4. The maximum length of the assignment will be two years, with possible renewal. YES

5. The area of potential interference to GPS reception (e.g., military or contractor facility) has to be under the control of the user. <u>YES</u>

6. The maximum equivalent isotropically radiated power (EIRP) must be such that the calculated emissions are no greater than -140 dBm/24 MHz as received by an isotropic antenna at a distance of 100 feet (30 meters) from the building where the test is being conducted. The calculations showing compliance with this requirement must be provided with the application for frequency assignment and should be based on free space propagation with no allowance for additional attenuation (e.g., building attenuation.) *SEE EXISTING EXHIBIT FOR ERP CALCULATIONS*

University of Kansas

7. GPS users in the area of potential interference to GPS reception must be notified that GPS information may be impacted for periods of time. <u>YES</u>

8. The use is limited to activity for the purpose of testing RNSS equipment/systems. <u>YES</u>

9. A "Stop Buzzer" point of contact for the authorized device must be identified and available at all times during GPS re-radiation operation of the device under any condition. <u>YES—Contact Information is</u> <u>accurate and up-to-date</u>. George R. Blake – Laboratory Coordinator / Avionics Technician – University of Kansas, Aerospace Engineering Department – 785-842-8927 – <u>mailto:grblake@ku.edu</u>

George R. Blake Laboratory Coordinator / Avionics Technician University of Kansas 785-842-8927