

NTIA Additional Fields
CADRE

1.) Nongeostationary

B.) 55° inclination, 700 km apogee, 342 km perigee, 1.5 hour period, 1 satellite

2.) Antenna 1: 0 dB antenna gain, 360° beamwidth === Antenna 2: 6 dB antenna gain, 360° beamwidth

3.) EC

4.) 18.9 dB antenna gain, 21° beamwidth, 0–360° azimuth range, site 30 m above sea level, 5 meter antenna height above terrain

5.) 0° minimum elevation

6.) S871

7.) Right hand circular transmit orientation, right hand circular receive orientation

1.) THE TYPE OF SATELLITE, GEOSTATIONARY OR NONGEOSTATIONARY, (XAL AND/OR RAL).

B.) IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB, 98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB, 72.9IN03209AP00655PE013.46H01NRR01

2.) THE SATELLITE TRANSMITTER ANTENNA GAIN AND BEAMWIDTH (XAD), EXAMPLE, XAD01 16G030B

3.) THE SATELLITE TRANSMITTER ANTENNA AZIMUTH (XAZ), NARROWBEAM, NB, EARTH COVERAGE, EC, EXAMPLE, XAZ01 EC OR LEAVE BLANK FOR SPACE-TO-SPACE OPERATIONS.

4.) THE EARTH STATION RECEIVER ANTENNA GAIN, BEAMWIDTH, AZIMUTHAL RANGE, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS AND THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS (RAD), EXAMPLE ASSUMING NONGEOSTATIONARY, RAD01 16G030B000-360A00357H006

5.) THE EARTH STATION RECEIVER ANTENNA AZIMUTH (RAZ), THE MINIMUM

ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, RAZ01 V00

6.) THE S NOTE (ASSUMING NONGEOSTATIONARY, USE S871--THIS ASSIGNMENT SUPPORTS OF THE NON-GEOSTATIONARY CUBESAT TEST BED (CSTB) SATELLITE).

7.) THE TRANSMITTER ANTENNA ORIENTATION (XAP), EXAMPLE XAP01 J , AND THE RECEIVER ANTENNA ORIENTATION (RAP), EXAMPLE RAP01 J , WHERE J REPRESENTS LINEAR POLARIZATION. OTHER POLARIZATIONS INCLUDE H FOR HORIZONTAL, V FOR VERTICAL, S FOR HORIZONTAL AND VERTICAL, L FOR LEFT HAND CIRCULAR, R FOR RIGHT HAND CIRCULAR, T FOR RIGHT AND LEFT HAND CIRCULAR, E FOR ELLIPTICAL AND O FOR OBLIQUE ANGLED CROSSED.
