Vivint Wireless File No. 0273-EX-CN-2018 Exhibit B

EXHIBIT B - TECHNICAL INFORMATION

Applicant Name: Vivint Wireless **Applicant FRN:** 0022792816

Technical Contact Details

Name of Contact:	Jason Hruban	
Contact Details:	Network Planning Manager	
	Vivint Wireless, Inc.	
	4931 North 300 West	
	Provo, UT 84604	
	Phone: 801-705-8037	
	Email: jhruban@vivint.com	
Charld any intenference	he man arted the man and viill access immediately unless and until the	

Should any interference be reported, the proposed will cease immediately unless and until the interference incident has been resolved. The technical point of contact above has "kill switch" capability for all devices involved in the proposed market trial.

Legal Contact Details

Name of Contact:	Timothy Bransford	
Contact Details:	Regulatory Counsel	
	Morgan, Lewis & Bockius LLP	
	1111 Pennsylvania Avenue, NW	
	Washington, DC 20004	
	Phone: 202-373-6140	
	Email: timothy.bransford@morganlewis.com	

Explanation

Vivint seeks authorization to undertake a market trial of prototype LTE equipment manufactured by OEM in Salt Lake County, Utah (Station 1). Please see **Exhibit A** to the instant application for a complementary narrative explanation of the proposed operations and justification for the market trial.

Vivint Wireless File No. 0273-EX-CN-2018 Exhibit B

Station 1 – Salt Lake County

Radius of Operation	Not to exceed 20 kilometers from geographic centerpoint		
	(Radius applicable to all STA operations)		
Geographic Centerpoint	40° 31' 21.58" N		
(Lat / Long. NAD 83)	111° 56' 14.83" W		
Elevation	4450 (@ centerpoint coordinates)		

Station 1 / Transmitter 1 - Small Cell Transmitter

Device Manufacturer & Model:	
Number of Transmitters:	Not to exceed 300

Frequency Range / Tolerance	High (MHz)	Low (MHz)
	3700.0000	3550.0000

Frequency Range / Tolerance	Modulation	Emission Designator	Bandwidth (MHz)	Power Out (Watts)	EIRP (dBW)
	Digital	D7D	18.5	0.631 W	6.31

Antenna Details	
Type	
Quantity	Not to exceed 300
Gain	10 dBi (@midband)
Beam Width at Half-	NA (Omni)
Power Point	
Orientation in	NA
Horizontal Plane	
Orientation in	NA
Vertical Plane	

Vivint Wireless File No. 0273-EX-CN-2018 Exhibit B

Station 1 / Transmitter 2 - Customer Premise Equipment (Outdoor Unit)

Device Manufacturer & Model:	
Number of Transmitters:	Not to exceed 900

Frequency Range / Tolerance	High (MHz)	Low (MHz)	
	3700.0000	3550.0000	

Frequency Range / Tolerance	Modulation	Emission Designator	Bandwidth (MHz)	Power Out (Watts)	EIRP (dBW)
	Digital	W7W	20.0	0.39	6.18

Antenna Details	
Type	Integrated
Quantity	Not to exceed 900
Gain	12 dBi (@midband)
Beam Width at Half-	63°
Power Point	
Orientation in	NA
Horizontal Plane	
Orientation in	NA
Vertical Plane	

Vivint Wireless File No. 0273-EX-CN-2018 Exhibit B

Station 1 / Transmitter 3 - Customer Premise Equipment (Indoor Unit)

Device Manufacturer & Model:	
Number of Transmitters:	Not to exceed 900

Frequency Range / Tolerance	High (MHz)	Low (MHz)		
	3700.0000	3550.0000		

Frequency	Modulation	Emission	Bandwidth	Power Out	EIRP
Range /		Designator	(MHz)	(Watts)	(dBW)
Tolerance					
	Digital	W7W	20.0	0.39	1.55

Antenna Details	
Type	Integrated
Quantity	Not to exceed 900
Gain	6 dBi (@midband)
Beam Width at Half-	NA (Omni)
Power Point	
Orientation in	NA
Horizontal Plane	
Orientation in	NA
Vertical Plane	