RADIATION CALCULATIONS FOR		1.20 meter EARTH STATION		
Nomenclature	Formula	Value	Unit	
INPUT PARAMETERS				
M = Antenna Aperture Major Axis m = Antenna Aperture Minor Axis d = Diameter of Feed Mouth f = frequency		1.20 1.20 0.133 14.25	meters meters meters GHz	
P = Max Power into Antenna		2.0	Watts	
n = Aperture Effeciency		63%		
k = Wavelength @ 14.25 GHz		0.0210	meters	
CALCULATED VALUES				
A = Area of Reflector	PlxMxm/4	1.131	meters^2	
I = Length of Near Field	M^2/4k	17	meters	
L = Beginning of Far Field	0.6M^2/k	41	meters	
G = Antenna Gain @ 14.25 GHz	n(4xPIxA)/k^2	20,230	(43.1) dBi	
a = Area of Feed Mouth	PI*d^2/4	0.0140	meters^2	
POWER DENSITY CALCULATIONS				
Region	Maximum Power Dens	sity in Region Value (mW/cm^2)		Hazard Assessment (FCC MPE Limit = 1 mW/cm^2)
	Torridia	value (IIIV/CIII*2)		(1 CO IVIF L LITTIL - 1 ITIVV/GIT''Z)
1 Near Field	4nP/A	0.45		< FCC MPE Limit
2 Far Field	GP/(4(PI)L^2)	0.19		< FCC MPE Limit
3 Transition	<= Nr Fld Region	0.45		< FCC MPE Limit
4 Near Reflector Surface	4P/A	0.71		< FCC MPE Limit
E Datuman Daffaster 9 Cround	D/Λ	0.40		∠ FOO MDE 1 imit