

Your source for quality GNSS Networking Solutions and Design Services, Now!

Change the values in the yellow boxes to calculate required readings

| A Receive Ant Gain | nt Cable Insertion Loss | Repeater Amp Gain | Repeater Ant Gain Best Case | Range in Feet | Repeated Signal Power @ Range In dBm |
|---|-------------------------------|----------------------|--------------------------------|--|--|
| 33 | -5 | 24 | 3 | 100 | -141.09 |
| GPS Carrier Frequency MHz Total System Gain 1575 55 | | | Range in Miles 0.02 | Total Signal Power @ Range in Watts 7.8E-18 | |
| Avg Receive Power L1 dBm North America -130 | | | | Range in Meters 31.17 | Radiated Power dBm -75 |
| Free Space | loss with Isotropic -66.09 | Antennas | | Range in Kilometers 0.03 | Transmitted Power (W) 15.8E-12 |
| | | | | | Effective Radiated Power (W) 19.2E-12 |
| | | | | | Effective Radiated Power (dBW) -105 |

Author: Allen Gross Doc. No.:22

Org.:Sales and Marketing Rev.:002



Your source for quality GNSS Networking Solutions and Design Services, Now!

Org.:Sales and Marketing Rev.:002

Author: Allen Gross Doc. No.:22