

\$\$ADD NG T210012
 TYP01 N
 DAT01 210126
 CLA01 U
 FRQ01 M1242.9375
 EXD01 221223
 STC01 XT
 EMS01 1M00G2D
 PWR01 W.00100
 XSC01 OR
 XAL01 PENDLETON
 XLA01 454127N
 XLG01 1185057W
 XAD01 DIPOLE 0006T
 XAP01 V
 XAZ01 ND
 RSC01 OR
 RAL01 PENDLETON
 RLA01 454127N
 RLG01 1185057W
 RAZ01 ND
 BUR01 FCC
 BIN01 -
 REM01 *FRB,M01242.937500,M01248.625000
 REM02 *EQT,C,GNI L1/L2GHNRRKIT
 REM03 *NTS,M018,FAA ,210126,RMURPHY,NG T210012
 SUP01 FCC FILE NO. 1032-EX-CN-2020: THE FAA CONCURS WITH THE UNDERSTANDING ITS
 SUP02 PURPOSE IS FOR GPS L2/L5/GLONASS TESTING WITH LEVELS AT -140 DBM/24 MHZ
 SUP03 AT 30 METERS FROM THE SHELTER PER NTIA 8.3.27. FOR PURPOSES OF PROTECTI
 SUP04 NG AVIATION OPERATIONS OUTSIDE OF L2/L5, THE FAA IS ADHERING TO THE SAME
 SUP05 STANDARD.