



## Electronic Filing

September 5, 2002

FEDERAL COMMUNICATIONS COMMISSION  
Experimental Radio Service  
P.O. Box 358320  
Pittsburgh, PA 15251-5320

Dear Sir or Madam:

This letter is to request an Special Temporary Authority (STA) to operate a transmitter in certain selected bands between 11.7 GHz to 12.2 GHz, and 14.0 to 14.5 in Plano (Collin County), Texas, and Miami (Dade County), Florida, as described below. In accordance with 47 CFR chapter 1, (10-1-00 edition), section 5.61, the attached Exhibit A – System Description is being provided to support the application.

Alcatel USA is planning a DVB-RCS platform to be used for a satellite 2-way broadband access demonstrations to customers for a limited period of time. Demonstrations are to begin on September 16, 2002 and will run until January 16, 2003. Since all outdoor work under this grant must be finished by September 16, Comsearch respectfully requests the FCC to expedite the approval of this STA request. If you have any questions please call.

Sincerely,  
COMSEARCH

Kenneth G. Ryan  
Director, Spectrum Management Services  
(703) 726-5685  
[kryan@comsearch.com](mailto:kryan@comsearch.com)

## **Exhibit A– System Description**

### **A.1 - Name, address, phone number of the applicant.**

Alcatel USA Marketing, Inc..  
Attn: Ravi Chari  
660 Data Drive  
Plano, Texas 75075  
Voice: (972) 477-2573  
Email: [ravi.chari@alcatel.com](mailto:ravi.chari@alcatel.com)

### **A.2 - Description of why a Special Temporary Authority (STA) is needed.**

Alcatel USA Marketing Inc., of Plano, Texas, is developing a project to test a DVB-RCS platform out of Montreal, Canada, into their Plano, Texas and Miami, Florida sites where terminals are located. This platform is to be used for a limited time, for a satellite 2-way broadband access demonstration to customers.

The reason for the STA request is to perform outdoor demonstrations between the hub location in Montreal, Canada and selected terminals in Plano, Texas and Miami, Florida.

### **A.3 Description of the operation to be conducted and its purpose**

Alcatel will perform real-time satellite link testing of their DVB equipment using a hub earth station located in Montreal, Canada and two US based transmit-receive VSATs, located in Plano, TX and Miami, FL.

The points of contact for each transmitting site are as follows:

#### Plano, Texas Site

Ravi Chari  
Alcatel USA Marketing, Inc.  
660 Data Drive  
Plano, Texas 75075  
Voice: (972) 477-2573  
Email: [ravi.chari@alcatel.com](mailto:ravi.chari@alcatel.com)

#### Miami, Florida Site

Olivier Badard  
Alcatel USA Marketing, Inc.  
Andesat  
7065 NW 52<sup>nd</sup> Street  
Miami, Florida 33166  
Voice: (305) 569-1440  
Email: [olivier.badard@space.alcatel.fr](mailto:olivier.badard@space.alcatel.fr)

#### **A.4 Time and dates of proposed operation.**

There will be demonstration sessions, from the Plano and Miami locations. It is anticipated that tests will be run during business hours and on weekends during daylight, beginning around September 16, 2002, and extending until about January 16, 2003.

#### **A.5 Class of station**

The transmitters, in both Miami and Plano, will be fixed all of the time.

#### **A.6 Description of the location and, if applicable, geographic coordinates of the proposed operation.**

All transmit signals will be from rooftop locations at the Plano, Texas (Coordinates: 33° – 00' – 32.5" North Latitude and 96° – 45' – 26.9" West Longitude), and Miami, Florida (Coordinates 25° 04' 15.4" North Latitude and 80° 18' – 43.5" West Longitude) sites.

#### **A.7 Equipment to be used, including name of manufacturer, model and number of units.**

The VSATs will use a Channel Master 1.2 meter antenna, model # 123, and 2 watt RFT transmitting at 1.8 watts. The 1.2 meter antenna gain is 43.3 dBi, the maximum EIRP out of both transmitting locations is 45.9 dBW. Both Miami and Plano will have same VSAT configurations.

#### **A.8 Frequencies Desired**

The tests will be performed in the US domestic FSS Ku-band. Transmissions will be between 14,000 and 14,500 MHz and reception will be between 11,700 and 12,200 MHz.

#### **A.9 Maximum effective radiated power (ERP) or equivalent isotropically radiated power (EIRP)**

A transmit antennas in Plano, Texas and Miami, Florida are Channel Master 1.2 meter earth stations (Model 123), with a gain of 43.3 dBi (at 14.25 GHz). The high powered amplifier is rated for 2 watts maximum. The maximum total EIRP at the feed flange of the earth stations will be 45.9 DBW, or a total RF power of 1.82 Watts.

#### **A.10 Emission designator and description of emission (bandwidth, modulation, etc.)**

The VSAT return link transmission is digital data at 210 ksps in an allocated bandwidth of 360 kHz. The received emission is a digital DVB signal at 7373 kbps in an allocated bandwidth of 11 MHz.

### **A.11 Overall height of antenna structure above the ground**

Both the Plano and Miami transmitters will be roof mounted no higher than 6' above roof top level.

## EXHIBIT B Miami, FL Site Data

### SATELLITE EARTH STATION

09/04/2002

|                                                |             |                                     |
|------------------------------------------------|-------------|-------------------------------------|
| Company                                        | ALCATEL USA |                                     |
| Earth Station Name, State                      |             | MIAMI, FL                           |
| Latitude (DMS) (NAD83)                         |             | 25 49 15.4 N                        |
| Longitude (DMS) (NAD83)                        |             | 80 18 43.5 W                        |
| Ground Elevation AMSL (Ft/m)                   |             | 5.02 / 1.53                         |
| Antenna Centerline AGL (Ft/m)                  |             | 50.00 / 15.24                       |
| Receive Antenna Type:                          | FCC32       | FCC Reference                       |
|                                                |             | 32-25LOG(THETA)                     |
| 12.0 GHz Gain (dBi) / Diameter (m)             |             | 41.8 / 1.2                          |
| 3 dB / 15 dB Half Beamwidth                    |             | 0.75 / 1.50                         |
| Transmit Antenna Type:                         | FCC32       | FCC Reference                       |
|                                                |             | 32-25LOG(THETA)                     |
| 14.0 GHz Gain (dBi) / Diameter (m)             |             | 43.3 / 1.2                          |
| 3 dB / 15 dB Half Beamwidth                    |             | 0.60 / 1.20                         |
| Operating Mode                                 |             | TRANSMIT AND RECEIVE                |
| Modulation                                     |             | DIGITAL                             |
| Emission / Receive Band (MHz)                  |             | 11M0G7D / 11700.00000 - 12200.00000 |
| Emission / Transmit Band (MHz)                 |             | 360KG7D / 14000.00000 - 14500.00000 |
| Max. Available RF Power (dBW)/4 kHz)           |             | -16.00                              |
| (dBW)/MHz)                                     |             | 8.00                                |
| Max. EIRP (dBW)/4 kHz)                         |             | 27.30                               |
| (dBW)/MHz)                                     |             | 51.30                               |
| (dBW)                                          |             | 45.90                               |
| Max permissible Interference Power             |             |                                     |
| 12.0 GHz, 20% (dBW/1 MHz)                      |             | -165.0                              |
| 12.0 GHz, 0.0100% (dBW/1 MHz)                  |             | -155.0                              |
| 14.0 GHz, 20% (dBW/4 kHz)                      |             | -151.0                              |
| 14.0 GHz, 0.0025% (dBW/4 kHz)                  |             | -128.0                              |
| Range of Satellite Arc (Geostationary)         |             |                                     |
| Degrees Longitude                              |             | 123.0 W / 123.0 W                   |
| Azimuth Range (Min/Max)                        |             | 244.7 / 244.7                       |
| Corresponding Elevation Angles                 |             | 34.2 / 34.2                         |
| Radio Climate                                  |             | B                                   |
| Rain Zone                                      |             | 1                                   |
| Max Great Circle Coordination Distance (Mi/Km) |             |                                     |
| 12.0 GHz                                       |             | 261.1 / 420.2                       |
| 14.0 GHz                                       |             | 81.1 / 130.5                        |
| Precipitation Scatter Contour Radius (Mi/Km)   |             |                                     |
| 12.0 GHz                                       |             | 337.3 / 542.9                       |
| 14.0 GHz                                       |             | 62.1 / 100.0                        |

Note: Horizon is less than 0.2 degrees at all azimuths

Table of Earth Station Coordination Values  
09/04/2002

Earth Station Name MIAMI FL  
 Owner ALCATEL USA  
 Latitude (DMS) (NAD83) 25 49 15.4 N  
 Longitude (DMS) (NAD83) 80 18 43.5 W  
 Ground Elevation (Ft/m) 5.02 / 1.53 AMSL  
 Antenna Centerline (Ft/m) 50.00 / 15.24 AGL  
 Antenna Model FCC Reference 32-25LOG(THETA)  
 Objectives: Receive -165.0 (dBW /1 MHz)  
 Transmit -151.0 (dBW /4 kHz) TX Power -16.0 (dBW/4 kHz)

| Azimuth<br>(Deg) | Horizon<br>Elevation<br>Angle<br>(Deg) | Antenna<br>Disc.<br>Angle<br>(Deg) | 12.0 GHz                 |                                  | 14.0 GHz                 |                                  |
|------------------|----------------------------------------|------------------------------------|--------------------------|----------------------------------|--------------------------|----------------------------------|
|                  |                                        |                                    | Antenna<br>Gain<br>(dBi) | Coordination<br>Distance<br>(Km) | Antenna<br>Gain<br>(dBi) | Coordination<br>Distance<br>(Km) |
| 0                | 0.00                                   | 110.67                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 5                | 0.00                                   | 114.63                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 10               | 0.00                                   | 118.52                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 15               | 0.00                                   | 122.31                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 20               | 0.00                                   | 125.97                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 25               | 0.00                                   | 129.48                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 30               | 0.00                                   | 132.80                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 35               | 0.00                                   | 135.88                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 40               | 0.00                                   | 138.67                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 45               | 0.00                                   | 141.09                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 50               | 0.00                                   | 143.08                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 55               | 0.00                                   | 144.56                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 60               | 0.00                                   | 145.47                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 65               | 0.00                                   | 145.75                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 70               | 0.00                                   | 145.40                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 75               | 0.00                                   | 144.43                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 80               | 0.00                                   | 142.88                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 85               | 0.00                                   | 140.84                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 90               | 0.00                                   | 138.37                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 95               | 0.00                                   | 135.55                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 100              | 0.00                                   | 132.44                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 105              | 0.00                                   | 129.10                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 110              | 0.00                                   | 125.57                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 115              | 0.00                                   | 121.89                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 120              | 0.00                                   | 118.09                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 125              | 0.00                                   | 114.19                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 130              | 0.00                                   | 110.22                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 135              | 0.00                                   | 106.20                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 140              | 0.00                                   | 102.13                             | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 145              | 0.00                                   | 98.02                              | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 150              | 0.00                                   | 93.90                              | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 155              | 0.00                                   | 89.77                              | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 160              | 0.00                                   | 85.64                              | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 165              | 0.00                                   | 81.52                              | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 170              | 0.00                                   | 77.42                              | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 175              | 0.00                                   | 73.35                              | -10.00                   | 381.6                            | -10.00                   | 118.7                            |
| 180              | 0.00                                   | 69.33                              | -10.00                   | 381.6                            | -10.00                   | 118.7                            |

Table of Earth Station Coordination Values  
09/04/2002

Earth Station Name        MIAMI FL  
Owner                        ALCATEL USA  
Latitude (DMS) (NAD83) 25 49 15.4 N  
Longitude (DMS) (NAD83) 80 18 43.5 W  
Ground Elevation (Ft/m)        5.02 /        1.53 AMSL  
Antenna Centerline (Ft/m)       50.00 /       15.24 AGL  
Antenna Model                FCC Reference 32-25LOG(THETA)  
Objectives: Receive        -165.0 (dBW /1 MHz)  
                 Transmit     -151.0 (dBW /4 kHz)    TX Power    -16.0 (dBW/4 kHz)

| Azimuth<br>(Deg) | Horizon<br>Elevation<br>Angle<br>(Deg) | Antenna<br>Disc.<br>Angle<br>(Deg) | 12.0 GHz<br>Antenna<br>Gain<br>(dBi) | 12.0 GHz<br>Coordination<br>Distance<br>(Km) | 14.0 GHz<br>Antenna<br>Gain<br>(dBi) | 14.0 GHz<br>Coordination<br>Distance<br>(Km) |
|------------------|----------------------------------------|------------------------------------|--------------------------------------|----------------------------------------------|--------------------------------------|----------------------------------------------|
| 185              | 0.00                                   | 65.37                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 190              | 0.00                                   | 61.48                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 195              | 0.00                                   | 57.70                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 200              | 0.00                                   | 54.03                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 205              | 0.00                                   | 50.52                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 210              | 0.00                                   | 47.20                              | -9.85                                | 383.1                                        | -9.85                                | 119.2                                        |
| 215              | 0.00                                   | 44.12                              | -9.12                                | 390.7                                        | -9.12                                | 121.5                                        |
| 220              | 0.00                                   | 41.33                              | -8.41                                | 398.1                                        | -8.41                                | 123.8                                        |
| 225              | 0.00                                   | 38.91                              | -7.75                                | 405.1                                        | -7.75                                | 125.9                                        |
| 230              | 0.00                                   | 36.92                              | -7.18                                | 411.2                                        | -7.18                                | 127.7                                        |
| 235              | 0.00                                   | 35.44                              | -6.74                                | 416.1                                        | -6.74                                | 129.2                                        |
| 240              | 0.00                                   | 34.53                              | -6.46                                | 419.2                                        | -6.46                                | 130.2                                        |
| 245              | 0.00                                   | 34.25                              | -6.37                                | 420.2                                        | -6.37                                | 130.5                                        |
| 250              | 0.00                                   | 34.60                              | -6.48                                | 418.9                                        | -6.48                                | 130.1                                        |
| 255              | 0.00                                   | 35.57                              | -6.78                                | 415.6                                        | -6.78                                | 129.1                                        |
| 260              | 0.00                                   | 37.12                              | -7.24                                | 410.6                                        | -7.24                                | 127.6                                        |
| 265              | 0.00                                   | 39.16                              | -7.82                                | 404.3                                        | -7.82                                | 125.7                                        |
| 270              | 0.00                                   | 41.63                              | -8.48                                | 397.3                                        | -8.48                                | 123.5                                        |
| 275              | 0.00                                   | 44.45                              | -9.20                                | 389.8                                        | -9.20                                | 121.2                                        |
| 280              | 0.00                                   | 47.56                              | -9.93                                | 382.3                                        | -9.93                                | 118.9                                        |
| 285              | 0.00                                   | 50.90                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 290              | 0.00                                   | 54.43                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 295              | 0.00                                   | 58.11                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 300              | 0.00                                   | 61.91                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 305              | 0.00                                   | 65.81                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 310              | 0.00                                   | 69.78                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 315              | 0.00                                   | 73.80                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 320              | 0.00                                   | 77.87                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 325              | 0.00                                   | 81.98                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 330              | 0.00                                   | 86.10                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 335              | 0.00                                   | 90.23                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 340              | 0.00                                   | 94.36                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 345              | 0.00                                   | 98.48                              | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 350              | 0.00                                   | 102.58                             | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |
| 355              | 0.00                                   | 106.65                             | -10.00                               | 381.6                                        | -10.00                               | 118.7                                        |

Earth Station Azimuth and Elevation Table  
09/04/2002

Earth Station Name      MIAMI FL  
 Owner                    ALCATEL USA  
 Latitude (DMS) (NAD83) 25 49 15.4 N  
 Longitude (DMS) (NAD83) 80 18 43.5 W  
 Ground Elevation (Ft/m)      5.02 /      1.53 AMSL  
 Antenna Centerline (Ft/m)      50.00 /      15.24 AGL  
 Satellite Arc Range      123.0 W  
                                  123.0 W

| Satellite<br>Longitude | Azimuth<br>(Degrees) | Elevation<br>(Degrees) | Satellite<br>Name |
|------------------------|----------------------|------------------------|-------------------|
| 123.0                  | 244.7                | 34.2                   | Galaxy 10R        |

## Exhibit C – Plano, TX Site Data

### SATELLITE EARTH STATION

09/04/2002

|                                                |                                                  |                                   |
|------------------------------------------------|--------------------------------------------------|-----------------------------------|
| Company                                        | ALCATEL USA                                      |                                   |
| Earth Station Name, State                      |                                                  | PLANO, TX                         |
| Latitude (DMS) (NAD83)                         |                                                  | 33 0 32.5 N                       |
| Longitude (DMS) (NAD83)                        |                                                  | 96 45 26.9 W                      |
| Ground Elevation AMSL (Ft/m)                   |                                                  | 700.03 / 213.36                   |
| Antenna Centerline AGL (Ft/m)                  |                                                  | 75.00 / 22.86                     |
| Receive Antenna Type:                          | FCC32                                            | FCC Reference                     |
|                                                |                                                  | 32-25LOG(THETA)                   |
| 12.0 GHz Gain (dBi) / Diameter (m)             |                                                  | 41.8 / 1.2                        |
| 3 dB / 15 dB Half Beamwidth                    |                                                  | 0.75 / 1.50                       |
| Transmit Antenna Type:                         | FCC32                                            | FCC Reference                     |
|                                                |                                                  | 32-25LOG(THETA)                   |
| 14.0 GHz Gain (dBi) / Diameter (m)             |                                                  | 43.3 / 1.2                        |
| 3 dB / 15 dB Half Beamwidth                    |                                                  | 0.60 / 1.20                       |
| Operating Mode                                 |                                                  | TRANSMIT AND RECEIVE              |
| Modulation                                     |                                                  | DIGITAL                           |
| Emission / Receive Band (MHz)                  |                                                  | 11M0G7D / 11700.0000 - 12200.0000 |
| Emission / Transmit Band (MHz)                 |                                                  | 360KG7D / 14000.0000 - 14500.0000 |
| Max. Available RF Power (dBW)/4 kHz)           |                                                  | -16.90                            |
| (dBW)/MHz)                                     |                                                  | 7.10                              |
| Max. EIRP                                      | (dBW)/4 kHz)                                     | 26.40                             |
|                                                | (dBW)/MHz)                                       | 50.40                             |
|                                                | (dBW)                                            | 45.90                             |
| Max permissible Interference Power             |                                                  |                                   |
| 12.0 GHz, 20% (dBW/1 MHz)                      |                                                  | -165.0                            |
| 12.0 GHz, 0.0100% (dBW/1 MHz)                  |                                                  | -155.0                            |
| 14.0 GHz, 20% (dBW/4 kHz)                      |                                                  | -151.0                            |
| 14.0 GHz, 0.0025% (dBW/4 kHz)                  |                                                  | -128.0                            |
| Range of Satellite Arc (Geostationary)         |                                                  |                                   |
| Degrees Longitude                              |                                                  | 123.0 W / 123.0 W                 |
| Azimuth Range (Min/Max)                        |                                                  | 222.1 / 222.1                     |
| Corresponding Elevation Angles                 |                                                  | 42.4 / 42.4                       |
| Radio Climate                                  |                                                  | A                                 |
| Rain Zone                                      |                                                  | 2                                 |
| Max Great Circle Coordination Distance (Mi/Km) |                                                  |                                   |
| 12.0 GHz                                       |                                                  | 173.0 / 278.4                     |
| 14.0 GHz                                       |                                                  | 69.5 / 111.9                      |
| Precipitation Scatter Contour Radius (Mi/Km)   |                                                  |                                   |
| 12.0 GHz                                       |                                                  | 62.1 / 100.0                      |
| 14.0 GHz                                       |                                                  | 62.1 / 100.0                      |
| Note:                                          | Horizon is less than 0.2 degrees at all azimuths |                                   |

Table of Earth Station Coordination Values  
09/04/2002

Earth Station Name      PLANO TX  
 Owner                    ALCATEL USA  
 Latitude (DMS) (NAD83) 33 0 32.5 N  
 Longitude (DMS) (NAD83) 96 45 26.9 W  
 Ground Elevation (Ft/m)      700.03 /      213.36 AMSL  
 Antenna Centerline (Ft/m)      75.00 /      22.86 AGL  
 Antenna Model                    FCC Reference 32-25LOG(THETA)  
 Objectives: Receive      -165.0 (dBW /1 MHz)  
                  Transmit      -151.0 (dBW /4 kHz)    TX Power      -16.9 (dBW/4 kHz)

| Azimuth<br>(Deg) | Horizon<br>Elevation<br>Angle<br>(Deg) | Antenna<br>Disc.<br>Angle<br>(Deg) | 12.0 GHz                 |                                  | 14.0 GHz                 |                                  |
|------------------|----------------------------------------|------------------------------------|--------------------------|----------------------------------|--------------------------|----------------------------------|
|                  |                                        |                                    | Antenna<br>Gain<br>(dBi) | Coordination<br>Distance<br>(Km) | Antenna<br>Gain<br>(dBi) | Coordination<br>Distance<br>(Km) |
| 0                | 0.00                                   | 123.22                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 5                | 0.00                                   | 126.09                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 10               | 0.00                                   | 128.73                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 15               | 0.00                                   | 131.11                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 20               | 0.00                                   | 133.19                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 25               | 0.00                                   | 134.92                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 30               | 0.00                                   | 136.25                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 35               | 0.00                                   | 137.15                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 40               | 0.00                                   | 137.59                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 45               | 0.00                                   | 137.56                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 50               | 0.00                                   | 137.05                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 55               | 0.00                                   | 136.09                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 60               | 0.00                                   | 134.69                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 65               | 0.00                                   | 132.91                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 70               | 0.00                                   | 130.79                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 75               | 0.00                                   | 128.37                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 80               | 0.00                                   | 125.69                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 85               | 0.00                                   | 122.80                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 90               | 0.00                                   | 119.72                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 95               | 0.00                                   | 116.50                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 100              | 0.00                                   | 113.15                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 105              | 0.00                                   | 109.70                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 110              | 0.00                                   | 106.17                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 115              | 0.00                                   | 102.58                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 120              | 0.00                                   | 98.94                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 125              | 0.00                                   | 95.27                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 130              | 0.00                                   | 91.58                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 135              | 0.00                                   | 87.89                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 140              | 0.00                                   | 84.20                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 145              | 0.00                                   | 80.53                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 150              | 0.00                                   | 76.90                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 155              | 0.00                                   | 73.32                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 160              | 0.00                                   | 69.80                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 165              | 0.00                                   | 66.36                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 170              | 0.00                                   | 63.03                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 175              | 0.00                                   | 59.83                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 180              | 0.00                                   | 56.78                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |

Table of Earth Station Coordination Values  
09/04/2002

Earth Station Name      PLANO TX  
Owner                      ALCATEL USA  
Latitude (DMS) (NAD83) 33 0 32.5 N  
Longitude (DMS) (NAD83) 96 45 26.9 W  
Ground Elevation (Ft/m)      700.03 /      213.36 AMSL  
Antenna Centerline (Ft/m)      75.00 /      22.86 AGL  
Antenna Model                      FCC Reference 32-25LOG(THETA)  
Objectives: Receive      -165.0 (dBW /1 MHz)  
                         Transmit      -151.0 (dBW /4 kHz)      TX Power      -16.9 (dBW/4 kHz)

| Azimuth<br>(Deg) | Horizon<br>Elevation<br>Angle<br>(Deg) | Antenna<br>Disc.<br>Angle<br>(Deg) | 12.0 GHz                 |                                  | 14.0 GHz                 |                                  |
|------------------|----------------------------------------|------------------------------------|--------------------------|----------------------------------|--------------------------|----------------------------------|
|                  |                                        |                                    | Antenna<br>Gain<br>(dBi) | Coordination<br>Distance<br>(Km) | Antenna<br>Gain<br>(dBi) | Coordination<br>Distance<br>(Km) |
| 185              | 0.00                                   | 53.91                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 190              | 0.00                                   | 51.27                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 195              | 0.00                                   | 48.89                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 200              | 0.00                                   | 46.81                              | -9.76                    | 272.6                            | -9.76                    | 109.2                            |
| 205              | 0.00                                   | 45.08                              | -9.35                    | 274.8                            | -9.35                    | 110.2                            |
| 210              | 0.00                                   | 43.75                              | -9.02                    | 276.6                            | -9.02                    | 111.0                            |
| 215              | 0.00                                   | 42.85                              | -8.80                    | 277.8                            | -8.80                    | 111.6                            |
| 220              | 0.00                                   | 42.41                              | -8.69                    | 278.4                            | -8.69                    | 111.8                            |
| 225              | 0.00                                   | 42.44                              | -8.69                    | 278.4                            | -8.69                    | 111.8                            |
| 230              | 0.00                                   | 42.95                              | -8.82                    | 277.7                            | -8.82                    | 111.5                            |
| 235              | 0.00                                   | 43.91                              | -9.07                    | 276.4                            | -9.07                    | 110.9                            |
| 240              | 0.00                                   | 45.31                              | -9.40                    | 274.5                            | -9.40                    | 110.1                            |
| 245              | 0.00                                   | 47.09                              | -9.82                    | 272.3                            | -9.82                    | 109.1                            |
| 250              | 0.00                                   | 49.21                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 255              | 0.00                                   | 51.63                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 260              | 0.00                                   | 54.31                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 265              | 0.00                                   | 57.21                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 270              | 0.00                                   | 60.28                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 275              | 0.00                                   | 63.50                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 280              | 0.00                                   | 66.85                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 285              | 0.00                                   | 70.30                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 290              | 0.00                                   | 73.83                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 295              | 0.00                                   | 77.42                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 300              | 0.00                                   | 81.06                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 305              | 0.00                                   | 84.73                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 310              | 0.00                                   | 88.42                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 315              | 0.00                                   | 92.11                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 320              | 0.00                                   | 95.80                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 325              | 0.00                                   | 99.47                              | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 330              | 0.00                                   | 103.10                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 335              | 0.00                                   | 106.68                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 340              | 0.00                                   | 110.20                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 345              | 0.00                                   | 113.64                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 350              | 0.00                                   | 116.97                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |
| 355              | 0.00                                   | 120.17                             | -10.00                   | 271.4                            | -10.00                   | 108.6                            |

Earth Station Azimuth and Elevation Table  
09/04/2002

Earth Station Name      PLANO TX  
 Owner                    ALCATEL USA  
 Latitude (DMS) (NAD83) 33 0 32.5 N  
 Longitude (DMS) (NAD83) 96 45 26.9 W  
 Ground Elevation (Ft/m)      700.03 /      213.36 AMSL  
 Antenna Centerline (Ft/m)      75.00 /      22.86 AGL  
 Satellite Arc Range            123.0 W  
                                  123.0 W

| Satellite<br>Longitude | Azimuth<br>(Degrees) | Elevation<br>(Degrees) | Satellite<br>Name |
|------------------------|----------------------|------------------------|-------------------|
| 123.0                  | 222.1                | 42.4                   | Galaxy 10R        |

## Exhibit D – Radiation Hazard Study

### Analysis of Non-Ionizing Radiation for a 1.2 Meter Earth Station System

This report analyzes the non-ionizing radiation levels for a 1.2 meter earth station system. The analysis and calculations performed in this report are in compliance with the methods described in the FCC Office of Engineering and Technology Bulletin, No. 65 first published in 1985 and revised in 1997 in Edition 97-01. The radiation safety limits used in the analysis are in conformance with the FCC R&O 96-326. Bulletin No. 65 and the FCC R&O specifies that there are two separate tiers of exposure limits that are dependant on the situation in which the exposure takes place and/or the status of the individuals who are subject to the exposure. The Maximum Permissible Exposure (MPE) limits for persons in a General Population/Uncontrolled environment are shown in Table 1. The General Population/Uncontrolled MPE is a function of transmit frequency and is for an exposure period of thirty minutes or less. The MPE limits for persons in an Occupational/Controlled environment are shown in Table 2. The Occupational MPE is a function of transmit frequency and is for an exposure period of six minutes or less. The purpose of the analysis described in this report is to determine the power flux density levels of the earth station in the far-field, near-field, transition region, between the subreflector or feed and main reflector surface, at the main reflector surface, and between the antenna edge and the ground and to compare these levels to the specified MPEs.

Table 1. Limits for General Population/Uncontrolled Exposure(MPE)

| Frequency Range (MHz) | Power Density (mWatts/cm**2) |
|-----------------------|------------------------------|
| 30-300                | 0.2                          |
| 300-1500              | Frequency(MHz)*(0.8/1200)    |
| 1500-100,000          | 1.0                          |

Table 2. Limits for Occupational/Controlled Exposure(MPE)

| Frequency Range (MHz) | Power Density (mWatts/cm**2) |
|-----------------------|------------------------------|
| 30-300                | 1.0                          |
| 300-1500              | Frequency(MHz)*(4.0/1200)    |
| 1500-100,000          | 5.0                          |

Table 3 contains the parameters that are used to calculate the various power densities for the earth stations.

Table 3. Formulas and Parameters Used for Determining Power Flux Densities

| Parameter            | Abbreviation | Value                       | Units     |
|----------------------|--------------|-----------------------------|-----------|
| Antenna Diameter     | D            | 1.2                         | meters    |
| Antenna Surface Area | Sa           | $\pi * D^2/4$               | meters**2 |
| Feed Flange Diameter | Df           | 7.6                         | cm        |
| Area of Feed Flange  | Fa           | $\pi * Df^2/4$              | cm**2     |
| Frequency            | Frequency    | 14250                       | MHz       |
| Wavelength           | lambda       | $300/\text{frequency(MHz)}$ | meters    |
| Transmit Power       | P            | 1.8                         | Watts     |
| Antenna Gain         | Ges          | 43.3                        | dBi       |
| Pi                   | $\pi$        | 3.1415927                   | n/a       |
| Antenna Efficiency   | n            | 0.67                        | n/a       |

#### 1. Far Field Distance Calculation

The distance to the beginning of the far field can be determined from the following equation:(1)

$$\begin{aligned} \text{Distance to the Far Field Region, (Rf)} &= 0.60 * D^2 / \lambda \\ &= 41.0 \text{ meters} \end{aligned} \quad (1)$$

The maximum main beam power density in the Far Field can be determined from the following equation:(2)

$$\begin{aligned} \text{On-Axis Power Density in the Far Field, (Wf)} &= \text{Ges} * P / 4 * \pi * Rf^2 \\ &= 1.818 \text{ Watts/meters}^2 \\ &= 0.182 \text{ mWatts/cm}^2 \end{aligned} \quad (2)$$

#### 2. Near Field Calculation

Power flux density is considered to be at a maximum value throughout the entire length of the defined Near Field region. The region is contained within a cylindrical volume having the same diameter as the antenna. Past the boundary of the Near Field region the power density from the antenna decreases linearly with respect to increasing distance.

The distance to the end of the Near Field can be determined from the following equation:(3)

$$\begin{aligned} \text{Extent of the Near Field, (Rn)} &= D^2 / (4 * \lambda) \\ &= 17.1 \text{ meters} \end{aligned} \quad (3)$$

The maximum power density in the Near Field can be determined from the following equation:(4)

$$\begin{aligned} \text{Near Field Power Density, (Wn)} &= 16.0 * n * P / \pi * D^2 \\ &= 4.245 \text{ Watts/meters}^2 \\ &= 0.424 \text{ mWatts/cm}^2 \end{aligned} \quad (4)$$

### 3. Transition Region Calculations

The Transition region is located between the Near and Far Field regions. The power density begins to decrease linearly with increasing distance in the Transition region. While the power density decreases inversely with distance in the Transition region, the power density decreases inversely with the square of the distance in the Far Field region. The maximum power density in the Transition region will not exceed that calculated for the Near Field region. The power density calculated in Section 1 is the highest power density the antenna can produce in any of the regions away from the antenna. The power density at a distance  $R_t$  can be determined from the following equation:(5)

$$\begin{aligned}\text{Transition region Power Density, (Tt)} &= W_n * R_n / R_t \\ &= 0.424 \text{ mWatts/cm}^2\end{aligned}\tag{5}$$

### 4. Region between Feed Assembly and Antenna Reflector

Transmissions from the feed assembly are directed toward the antenna reflector surface, and are confined within a conical shape defined by the type of feed assembly. The most common feed assemblies are waveguide flanges, horns or subreflectors. The energy between the feed assembly and reflector surface can be calculated by determining the power density at the feed assembly surface. This can be determined from the following equation:(6)

$$\begin{aligned}\text{Power Density at Feed Flange, (Wf)} &= 4 * P / F_a \\ &= 158.714 \text{ mWatts/cm}^2\end{aligned}\tag{6}$$

### 5. Main Reflector Region

The power density in the main reflector is determined in the same manner as the power density at the feed assembly. The area is now the area of the reflector aperture and can be determined from the following equation:(7)

$$\begin{aligned}\text{Power Density at the Reflector Surface, (Ws)} &= 4 * P / S_a \\ &= 6.366 \text{ Watts/meters}^2 \\ &= 0.637 \text{ mWatts/cm}^2\end{aligned}\tag{7}$$

### 6. Region between Reflector and Ground

Assuming uniform illumination of the reflector surface, the power density between the antenna and ground can be determined from the following equation:(8)

$$\begin{aligned}\text{Power Density between Reflector and Ground, (Wg)} &= P / S_a \\ &= 1.592 \text{ Watts/meters}^2 \\ &= 0.159 \text{ mWatts/cm}^2\end{aligned}\tag{8}$$

Table 4. Summary of Expected Radiation levels for Uncontrolled Environment

| <u>Region</u>                                     | <u>Calculated Maximum Radiation<br/>Power Density Level<br/>(mWatts/cm**2)</u> | <u>Hazard Assessment</u> |
|---------------------------------------------------|--------------------------------------------------------------------------------|--------------------------|
| 1. Far Field (Rf) = 41.0 meters                   | 0.182                                                                          | Satisfies FCC MPE        |
| 2. Near Field (Rn) = 17.1 meters                  | 0.424                                                                          | Satisfies FCC MPE        |
| 3. Transition Region<br>Rn < Rt < Rf, (Rt)        | 0.424                                                                          | Satisfies FCC MPE        |
| 4. Between Feed Assembly<br>and Antenna Reflector | 158.714                                                                        | Potential Hazard         |
| 5. Main Reflector                                 | 0.637                                                                          | Satisfies FCC MPE        |
| 6. Between Reflector<br>and Ground                | 0.159                                                                          | Satisfies FCC MPE        |

Table 5. Summary of Expected Radiation levels for Controlled Environment

| <u>Region</u>                                     | <u>Calculated Maximum Radiation<br/>Power Density Level<br/>(mWatts/cm**2)</u> | <u>Hazard Assessment</u> |
|---------------------------------------------------|--------------------------------------------------------------------------------|--------------------------|
| 1. Far Field (Rf) = 41.0 meters                   | 0.182                                                                          | Satisfies FCC MPE        |
| 2. Near Field (Rn) = 17.1 meters                  | 0.424                                                                          | Satisfies FCC MPE        |
| 3. Transition Region<br>Rn < Rt < Rf, (Rt)        | 0.424                                                                          | Satisfies FCC MPE        |
| 4. Between Feed Assembly<br>and Antenna Reflector | 158.714                                                                        | Potential Hazard         |
| 5. Main Reflector                                 | 0.637                                                                          | Satisfies FCC MPE        |
| 6. Between Reflector<br>and Ground                | 0.159                                                                          | Satisfies FCC MPE        |

It is the applicant's responsibility to ensure that the public and operational personnel are not exposed to harmful levels of radiation.

7. Conclusions

Based on the above analysis it is concluded that harmful levels of radiation will not exist in regions normally occupied by the public or the earth station's operating personnel. The transmitter will be turned off during antenna maintenance so that the FCC MPE of  $5.0 \text{ mW/cm}^2$  will be complied with for those regions with close proximity to the reflector that exceed acceptable levels.