

UNCLASSIFIED		A20030300062
SECURITY SUMMARY & SPECIAL HANDLING REQUIREMENTS		
The title of this application is: L3 Communications Tactical Common Data Link (TCDL) The overall classification of this application is: UNCLASSIFIED		
The following Special Handling summary lists the applicable markings for the printed page(s). It is your responsibility to place all Special Handling markings on the cover page of the application. If an Entire Application was printed, the following Special Handling summary lists the applicable markings for the Entire Application. If an Individual Page (TX, RX, ANT, etc.) was printed, the following Special Handling summary lists the applicable markings for the printed page. It is your responsibility to make certain that any Special Handling markings that are unique to the Individual Page are also reflected on the cover of the Entire Application. If the "!" code is shown below, the "SEE REMARKS" refers to the REMARKS block on the applicable page. Refer to your Security Manual for further guidance.		
No Application Level Special Handling No Page Level Special Handling		
UNCLASSIFIED		A20030300062

UNCLASSIFIED			A20030300062
SECURITY SUMMARY & SPECIAL HANDLING REQUIREMENTS			
The title of this application is: L3 Communications Tactical Common Data Link (TCDL)			
The overall classification of this application is: UNCLASSIFIED			
All Application Level Special Handling markings (if any) will appear at the top of the Special Handling list for each individual page type. Field Level markings will follow. It is your responsibility to mark the individual pages of this application in accordance with the procedures in your Security Manual. The following summaries are provided for that purpose.			
If the "I" code is shown below, the "SEE REMARKS" refers to the REMARKS block on the applicable page.			
Page Type:	Page #:	Classification:	Special Handling Requirement:
DoD Page	1	UNCLASSIFIED	
Transmitter Page 1	2	UNCLASSIFIED	
Transmitter Page 2	3	UNCLASSIFIED	
Receiver Page 1	4	UNCLASSIFIED	
Receiver Page 2	5	UNCLASSIFIED	
Antenna Page 1	6	UNCLASSIFIED	
Antenna Page 2	7	UNCLASSIFIED	
Antenna Page 3	8	UNCLASSIFIED	
NTIA Page	9	UNCLASSIFIED	
MCEB Guidance Page	10	UNCLASSIFIED	
MCEB Overflow	11	UNCLASSIFIED	
Note to Holders 1	12	UNCLASSIFIED	
NTIA Admin Page	13	UNCLASSIFIED	
Administrative Page		UNCLASSIFIED	
UNCLASSIFIED			A20030300062

APPLICATION FOR EQUIPMENT FREQUENCY ALLOCATION		CLASSIFICATION UNCLASSIFIED		DATE 02/18/1999		J/F 12/07834	
				Page 1 of 13 Pages			
DOD GENERAL INFORMATION							
TO AF Frequency Management Agency AFFMA/SCOE 2461 Eisenhower Ave., Suite 1203 Alexandria, VA 22331-1500				FROM AF Materiel Command (ASC 1999-16/17) AFMC CSO/SCSC 4225 Logistics Avenue, Suite 20 Wright Patterson AFB, OH 45433-5759			
1. APPLICATION TITLE (U) L3 Communications Tactical Common Data Link (TCDL)							
2. SYSTEM NOMENCLATURE (U) L3 Communications Tactical Common Data Link (TCDL)							
3. STAGE OF ALLOCATION (U) ☐ a. STAGE 1 CONCEPTUAL ☐ b. STAGE 2 EXPERIMENTAL ☒ c. STAGE 3 DEVELOPMENTAL ☐ d. STAGE 4 OPERATIONAL							
4. FREQUENCY REQUIREMENTS a. FREQUENCY(IES) (U) 15.15 GHz - 15.35 GHz 14.4 GHz - 14.83 GHz b. EMISSION DESIGNATORS (U) (See Remarks)							
5. TARGET STARTING DATE FOR SUBSEQUENT STAGES							
a. STAGE 2 (U) NA			b. STAGE 3 (U) NA			c. STAGE 4 (U) NAvail	
6. EXTENT OF USE (U) Intermittent use up to 24 hours/day							
7. GEOGRAPHICAL AREA FOR							
a. STAGE 2 (U) NA							
b. STAGE 3 (U) China Lake, Ca; Salt Lake City, UT (See Remarks)							
c. STAGE 4 (U) Worldwide (Specific Locations Not Yet Available)							
8. NUMBER OF UNITS							
a. STAGE 2 (U) NA			b. STAGE 3 (U) 5			c. STAGE 4 (U) 200	
9. NUMBER OF UNITS OPERATING SIMULTANEOUSLY IN THE SAME ENVIRONMENT (U) 4							
10. OTHER J/F 12 APPLICATION ID(S) TO BE (U) ☐ a. SUPERSEDED ☒ b. RELATED J/F 12/06534				11. IS THERE ANY OPERATIONAL REQUIREMENT AS DESCRIBED IN THE INSTRUCTIONS FOR PARAGRAPH 11? (U) ☒ a. YES ☐ b. NO ☐ c. NAVAIL			
12. NAMES AND TELEPHONE NUMBERS (U)							
a. PROGRAM MANAGER Mr Walt Hartman, AFRL/IFGD				(1) COMMERCIAL 927-255-4957		(2) DSN 785-4947	
b. PROJECT ENGINEER M4 Roger Swanson, AFRL/IFGD				(1) COMMERCIAL 937-255-4947		(2) DSN 785-4947	
13. REMARKS (U) Item 4b, Emission Designator: 800KG1D, 8M00G1D, 21M4G1D, 45M0G1D, 64M0G1D Item 7b, Geographical Area: Rancho Bernardo, CA; El Mirage, CA; Patuxent River NAS, MD; Edwards AFB, CA; Ft Huachuca, AZ; and Fallon NAS, NV. Item 11, Operational Requirement: Equipment interfaces with other existing DoD Common Data Link systems in the same frequency band.							
DOWNGRADING INSTRUCTIONS						J/F 12/07834	
						CLASSIFICATION UNCLASSIFIED	

CLASSIFICATION UNCLASSIFIED					PAGE 4				
RECEIVER EQUIPMENT CHARACTERISTICS									
1. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) None Assigned (Surface Receiver)					2. MANUFACTURER'S NAME (U) L3 Communications				
3. RECEIVER INSTALLATION (U) Ground or Ship Terminal					4. RECEIVER TYPE (U) Dual Conversion Superheterodyne				
5. TUNING RANGE (U) 14.4 GHz - 14.83 GHz					6. METHOD OF TUNING (U) Crystal Controlled Synthesizer				
7. RF CHANNELING CAPABILITY (U) 14.4 GHz, 5 MHz Steps					8. EMISSION DESIGNATORS (U) 800KG1D (See Remarks)				
9. FREQUENCY TOLERANCE (U) 10 ppm					11. RF SELECTIVITY X CALCULATED MEASURED				
10. IF SELECTIVITY		1st (U)	2nd (U)	3rd (U)	a. -3 dB (U) 430 MHz				
a. -3 dB		200 MHz	90 MHz	NA	b. -20 dB (U) 500 MHz				
b. -20 dB		450 MHz	300 MHz	NA	c. -60 dB (U) 750 MHz				
c. -60 dB		1500 MHz	850 MHz	NA	d. Preselection Type (U) Waveguide				
12. IF FREQUENCY a. 1st (U) 3570 MHz b. 2nd (U) 680 MHz c. 3rd (U) NA					13. MAXIMUM POST DETECTION FREQUENCY (U) 90 MHz				
15. OSCILLATOR TUNED 1st (U) 2nd (U) 3rd (U)					14. MINIMUM POST DETECTION FREQUENCY (U) NA				
a. ABOVE TUNED FREQUENCY					16. MAXIMUM BIT RATE (U) 45 Mbps				
b. BELOW TUNED FREQUENCY		X	X		17. SENSITIVITY a. SENSITIVITY (U) - 109.4 dBm				
c. EITHER ABOVE OR BELOW THE FREQUENCY					b. CRITERIA (U) 10 x -8 BER				
18. DE-EMPHASIS (U) a. YES X b. NO					c. NOISE FIG (U) 3.7 dB				
19. IMAGE REJECTION (U) 85 dB					d. NOISE TEMP (U) NA				
20. SPURIOUS REJECTION (U) 85 dB					21. REMARKS (U) Item 8, Emission Designators: 8M00G1D 21M4G1D 45M0G1D 64M0G1D Item 17a, Sensitivity -99.4 dBm -92.1 dBm -85.9 dBm -109.4 dBm				
CLASSIFICATION UNCLASSIFIED					J/F 12/07834				

CLASSIFICATION UNCLASSIFIED					PAGE 5				
RECEIVER EQUIPMENT CHARACTERISTICS									
1. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) None Assigned (Airborne Receiver)					2. MANUFACTURER'S NAME (U) L3 Communications				
3. RECEIVER INSTALLATION (U) Ground or Ship Terminal					4. RECEIVER TYPE (U) Dual Conversion Superheterodyne				
5. TUNING RANGE (U) 15.15 GHz - 15.35 GHz					6. METHOD OF TUNING (U) Crystal Controlled Synthesizer				
7. RF CHANNELING CAPABILITY (U) 15.15 GHz, 5 MHz Steps					8. EMISSION DESIGNATORS (U) 800KG1D (See Remarks)				
9. FREQUENCY TOLERANCE (U) 10 ppm					11. RF SELECTIVITY X CALCULATED MEASURED				
10. IF SELECTIVITY		1st (U)	2nd (U)	3rd (U)	a. -3 dB (U) 200 MHz				
a. -3 dB		200 MHz	90 MHz	NA	b. -20 dB (U) 410 MHz				
b. -20 dB		450 MHz	300 MHz	NA	c. -60 dB (U) 560 MHz				
c. -60 dB		1500 MHz	850 MHz	NA	d. Preselection Type (U) Waveguide				
12. IF FREQUENCY a. 1st (U) 3570 MHz b. 2nd (U) 680 MHz c. 3rd (U) NA					13. MAXIMUM POST DETECTION FREQUENCY (U) 90 MHz				
15. OSCILLATOR TUNED 1st (U) 2nd (U) 3rd (U)					14. MINIMUM POST DETECTION FREQUENCY (U) NA				
a. ABOVE TUNED FREQUENCY					16. MAXIMUM BIT RATE (U) 45 Mbps				
b. BELOW TUNED FREQUENCY		X	X		17. SENSITIVITY a. SENSITIVITY (U) - 109.2 dBm				
c. EITHER ABOVE OR BELOW THE FREQUENCY					b. CRITERIA (U) 10 x -8 BER				
18. DE-EMPHASIS (U) a. YES X b. NO					c. NOISE FIG (U) 3.9 dB				
19. IMAGE REJECTION (U) 85 dB					d. NOISE TEMP (U) NA				
20. SPURIOUS REJECTION (U) 85 dB					21. REMARKS (U) Item 8, Emission Designators: 8M00G1D 21M4G1D 45M0G1D 64M0G1D Item 17a, Sensitivity -99.2 dBm -91.9 dBm -85.7 dBm -109.2 dBm				
CLASSIFICATION UNCLASSIFIED					J/F 12/07834				

APPLICATION FOR SPECTRUM REVIEW	CLASSIFICATION UNCLASSIFIED	PAGE 9
NTIA GENERAL INFORMATION		
1. APPLICATION TITLE (U) L3 Communications Tactical Common Data Link (TCDL)		
2. SYSTEM NOMENCLATURE (U) L3 Communications Tactical Common Data Link (TCDL)		
3. STAGE OF ALLOCATION (U) ☐ a. STAGE 1 CONCEPTUAL ☐ b. STAGE 2 EXPERIMENTAL ☒ c. STAGE 3 DEVELOPMENTAL ☐ d. STAGE 4 OPERATIONAL		
4. FREQUENCY REQUIREMENTS a. FREQUENCY(IES) (U) 15.15 GHz - 15.35 GHz 14.4 GHz - 14.83 GHz b. EMISSION DESIGNATORS (U) (See Remarks)		
5. PURPOSE OF SYSTEM, OPERATIONAL AND SYSTEM CONCEPTS (U) Line of sight (LOS) transmission of intelligence, surveillance, and reconnaissance imagery data from an airborne platform to a ground control station. (See Remarks) (WARTIME USE) ☒ a. YES ☐ b. NO		
6. INFORMATION TRANSFER REQUIREMENTS (U) 0.2 & 2 Mbps, R=1/2 BPSK; 10.71 & 45 Mbps QPSK; 200 Kbps, R=1/2, DSSS @ 32 Megachips/sec		
7. ESTIMATED INITIAL COST OF THE SYSTEM (U) \$200,000/surface terminal; \$50,000/airborne terminal		
8. TARGET DATE FOR		
a. APPLICATION APPROVAL (U) ASAP	b. SYSTEM ACTIVATION (U) ASAP	c. SYSTEM TERMINATION (U) NAvail
9. SYSTEM RELATIONSHIP AND ESSENTIALITY (U) Essential for passing imagery and other reconnaissance data from an airborne platform to a ground control station. System interfaces with existing Army and Navy wideband RF data link systems.		
10. REPLACEMENT INFORMATION (U) None		
11. RELATED ANALYSIS AND/OR TEST DATA (U) None		
12. NUMBER OF MOBILE UNITS (U) 5		
13. GEOGRAPHICAL AREA FOR		
a. STAGE 2 (U) NA		
b. STAGE 3 (U) China Lake, CA; Salt Lake City, UT; (See remarks)		
c. STAGE 4 (U) Worldwide, (Specific locations not yet determined)		
14. LINE DIAGRAM (U) See Page(s) 10		15. SPACE SYSTEMS (U) See Page(s) NA
16. TYPE OF SERVICE(S) FOR STAGE 4 (U) Aeronautical Mobile		17. STATION CLASS(ES) FOR STAGE 4 (U) FA MA
18. REMARKS (U) Item 4b, Emission Designator: 800KG1D, 8M00G1D, 21M4G1D, 45M0G1D, 64M0G1D Item 13b, Geographical Area: Rancho Bernardo, CA; El Mirage, CA; Patuxent River NAS, MD; Edwards AFB, CA; Ft Huachuca, AZ; and Fallon NAS, NV.		
DOWNGRADING INSTRUCTIONS		J/F 12/07834
		CLASSIFICATION UNCLASSIFIED

UNCLASSIFIED

MILITARY COMMUNICATIONS ELECTRONICS BOARD (MCEB)
EQUIPMENT FREQUENCY ALLOCATION GUIDANCE

Military Department: Air Force AND NAVY
Equipment: L3 COMMUNICATIONS TACTICAL COMMON DATA LINK (TDCL)
Stage: 3, Developmental

Section 1: ENCLOSURE

Enclosure Number: 1
Description: J/F 12/7834
Dated: 18 February 1999

Section 2: OPERATING CHARACTERISTICS FOR WHICH SUPPORT IS CERTIFIED

Frequency (GHz): 14.4 - 14.83, 15.15 - 15.35
Emissions: 800KG1D, 8M00G1D, 21M4G1D, 45M0G1D, 64M0G1D
Power (Mean): 2 Watts
Type of Services: Aeronautical, Mobile
Operating Location: El Mirage, Rancho Bernado, Edwards AFB, and China Lake, CA; Hondo, TX; Patuxent River NAS, MD; Fallon NAS, NV; and Fort Huachuca, AZ

Section 3: MCEB GUIDANCE

1. The subject system is approved for developmental use at the locations listed above subject to the following guidance:
2. For the intended use in the Aeronautical Mobile service, the subject system is in conformance with the National Tables of Frequency Allocations, noting the mobile service has primary status only in the 14.7145-15.1365 MHz band. Outside of the US, the band 14.4-14.5 GHz can not be used for aeronautical mobile operations.
3. Based on the information provided, the equipment does not comply with the requirements of NTIA manual standard section 5.2 part 5.2.2.2. for unwanted emissions. In any instance of harmful interference caused by nonconformance with these provisions, the responsibility for eliminating the harmful interference normally shall rest with the agency operating in nonconformance.
4. The subject equipment complies with the transmitter spurious and harmonic attenuation level requirements of MIL-STD-461E.
5. Operation of the equipment must be coordinated in accordance with ACP 190
US SUPP-1(D), Guide to Frequency Planning.
6. NTIA/SPS coordination was accomplished per SPS-12712 with the following recommendations:
 - a. Air Force ensure that 800KG1D, 8M00G1D, 21M4G1D, 45M0G1D and 64M0G1D transmissions are brought into compliance with Section 5.2.2.2 of the

NTIA Manual.

b. Air Force take all practicable steps to utilize 14.7145-14.83 GHz where mobile service is primary and to protect the radio astronomy service in the band 14.47-14.5 GHz. Coordinating assignments in the 14.4-14.71445 and 15.15-15.35 GHz bands may be difficult.

c. Air Force ensure that personnel are protected from radiation levels that exceed generally accepted exposure criteria.

Steering Member

J-12 Working Group

MCEB Frequency Panel

Signature:....; Date: 02 MAY 2001

IRAC DOC.: 31842

SPS#: 12712

Downgrading Instructions: NA

Distribution: J-12 Holders

MCEB J-12 Number: J/F 12/7834/1

UNCLASSIFIED

UNCLASSIFIED

PAGE 12

MILITARY COMMUNICATIONS ELECTRONICS BOARD
WASHINGTON, DC 20301

UNCLASSIFIED
NH J/F 12/7834/1
(Agenda Item No. J-12)

5 MAR 2003

NOTE TO HOLDERS
OF
J/F 12/7834/1

L3 Communications Tactical Common Data Link (TCDL)

Holders of subject Air Force document, dated 2 MAY 2001, are requested by
the Navy to note the following changes:

Military Department: Add "NAVY".

Steering Member
ESG Working Group
MCEB Frequency Panel

cc: MCEB ESG Distribution List

UNCLASSIFIED

NH J/F 12/7834/1

UNCLASSIFIED

J/F 12/07834

ADMINISTRATIVE INFORMATION PAGE

1. SYSTEM IDENTIFIER:

(U)

C

2. EQUIPMENT FUNCTION:

(U)

CD

C

SQ

SV

IM

PP

3. EQUIPMENT NOMENCLATURE:

(U)

L3 COMM TACT COMM DA LK

(U)

(U)

TCDL

(U)

(U)

(U)

(U)

4. ECI CODE:

(U)

5. MCEB USE:

(U)

D

(C:CONCEP; E:EXPER; D:DEVELOP; O:OPER; N:NOTED)

6. MCEB LOCATIONS:

(U)

COUNTRY	STATE	CITY
USA	CA	EL MIRAGE
USA	CA	RANCHO BERNADO
USA	CA	EDWARDS AFB
USA	CA	CHINA LAKE
USA	TX	HONDO
USA	MD	PAX R. NAS
USA	NV	FALON NAS
USA	AZ	FT. HUACHUCA

7. HOST COUNTRY:

COUNTRY

DATE

MESSAGE DTG

(U)

(U)

(U)

(U)

(U)

(U)

(U)

(U)

(U)

8. NOTE-TO-HOLDER:

(U)

03-05-2003

(U)

(U)

(U)

(U)

(U)

(U)

(U)

(U)

(U)

9. JSC MEMO DATE:

(U)

05-02-2001

10. USING AGENCIES:

(U)

1:AF

2:N

3:

11. PROCURING AGENCY:

(U)

AF

12. APPLICATION STATUS:

(U)

1

(1:APPROV; 2:CANCEL; 3:SUPERSE; 4:NOTED; 5:WITHDR; 6:PEND)

Line Diagram for the
L3 Communications Tactical Common Data Link (TCDL)

