

## CenturyLink Response for NTIA, Section 8.3.28

### 8.3.28 Use of Fixed Devices That Re-Radiate Signals Received From the Global Positioning System

Except as otherwise authorized under Part 7.14, federal agencies and departments may, under the following conditions, operate fixed devices that re-radiate signals received from the Global Positioning System (GPS).

1. Individual authorization is for indoor use only, and is required for each device at a specific site.

**Response: Compliant**

2. Applications for frequency assignment should be applied for as an XT station class with a note indicating the device is to be used as an "Experimental RNSS Test Equipment for the purpose of testing GPS receivers" and describing how the device will be used.

**Response: Compliant.** *Device will be used to repeat the GPS signal to wireless carrier base station GPS receivers that are exclusively inside the building/room*

3. Approved applications for frequency assignment will be entered in the GMF.

**Response: Compliant,** *upon approval of application*

4. The maximum length of the assignment will be two years, with possible renewal.

**Response: Compliant**

5. The area of potential interference to GPS reception (e.g., military or contractor facility) has to be under the control of the user.

**Response: Compliant**

6. The maximum equivalent isotropically radiated power (EIRP) must be such that the calculated emissions are no greater than -140 dBm/24 MHz as received by an isotropic antenna at a distance of 100 feet (30 meters) from the building where the test is being conducted. The calculations showing compliance with this requirement must be provided with the application for frequency assignment and should be based on free space propagation with no allowance for additional attenuation (e.g., building attenuation.)

**Response: Compliant,** see calculations on next page.

### EIRP calculations, assuming free space propagation

|                                         |                                                              |                   |                             |                     |                                      |
|-----------------------------------------|--------------------------------------------------------------|-------------------|-----------------------------|---------------------|--------------------------------------|
|                                         | -140 or less at a range of 100 feet to meet NTIA regulations |                   |                             |                     |                                      |
| Receive Ant Gain                        | Ant Cable Insertion Loss                                     | Repeater Amp Gain | Repeater Ant Gain Best Case | Range in Feet       | Repeated Signal Power @ Range In dBm |
| 38                                      | -15                                                          | 30                | 3                           | 123                 | -141.89                              |
|                                         | GPS Carrier Frequency MHz                                    |                   | Total System Gain           | Range in Miles      | Total Signal Power @ Range in Watts  |
|                                         | 1575                                                         |                   | 56                          | 0.02                | 6.5E-18                              |
| Avg Receive Power L1 dBm North America  |                                                              |                   |                             | Range in Meters     | Radiated Power dBm                   |
|                                         | -130                                                         |                   |                             | 38.34               | -74                                  |
| Free Space loss with Isotropic Antennas |                                                              |                   |                             | Range in Kilometers | Transmitted Power (W)                |
|                                         | -67.89                                                       |                   |                             | 0.04                | 20.0E-12                             |
|                                         |                                                              |                   |                             |                     | Effective Radiated Power (W)         |
|                                         |                                                              |                   |                             |                     | 39.8E-12                             |
|                                         |                                                              |                   |                             |                     | Effective Radiated Power (dBW)       |
|                                         |                                                              |                   |                             |                     | -104                                 |

7. GPS users in the area of potential interference to GPS reception must be notified that GPS information may be impacted for periods of time.

**Response: Compliant**

8. The use is limited to activity for the purpose of testing RNSS equipment/systems.

**Response: Compliant**

9. A "Stop Buzzer" point of contact for the authorized device must be identified and available at all times during GPS re-radiation operation of the device under any condition.

**Response: Compliant** Contact name: Brodie McMahon  
Office Ph: 318-450-3897  
Cell Ph: 318-3510-3376  
Email: [Brodie.Mcmahon@centurylink.com](mailto:Brodie.Mcmahon@centurylink.com)  
Address: 100 CenturyLink DR  
Room # 1SE472  
Monroe, LA 71203