

## **ELTA North America Request for FCC Experimental License**

Form 442 File Number: 0532-EX-PL-2016

Form 442 Confirmation Number: EL286423

26 July 2016

### **Question 9: Statement of Environmental Impact**

ELTA North America (N.A.) will occupy a section of the building located at 11840 West Market Place, Fulton, MD. The building is a new, single-story structure, with multiple bays, and is constructed of concrete block with a web girder and steel pan roof. The surrounding area is a mixed use development of retail, office, educational, and residential buildings. The adjacent property consists of similar single-story buildings to the north and south of the site, a public school campus to the west, and an open field to the east. Further north is a residential neighborhood and the Johns Hopkins University (JHU) Applied Physics Laboratory (APL) campus. Further east is a small urban development with multistory buildings. The other specified location for this application are isolated and have wide open area surrounding including trees and foliage necessary for testing the radar. The antenna will be mounted on top of a 90 foot mast which will be located on ground. The radar equipment will be remotely controlled.

It is the policy of ELTA N.A. that company personnel, customers, or members of the public are not subjected to RF power density levels that exceed the Maximum Permissible Exposure (MPE) limits as given in Part 1.1310 of the FCC Rules. Experimental testing will only be conducted with appropriate controls in place, and no personnel will be on the roof during transmissions that will exceed the MPE levels. ELTA N.A. will have an RF Safety Plan which describes the procedures and controls necessary to comply with MPE levels during operations and maintenance. Measurements will also be used to confirm that MPE levels are not exceeded.

ELTA N.A. conducted a worst-case analysis of power density levels in the area surrounding the transmitting antenna based on the FCC's OET Bulletin Number 65<sup>1</sup>. The applicable radar parameters and results are shown in Tables 1 and 2, respectively. The MPE limit is exceeded for areas within 5.3 and 11.8 feet for controlled and uncontrolled exposure limits, respectively. With the building height of approximately 19 feet, personnel on the ground will be beyond the distance where the power density exceeds the MPE limit. For personnel on the roof, the roof has controlled access; therefore, appropriate controls will be implemented for areas within 5.3 ft during test periods. Measurements will be made to confirm the emission levels.

<sup>1</sup> Cleveland, Robert F., et al., *Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields*, Edition 97-01, OET BULLETIN 65, Washington D.C.: Federal Communications Commission, Office of Engineering and Technology, August 1997.

**Table 1 – Power Density Analysis**

| <b>Parameter</b>                 | <b>Value</b> |
|----------------------------------|--------------|
| Operational frequency, MHz       | 1200         |
| Transmitter output power (peak), | 1 W          |
| Antenna gain (mainbeam), dBi     | 12           |
| Ground reflection factor         | 2.56         |

**Table 2 – Power Density Analysis  
Results**

| <b>Parameter</b>                                 | <b>Controlled</b> | <b>Uncontrolled</b> |
|--------------------------------------------------|-------------------|---------------------|
| Maximum Permissible Exposure, mW/cm <sup>2</sup> | 10                | 6.6                 |
| Minimum required distance, meters                | 0.5               | 1                   |
| Minimum required distance, feet                  | 2                 | 3                   |