

ELTA North America Request for FCC Experimental License

Form 442 File Number: 0796-EX-CN-2018
Form 442 Confirmation Number: EL290730

4 Oct 2018

Question 9: Statement of Environmental Impact

The specified locations for this application are isolated and have wide open area surrounding including trees and foliage necessary for testing the mobile LTE network.

There are 4, omnidirectional manpack antennas located on the unit which is mounted to a backpack design to be worn during operations. The unit will not be more than 2 meters off of the ground

It is the policy of ELTA N.A. that company personnel, customers, or members of the public are not subjected to RF power density levels that exceed the Maximum Permissible Exposure (MPE) limits as given in Part 1.1310 of the FCC Rules. Experimental testing will only be conducted with appropriate controls in place, and no personnel will be on the roof during transmissions that will exceed the MPE levels. ELTA N.A. will have an RF Safety Plan which describes the procedures and controls necessary to comply with MPE levels during operations and maintenance. Measurements will also be used to confirm that MPE levels are not exceeded.

¹ Cleveland, Robert F., et al., *Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields*, Edition 97-01, OET BULLETIN 65, Washington D.C.: Federal Communications Commission, Office of Engineering and Technology, August 1997.

Table 1 – Power Density Analysis

Parameter	Value
Operational frequency, MHz	2570-2620 MHz
Transmitter output power (peak),	1 W
Antenna gain (mainbeam), dBi	6
Radiation Pattern	Azimuth- 360° Elevation- 28°

