

**United States of America
FEDERAL COMMUNICATIONS COMMISSION
EXPERIMENTAL
RADIO STATION CONSTRUCTION PERMIT
AND LICENSE**

EXPERIMENTAL

(Nature of Service)

XT FX

(Class of Station)

WJ2XZC

(Call Sign)

0957-EX-CN-2018

(File Number)

NAME General Aviation Aircraft Service, dba, Meridian - Teterboro

Subject to the provisions of the Communications Act of 1934, subsequent acts, and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions and requirements set forth in this license, the licensee hereof is hereby authorized to use and operate the radio transmitting facilities hereinafter described for radio communications in accordance with the program of experimentation described by the licensee in its application for license.

Operation: In accordance with Sec. 5.3(J) of the Commission's Rules

Station Locations

- (1) Teterboro (BERGEN), NJ - NL 40-51-03; WL 74-04-08
- (2) Teterboro (BERGEN), NJ - NL 40-51-05; WL 74-04-05
- (3) Teterboro (BERGEN), NJ - NL 40-51-27; WL 74-03-43
- (4) Teterboro (BERGEN), NJ - NL 40-51-28; WL 74-03-42

Frequency Information

Teterboro (BERGEN), NJ - NL 40-51-03; WL 74-04-08

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	2M04W7D	19.2 pW (ERP)	0.01 %

Teterboro (BERGEN), NJ - NL 40-51-05; WL 74-04-05

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	2M04W7D	19.2 pW (ERP)	0.01 %

This authorization effective March 05, 2019 and
will expire 3:00 A.M. EST March 01, 2021

**FEDERAL
COMMUNICATIONS
COMMISSION**



Frequency Information

Teterboro (BERGEN), NJ - NL 40-51-27; WL 74-03-43

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	2M04W7D	19.2 pW (ERP)	0.01 %

Teterboro (BERGEN), NJ - NL 40-51-28; WL 74-03-42

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	2M04W7D	19.2 pW (ERP)	0.01 %

Special Conditions:

- (1) GPS re-radiators are limited to a maximum ERP value that will result in power levels not to exceed a power spectral density of -140 dBm/24 MHz measured at a distance of 100 ft outside the building of operation. Any malfunction, misalignment, or tampering of the equipment or its location which results in an increased power spectral density outside the building could cause harmful radio frequency interference to GPS receivers, including those in aircraft and/or ground based facilities.
- (2) Licensee should be aware that other stations may be licensed on these frequencies and if any interference occurs, the licensee of this authorization will be subject to immediate shut down.
- (3) In lieu of frequency tolerance, the occupied bandwidth of the emission shall not extend beyond the band limits set forth above.
- (4) The designated point of contact to terminate the systems if interference occurs is STEVE CHANDOHA 201-288-5040
- (5) GPS users in the area of potential interference to GPS reception must be notified that GPS information may be impacted for periods of time.
- (6) Licensee shall maintain testing according to the NTIA requirements of section 8.3.27 as stated in the filed application.
- (7) Licensee shall post signs on doors to the test area notifying that, "GPS re-radiator is in use and the GPS information you receive may be in error." For Indoor Use Only.
- (8) Authorization is for indoor use only.
- (9) The device is to be used as an Experimental RNSS Test Equipment for the purpose of testing RNSS equipment/systems.

Special Conditions:

- (10) The area of potential interference to GPS reception has to be under the control of the user.
- (11) GPS re-radiators must operate in accordance with Section 8.3.28 of the NTIA Manual. Power spectral density of the signal should be very well controlled beyond the building.
- (12) This authorization SUPERSEDES the previously issued authorization with the same call sign and file number: amended conditions.