

NTIA Space record data form

NTIA requires the following data for space related experiments using government shared spectrum. For each transmit frequency, please provide the data for both ends of the transmit-receive link. Use Part A to describe the satellite to ground information. Part B is for all ground to space transmit links.

Part A: Space to Earth Downlink Data

Satellite Transmitter Data

Transmit Frequency: 437.475 MHz		
Satellite Name: RANGE-B		
Data Field	Data Answer	Description/Comments
Polarization (XAP)	XAP = J	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Orientation (XAZ)	XAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Antenna Dimension (XAD)	ANTENNA GAIN__1.4 dBi_____ BEAMWIDTH __360_____ XAD = XAD01 02G360B	(NTIA format (XAD), EXAMPLE, XAD01 16G030B)
Type of satellite (State = SP) (City = geo or non)	Type = Nongeostationary	Choose either: Geostationary or Nongeostationary
For Geostationary	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE__97.4_____, APOGEE IN KILOMETERS__500_____, PERIGEE IN KILOMETERS__500_____, ORBITAL PERIOD IN HOURS __1____AND FRACTIONS OF HOURS IN DECIMAL__0.53____, THE NUMBER OF SATELLITES IN THE SYSTEM__2_____, ORB = ORB,97.4IN00500AP00500PE001.53H02N RT01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01

	ORB,97.4IN00500AP00500PE001.53H02N RTR01	
Earth Station Data (Receiver)		
State (RSC)	RSC = GA	
City Name (RAL)	RAL = Atlanta	
Latitude (DDMMSS)	Lat = 334619	
Longitude (DDDMMSS)	Lon = 842346	
Antenna Polarization (RAP)	RAP = T	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Antenna Azimuth (RAZ)	RAZ = RAZ01 V00	THE EARTH STATION RECEIVER ANTENNA AZIMUTH (RAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, RAZ01 V00
Antenna Dimensions (RAD)	ANTENNA GAIN _____18.9_____, BEAMWIDTH _____21_____, AZIMUTHAL RANGE _____360_____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____340_____ THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____10_____ RAD = RAD01 19G021B000-360A00340H010	EXAMPLE ASSUMING NONGEOSTATIONARY, RAD01 16G030B000-360A00357H006
FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, RANGE-B		

Part B: Ground Stations, Earth to Space link data:

Earth Station Transmitter Data

Transmit Frequency: 437.475 MHz		
State (XSC)	XSC = GA	
City Name (XAL)	XAL = Atlanta	
Latitude (DDMMSS)	Lat = 334619	
Longitude (DDDMMSS)	Lon = 842346	
Antenna Polarization (XAP)	XAP = T	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Antenna Azimuth (XAZ)	XAZ = V00 to V90	THE EARTH STATION Transmitter ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, XAZ01 V00
Antenna Dimensions (XAD)	ANTENNA GAIN____18.9 dBi_____ BEAMWIDTH____21_____ AZIMUTHAL RANGE____360_____ THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____340_____ THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____10_____ XAD = XAD01 19G021B000-360A00340H010	EXAMPLE ASSUMING NONGEOSTATIONARY, XAD01 16G030B000-360A00357H006
Satellite Receive Specifications		
Polarization (RAP)	RAP = T	POLARIZATIONS INCLUDE : H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Azimuth (RAZ)	RAZ = RAZ01 V00	STATION RECEIVER ANTENNA AZIMUTH (XAZ), THE MINIMUM ANGLE OF ELEVATION, V00 TO V90, EXAMPLE, RAZ01 V00
Dimension (RAD)	ANTENNA GAIN____1.4 dBi_____ BEAMWIDTH ____360_____ RAD = RAD01 02G360B	(NTIA format (RAD), EXAMPLE, RAD01 16G030B)

Type of satellite (State = SP) City = G/No	Type = Nongeostationary	Choose either: Geostationary or Nongeostationary
For Geostationary	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE____97.4_____, APOGEE IN KILOMETERS____500_____, PERIGEE IN KILOMETERS____500_____, ORBITAL PERIOD IN HOURS ____1____AND FRACTIONS OF HOURS IN DECIMAL__0.53_____, THE NUMBER OF SATELLITES IN THE SYSTEM____2_____, ORB,97.4IN00500AP00500PE001.53H02N RT01 ORB,97.4IN00500AP00500PE001.53H02N RTR01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01