

**United States of America
FEDERAL COMMUNICATIONS COMMISSION
EXPERIMENTAL
RADIO STATION CONSTRUCTION PERMIT
AND LICENSE**

EXPERIMENTAL

(Nature of Service)

WK2XLV

(Call Sign)

XD FX MO

(Class of Station)

0192-EX-CM-2021

(File Number)

NAME _____ Insitu _____

Subject to the provisions of the Communications Act of 1934, subsequent acts, and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions and requirements set forth in this license, the licensee hereof is hereby authorized to use and operate the radio transmitting facilities hereinafter described for radio communications in accordance with the program of experimentation described by the licensee in its application for license.

Operation: In accordance with Sec. 5.3(j) of the Commission's Rules

Station Locations

- (1) Boardman Bombing Ran, OR - NL 45-44-54; WL 119-47-38
- (2) Bingen, WA - NL 45-42-24; WL 121-27-30
- (3) MOBILE: Boardman Bombing Ran, OR. Flight Level is 10000 feet, within 200 km, centered around NL 45-44-54; WL 119-47-38
- (4) Pendleton, OR - NL 45-41-52; WL 118-50-12
- (5) MOBILE: Pendleton, OR. Maximum Flight Level is 15,000 Feet, within 50 km, centered around NL 45-41-52; WL 118-50-12

Frequency Information

Boardman Bombing Ran, OR - NL 45-44-54; WL 119-47-38

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
30-50 MHz	FX	6K00A3E 11K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
60-64 MHz	FX	6K00A3E 11K0F3E 16K0F3E	5 W (ERP)	

This authorization effective October 04, 2021 and
will expire 3:00 A.M. EST October 01, 2023

**FEDERAL
COMMUNICATIONS
COMMISSION**



Frequency Information

Boardman Bombing Ran, OR - NL 45-44-54; WL 119-47-38

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
60-64 MHz	FX	25K0A3E 25K0F3E	5 W (ERP)	
76-80 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
138-148 MHz	FX	6K00A3E 11K0F3E 12K5A3E 12K5F3E	5 W (ERP)	
174-200 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
217-220 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
401-406 MHz	FX	6K00A3E 11K0F3E 16K0F3E	5 W (ERP)	

Frequency Information

Boardman Bombing Ran, OR - NL 45-44-54; WL 119-47-38

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
401-406 MHz	FX	25K0A3E 25K0F3E	5 W (ERP)	
465-470 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
480-495 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	

Bingen, WA - NL 45-42-24; WL 121-27-30

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
30-50 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
60-64 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E	5 W (ERP)	

Frequency Information

Bingen, WA - NL 45-42-24; WL 121-27-30

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
60-64 MHz	FX	25K0F3E	5 W (ERP)	
76-80 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
138-148 MHz	FX	6K00A3E 11K0F3E 12K5A3E 12K5F3E	5 W (ERP)	
174-200 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
217-220 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
401-406 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E	5 W (ERP)	

Frequency Information

Bingen, WA - NL 45-42-24; WL 121-27-30

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
401-406 MHz	FX	25K0F3E	5 W (ERP)	
465-470 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
480-495 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	

MOBILE: Boardman Bombing Ran, OR. Flight Level is 10000 feet, within 200 km, centered around NL 45-44-54; WL 119-47-38

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
30-50 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	
60-64 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E	2 W (ERP)	

Frequency Information

MOBILE: Boardman Bombing Ran, OR. Flight Level is 10000 feet, within 200 km, centered around NL 45-44-54; WL 119-47-38

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
60-64 MHz	MO	25K0F3E	2 W (ERP)	
76-80 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	
138-148 MHz	MO	6K00A3E 11K0F3E 12K5A3E 12K5F3E	2 W (ERP)	
174-200 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	
217-220 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	
401-406 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E	2 W (ERP)	

Frequency Information

MOBILE: Boardman Bombing Ran, OR. Flight Level is 10000 feet, within 200 km, centered around NL 45-44-54; WL 119-47-38

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
401-406 MHz	MO	25K0F3E	2 W (ERP)	
465-470 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	
480-495 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	

Pendleton, OR - NL 45-41-52; WL 118-50-12

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
30-50 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
60-64 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E	5 W (ERP)	

Frequency Information

Pendleton, OR - NL 45-41-52; WL 118-50-12

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
60-64 MHz	FX	25K0F3E	5 W (ERP)	
76-80 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
138-148 MHz	FX	6K00A3E 11K0F3E 12K5A3E 12K5F3E	5 W (ERP)	
174-200 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
217-220 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
401-406 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E	5 W (ERP)	

Frequency Information

Pendleton, OR - NL 45-41-52; WL 118-50-12

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
401-406 MHz	FX	25K0F3E	5 W (ERP)	
465-470 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	
480-495 MHz	FX	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	5 W (ERP)	

MOBILE: Pendleton, OR. Maximum Flight Level is 15,000 Feet, within 50 km, centered around NL 45-41-52; WL 118-50-12

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
30-50 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	
60-64 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E	2 W (ERP)	

Frequency Information

MOBILE: Pendleton, OR. Maximum Flight Level is 15,000 Feet, within 50 km, centered around NL 45-41-52; WL 118-50-12

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
60-64 MHz	MO	25K0F3E	2 W (ERP)	
76-80 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	
138-148 MHz	MO	6K00A3E 11K0F3E 12K5A3E 12K5F3E	2 W (ERP)	
174-200 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	
217-220 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	
401-406 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E	2 W (ERP)	

Frequency Information

MOBILE: Pendleton, OR. Maximum Flight Level is 15,000 Feet, within 50 km, centered around NL 45-41-52; WL 118-50-12

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
401-406 MHz	MO	25K0F3E	2 W (ERP)	
465-470 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	
480-495 MHz	MO	6K00A3E 11K0F3E 16K0F3E 25K0A3E 25K0F3E	2 W (ERP)	

Special Conditions:

- (1) Operation is subject to prior coordination with the local Society of Broadcast Engineers, Inc. (SBE) frequency coordinator. Consult the list at <http://sbe.org/wp-content/uploads/freqcoor.pdf> to find the appropriate coordinator.
- (2) Licensee should be aware that other stations may be licensed on these frequencies and if any interference occurs, the licensee of this authorization will be subject to immediate shut down.
- (3) In lieu of frequency tolerance, the occupied bandwidth of the emission shall not extend beyond the band limits set forth above.
- (4) The station identification requirements of Section 5.115 of the Commission's Rules are waived.
- (5) Prior to commencing any operations in the frequencies below, the experimental licensee must obtain consent from the following within 141 miles of the contours of the testing area:
 Paging Service licensees in 35 MHz
 Paging Service licensees in 43 MHz
 AMTS Licensee (217-218 MHz/219-220 MHz)
 218-219 MHz Service licensees
- (6) Airborne use of the Part 22 Paging frequencies (35 MHz, 43 MHz, 152 MHz, 158 MHz and 931 MHz) is not allowed due to an explicit airborne prohibition in our rules.
- (7) During transmission, aircraft shall not exceed the altitude of 15000 ft AGL.

Special Conditions:

(8) The stop buzzer POC is Insitu Operations Center at (509) 637-4691.