

EXHIBIT 2

PARTICULARS OF OPERATION:

CALL SIGN	FREQUENCIES	CLASS	OUTPUT POWER/ERP	Tolerance	Emission Designator	MODULAT- ING SIGNAL
B029	2602.0-2608.0 MHz, 2618.0- 2624.0 MHz, 2640.5-2673.5 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
B461	2602.0-2614.0 MHz, 2618.0-2673.5 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
WNC708	2502.0-2518.5 MHz, 2572.0-2578.0 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
WHR807	2518.5-2524.0 MHz, 2578.0-2584.0 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
WDT881	2502.0-2518.5 MHz, 2572.0-2578.0 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
WHT631	2602.0-2608.0 MHz, 2640.5-2657.0 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
WNEK883	2657.0-2662.5 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
WNEY445	2657.0-2662.5 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
WNEK840	2662.5-2668.0 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
WHJ920	2668.0-2673.5 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
WHT659	2602.0-2608.0 MHz, 2640.5-2657.0 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA
WMY489	2657.0-2662.5 MHz	MO	444 mW/220 mW	5%	10M0FXW/ 5M00FXW	OFDMA