

UNCLASSIFIED

J/F 12/07989

SECURITY SUMMARY & SPECIAL HANDLING REQUIREMENTS

The title of this application is: TUAV Video Link

The overall classification of this application is: **UNCLASSIFIED**

The following Special Handling summary lists the applicable markings for the printed page(s). It is your responsibility to place all Special Handling markings on the cover page of the application.

If an Entire Application was printed, the following Special Handling summary lists the applicable markings for the Entire Application.

If an Individual Page (TX, RX, ANT, etc.) was printed, the following Special Handling summary lists the applicable markings for the printed page. It is your responsibility to make certain that any Special Handling markings that are unique to the Individual Page are also reflected on the cover of the Entire Application.

If the "!" code is shown below, the "SEE REMARKS" refers to the REMARKS block on the applicable page.

Refer to your Security Manual for further guidance.

No Application Level Special Handling
No Page Level Special Handling

UNCLASSIFIED

J/F 12/07989

The title of this application is: **TUAV Video Link**

All Application Level Special Handling markings (if any) will appear at the top of the Special Handling list for each individual page type. Field Level markings will follow. It is your responsibility to mark the individual pages of this application in accordance with the procedures in your Security Manual. The following summaries are provided for that purpose.

[illegible]

APPLICATION FOR EQUIPMENT FREQUENCY ALLOCATION		CLASSIFICATION UNCLASSIFIED		DATE 10-17-2002		J/F 12/07989	
						Page 1 of 9 Pages	
DOD GENERAL INFORMATION							
TO USMCEB				FROM Office of the Army Spectrum Manager Submitted By: (Project Manager, UAV Systems ATTN: SFAE-AV-UAV-TM)			
1. APPLICATION TITLE (U) TUAV Video Link							
2. SYSTEM NOMENCLATURE (U) Tactical Unmanned Aerial Vehicle System (079 89)							
3. STAGE OF ALLOCATION (U) ☐ a. STAGE 1 CONCEPTUAL ☐ b. STAGE 2 EXPERIMENTAL ☐ c. STAGE 3 DEVELOPMENTAL ☒ d. STAGE 4 OPERATIONAL							
4. FREQUENCY REQUIREMENTS							
a. FREQUENCY(IES) (U) 4.4 GHz - 4.94 GHz 5.25 GHz - 5.85 GHz							
b. EMISSION DESIGNATORS (U) 16M3F3F 16M3F3F							
5. TARGET STARTING DATE FOR SUBSEQUENT STAGES							
a. STAGE 2 (U) NA b. STAGE 3 (U) NA c. STAGE 4 (U) NA							
6. EXTENT OF USE (U) Up to 18 hrs/day							
7. GEOGRAPHICAL AREA FOR							
a. STAGE 2 (U) NA							
b. STAGE 3 (U) NA							
c. STAGE 4 (U) US&P (See Remarks)							
8. NUMBER OF UNITS							
a. STAGE 2 (U) NA b. STAGE 3 (U) NA c. STAGE 4 (U) 176							
9. NUMBER OF UNITS OPERATING SIMULTANEOUSLY IN THE SAME ENVIRONMENT(U) 6							
10. OTHER J/F 12 APPLICATION ID(S) TO BE (U) ☐ a. SUPERSEDED ☐ b. RELATED				11. IS THERE ANY OPERATIONAL REQUIREMENT AS DESCRIBED IN THE INSTRUCTIONS FOR PARAGRAPH 11? (U) ☐ a. YES ☒ b. NO ☐ c. NAVAIL			
12. NAMES AND TELEPHONE NUMBERS (U)							
a. PROGRAM MANAGER COL Michael Hamilton				(1) COMMERCIAL 256-895-4449		(2) DSN 788-4449	
b. PROJECT ENGINEER Mr. Tommy Thomas				(1) COMMERCIAL 256-895-4321		(2) DSN 788-4321	
13. REMARKS (U) Unit is used for transmission of realtime analog video imagery from the UAV to any properly equipped ground receiver within LOS. Block 7c: Leighton Barracks, Wurzburg, Germany; (Uijongbu, Camp Red Cloud) Republic of Korea; Item 8c: 4 transmitters and 7 receivers per TUAV system.							
DOWNGRADING INSTRUCTIONS						J/F 12/07989	
						CLASSIFICATION UNCLASSIFIED	

CLASSIFICATION UNCLASSIFIED		PAGE 2	
TRANSMITTER EQUIPMENT CHARACTERISTICS			
1. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) 38214-41660-10 Transmitter		2. MANUFACTURER'S NAME (U) AAI Corporation	
3. TRANSMITTER INSTALLATION (U) TUAV		4. TRANSMITTER TYPE (U) FM Communications	
5. TUNING RANGE (U) 4.4 GHz - 4.94 GHz 5.25 GHz - 5.85 GHz		6. METHOD OF TUNING (U) Digital Synthesizer	
7. RF CHANNELING CAPABILITY (U) 4.4 GHz, 1 MHz increments(See Remarks)		8. EMISSION DESIGNATORS (U) 16M3F3F (U)	
9. FREQUENCY TOLERANCE (U) 20 ppm		12. EMISSION BANDWIDTH ☐ CALCULATED ☒ MEASURED	
10. FILTER EMPLOYED (U) ☐ a. YES ☒ b. NO		a. -3 dB (U) 2 MHz (U)	
		b. -20 dB (U) 16.0 MHz (U)	
		c. -40 dB (U) 26 MHz (U)	
11. SPREAD SPECTRUM (U) ☐ a. YES ☒ b. NO		d. -60 dB (U) 30.0 MHz (U)	
		e. OC-BW(U) 16.8 MHz (U)	
13. MAXIMUM BIT RATE (U) NA		15. MAXIMUM MODULATION FREQUENCY (U) 4.2 MHz	
14. MODULATION TECHNIQUES AND CODING (U) FM Video		17. DEVIATION RATIO (U) 1	
16. PRE-EMPHASIS (U) ☒ a. YES ☐ b. NO		18. PULSE CHARACTERISTICS	
		a. RATE (U) NA (U)	
19. POWER		b. WIDTH (U) NA (U)	
a. MEAN (U) 10 mW (U) (U) - 30 W		c. RISE TIME (U) NA (U) (U)	
b. PEP (U) NA (U) (U)		d. FALL TIME (U) NA (U) (U)	
		e. COMP RATIO (U) NA (U) (U)	
20. OUTPUT DEVICE (U) Field Effect Transistor		21. HARMONIC LEVEL	
		a. 2nd (U) -50 dB	
22. SPURIOUS LEVEL (U) -50 dB		b. 3rd (U) -70 dB	
23. FCC TYPE ACCEPTANCE NO. (U) NA		c. OTHER (U) -80 dB	
24. REMARKS (U) Item 1: OCONUS HPA part number is 38214-91005-1; 5 GHz band CONUS HPA part number is 38214-91005-2; 4 GHz band Item 7: 5.25 GHz, 1.0 MHz increments Item 16: Pre-emphasis IAW ITU Recommendation F405-1 for 525 line video; is 3 dB. Item 19: The transmitter system is composed of a tunable low power device with the capability to output between 10 to 30 mWatts. The HPA add 20 dB of gain to achieve between 10 to 30 Watts of output.			

CLASSIFICATION UNCLASSIFIED				PAGE 3	
RECEIVER EQUIPMENT CHARACTERISTICS					
1. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) 38214-44410-10 Compact2 Receiver			2. MANUFACTURER'S NAME (U) AAI Corporation		
3. RECEIVER INSTALLATION (U) Mobile Ground Stations			4. RECEIVER TYPE (U) Double Conversion Superhetrodyne		
5. TUNING RANGE (U) 4.4 GHz - 4.94 GHz 5.25 GHz - 5.85 GHz			6. METHOD OF TUNING (U) Digital Synthesizer		
7. RF CHANNELING CAPABILITY (U) 4.4 GHz, 1 MHz increments(See Remarks)			8. EMISSION DESIGNATORS (U) 16M3F3F		
9. FREQUENCY TOLERANCE (U) 20 ppm			11. RF SELECTIVITY ☐ CALCULATED ☒ MEASURED		
10. IF SELECTIVITY			a. -3 dB (U) 730 MHz		
1st (U)			b. -20 dB (U) 1400 MHz		
2nd (U)			c. -60 dB (U) 2409 MHz		
3rd (U)			d. Preselection Type (U) 6 Section Cavity BPF		
a. -3 dB 39 MHz			13. MAXIMUM POST DETECTION FREQUENCY (U) 4.2 MHz		
b. -20 dB 58 MHz			14. MINIMUM POST DETECTION FREQUENCY (U) 10 Hz		
c. -60 dB 145 MHz			16. MAXIMUM BIT RATE (U) NA		
12. IF FREQUENCY			17. SENSITIVITY		
a. 1st (U) 964 MHz			a. SENSITIVITY (U) - 91 dBm		
b. 2nd (U) 70 MHz			b. CRITERIA (U) 12dB S+N/N		
c. 3rd (U)			c. NOISE FIG (U) 2.5 dB		
15. OSCILLATOR TUNED			d. NOISE TEMP (U) NA		
1st (U)			20. SPURIOUS REJECTION		
2nd (U)			(U) 75 dB		
3rd (U)					
a. ABOVE TUNED FREQUENCY					
b. BELOW TUNED FREQUENCY X					
c. EITHER ABOVE OR BELOW THE FREQUENCY					
18. DE-EMPHASIS (U) ☒ a. YES ☐ b. NO					
19. IMAGE REJECTION (U) 60 dB					
21. REMARKS (U) Unit is wideband in design to accommodate operation in both the CONUS and OCONUS (4.4 to 4.95 GHz and 5.25 to 5.85 GHz respectively). Item 7: 5.25 GHz, 1.0 MHz increments Item 17: The receiver system includes a 30 dB gain LNA in RF Box Assembly (part number 38214-444401-10) which is located 12 feet from the receiver assembly. Item 18: De-emphasis IAW ITU Recommendation F405-1 for 525 line video, is 3 dB.					
CLASSIFICATION UNCLASSIFIED				J/F 12/07989	

CLASSIFICATION

UNCLASSIFIED

PAGE 4

ANTENNA EQUIPMENT CHARACTERISTICS

1. (U) ☐ a. TRANSMITTING ☐ b. RECEIVING ☒ c. TRANSMITTING AND RECEIVING

2. NOMENCLATURE, MANUFACTURER'S MODEL NO.

(U) 38214-90001-1

3. MANUFACTURER'S NAME

(U) AAI Corporation

4. FREQUENCY RANGE

(U) 5.25 GHz - 5.85 GHz

5. TYPE (U) Monopole

7. SCAN CHARACTERISTICS

a. TYPE (U) FIXED

b. VERTICAL SCAN (U) NA

(1) Max Elev (U) NA

(2) Min Elev (U) NA

(3) Scan Rate (U) NA

c. HORIZONTAL SCAN (U) NA

(1) Sector Scanned (U) NA

(2) Scan Rate (U) NA

d. SECTOR BLANKING (U) ☐ (1) YES ☒ (2) NO

6. POLARIZATION

(U) Vertical

8. GAIN

a. MAIN BEAM

(U) 4.32 dBi

b. 1st MAJOR SIDE LOBE

(U) NA

9. BEAMWIDTH

a. HORIZONTAL

(U) 360 deg

b. VERTICAL

(U) 60 deg

10. REMARKS (U)

Item 1: These omni antennas are used in 2 places in the system, one as a transmit antenna aboard the UAV and one as a receive only unit at each control station, either the Ground Data Terminal or the Portable Ground Data Terminal (see line diagram).

CLASSIFICATION

UNCLASSIFIED

J/F 12/07989

CLASSIFICATION

UNCLASSIFIED

PAGE 6

ANTENNA EQUIPMENT CHARACTERISTICS

1. (U) ☐ a. TRANSMITTING ☒ b. RECEIVING ☐ c. TRANSMITTING AND RECEIVING	
2. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) 38214-90003-1 Reflector (Remarks)	3. MANUFACTURER'S NAME (U) AAI Corporation
4. FREQUENCY RANGE (U) 4.4 GHz - 4.95 GHz	5. TYPE (U) Parabolic Reflector
6. POLARIZATION (U) Linear Vertical	7. SCAN CHARACTERISTICS
8. GAIN	a. TYPE (U) MECHANICAL
a. MAIN BEAM (U) 31.5 dBi	b. VERTICAL SCAN (U) Mechanical
b. 1st MAJOR SIDE LOBE (U) 11.5 dBi @ 7.3 deg	(1) Max Elev (U) +95 deg
9. BEAMWIDTH	(2) Min Elev (U) -5 deg
a. HORIZONTAL (U) 4.35 deg	(3) Scan Rate (U) 11 deg/sec max
b. VERTICAL (U) 4.35 deg	c. HORIZONTAL SCAN (U) Mechanical
	(1) Sector Scanned (U) 360 degrees
	(2) Scan Rate (U) 11 deg/sec max
	d. SECTOR BLANKING (U) ☐ (1) YES ☒ (2) NO

10. REMARKS (U)

Item 2: Dual Element Feed part number is 38214-90004-1 (CONUS)
Rotor part number is 38214-90002-1

CLASSIFICATION

UNCLASSIFIED

J/F 12/07989

ANTENNA EQUIPMENT CHARACTERISTICS

1. (U) ☐ a. TRANSMITTING ☐ b. RECEIVING ☒ c. TRANSMITTING AND RECEIVING

2. NOMENCLATURE, MANUFACTURER'S MODEL NO.

(U) 38214-90001-2

3. MANUFACTURER'S NAME

(U) AAI Corporation

4. FREQUENCY RANGE

(U) 4.4 GHz - 4.95 GHz

5. TYPE (U) Monopole

7. SCAN CHARACTERISTICS

a. TYPE (U) FIXED

b. VERTICAL SCAN (U) NA

(1) Max Elev (U) NA

(2) Min Elev (U) NA

(3) Scan Rate (U) NA

c. HORIZONTAL SCAN (U) NA

(1) Sector Scanned (U) NA

(2) Scan Rate (U) NA

d. SECTOR BLANKING (U) ☐ (1) YES ☒ (2) NO

6. POLARIZATION

(U) Vertical

8. GAIN

a. MAIN BEAM

(U) 3.5 dBi

b. 1st MAJOR SIDE LOBE

(U) NA

9. BEAMWIDTH

a. HORIZONTAL

(U) 360 deg

b. VERTICAL

(U) 65 deg

10. REMARKS (U)

Block 1: These omni antennas are used in 2 places in the system, one as a transmit antenna aboard the UAV and one as a receive only unit at each control station, either the Ground Data Terminal or the Portable Ground Data Terminal.

APPLICATION FOR SPECTRUM REVIEW	CLASSIFICATION UNCLASSIFIED	PAGE 8
NTIA GENERAL INFORMATION		
1. APPLICATION TITLE (U) TUAV Video Link		
2. SYSTEM NOMENCLATURE (U) Tactical Unmanned Aerial Vehicle System (07989)		
3. STAGE OF ALLOCATION (U) ☐ a. STAGE 1 CONCEPTUAL ☐ b. STAGE 2 EXPERIMENTAL ☐ c. STAGE 3 DEVELOPMENTAL ☒ d. STAGE 4 OPERATIONAL		
4. FREQUENCY REQUIREMENTS a. FREQUENCY(IES) (U) 4.4 GHz - 4.94 GHz 5.25 GHz - 5.85 GHz b. EMISSION DESIGNATORS (U) 16M3F3F 16M3F3F		
5. PURPOSE OF SYSTEM, OPERATIONAL AND SYSTEM CONCEPTS (U) Video Tx/Rx system used for dissemination of real time imagery intelligence from the airborne UAV. (WARTIME USE) ☒ a. YES ☐ b. NO		
6. INFORMATION TRANSFER REQUIREMENTS(U) NA		
7. ESTIMATED INITIAL COST OF THE SYSTEM (U) Development TUAV System: \$2M; Production TUAV System: \$4M ea		
8. TARGET DATE FOR		
a. APPLICATION APPROVAL (U) 09-01-2002	b. SYSTEM ACTIVATION (U) 10-31-2002	c. SYSTEM TERMINATION (U) 2025
9. SYSTEM RELATIONSHIP AND ESSENTIALITY (U) System provides critical realtime surveillance and reconnaissance to the Brigade commander in the tactical environment. System is used for accurately locating and identifying tactical targets, gunfire direction support, and battle damage assessment.		
10. REPLACEMENT INFORMATION (U) NA		
11. RELATED ANALYSIS AND/OR TEST DATA (U) NA		
12. NUMBER OF MOBILE UNITS (U) Per system: 4 aeronautical mobile, 3 ground mobile		
13. GEOGRAPHICAL AREA FOR		
a. STAGE 2 (U) NA		
b. STAGE 3 (U) NA		
c. STAGE 4 (U) US&P (See Remarks)		
14. LINE DIAGRAM (U) See Page(s) 8		15. SPACE SYSTEMS (U) See Page(s) NA
16. TYPE OF SERVICE(S) FOR STAGE 4 (U) Mobile		17. STATION CLASS(ES) FOR STAGE 4 (U) MO
18. REMARKS (U) The system is designed to operate in two sections of 4.4 to 5.85 GHz Band known as CONUS and OCONUS, with simple substitution of a minimal amount of hardware. The transmitter and receiver are capable of operation in 1 MHz steps in each band. Airborne antennas and power amplifiers are swapped in the UAV and ground based antennas (both directional and omni-directional) are swapped on the ground to effect band switch-over.		
DOWNGRADING INSTRUCTIONS		J/F 12/07989
		CLASSIFICATION UNCLASSIFIED

NTIA REMARK OVERFLOW PAGE

Item 9: The TUAV system can operate as a self contained system presenting live video imagery to the commander on a video monitor or the video intelligence information may be disseminated via C4I interfaces to other units in the Tactical Operations Center (TOC).

Item 13c: Leighton Barracks, Wurzburg, Germany; (Uijongbu, Camp Red Cloud) Republic of Korea