

**United States of America
FEDERAL COMMUNICATIONS COMMISSION
EXPERIMENTAL
RADIO STATION CONSTRUCTION PERMIT
AND LICENSE**

EXPERIMENTAL

(Nature of Service)

WH2XQW

(Call Sign)

XC FX MO

(Class of Station)

0155-EX-CR-2021

(File Number)

NAME L3Harris Technologies, Inc.

Subject to the provisions of the Communications Act of 1934, subsequent acts, and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions and requirements set forth in this license, the licensee hereof is hereby authorized to use and operate the radio transmitting facilities hereinafter described for radio communications in accordance with the program of experimentation described by the licensee in its application for license.

Operation: In accordance with Sec. 5.3(c & j) of the Commission's Rules

Station Locations

- (1) Rochester (MONROE), NY - NL 43-08-51; WL 77-33-24; MOBILE: Rochester, NY, within 50 km, centered around NL 43-08-51; WL 77-33-24

Frequency Information

Rochester (MONROE), NY - NL 43-08-51; WL 77-33-24; MOBILE: Rochester, NY, within 50 km, centered around NL 43-08-51

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1370-1390 MHz	FX	5M00D7D	200 W (ERP)	0.005 %
1370-1390 MHz	MO	5M00D7D	200 W (ERP)	0.005 %

Special Conditions:

- (1) This frequency assignment was coordinated prior to authorization with FAA Headquarters, 800 Independence Avenue, S.W., Washington, DC 20591; Telephone: 202-267-8699.
- (2) The occupied bandwidth of the emission shall not extend beyond the band limits set forth above.
- (3) The station identification requirements of Section 5.115 of the Commission's Rules are waived.

This authorization effective April 01, 2021 and
will expire 3:00 A.M. EST April 01, 2023

**FEDERAL
COMMUNICATIONS
COMMISSION**



Special Conditions:

- (4) Licensee should be aware that other stations may be licensed on these frequencies and if any interference occurs, the licensee of this authorization will be subject to immediate shut down.
- (5) Transmissions are required to be blanked between 50-100 and 225-270 degrees reference to true north.