

Exhibit 1

Description of Experimental Program

System 12

Lockheed Martin Corporation requires the use of GPS Re-Radiation (Re-Rad) systems inside our aircraft production/flight test facilities at Palmdale Airfield, California.¹ This equipment will be used as “Experimental RNSS Test Devices” for the purpose of testing and verifying GPS receiver functionality of various aircraft systems. Currently, in order to obtain a GPS signal, the aircraft and all supporting test equipment must be towed outside of the production/flight test facility. During this time, aircraft and personnel are exposed to adverse weather conditions and prevented from accessing certain tools and equipment. In addition, additional power and cooling is required for the aircraft. At certain times, due to safety and efficiency considerations, Lockheed Martin must have the ability to perform pre-flight GPS receiver functionality tests indoors. The GPS Re-Rad systems are designed to re-transmit the GPS signal at approximately the same signal level as received outside the hangars. This Exhibit describes the various implementations required at Palmdale. The purpose of this application is modify the license to add GPS L1 in addition to its currently-authorized GPS L2.

1. PROGRAM DESCRIPTIONS

F-22. The program title is: F-22 “Raptor” Modification Line. The contract number for this program is: F33657-02-D-0009.

General Description.

GPS Re-Rad capability is needed in one building at Lockheed Martin Aeronautics Company Plant 10 to support the F-22 “Raptor” modification line. GPS signals are necessary for the checkout, alignment and maintenance of the F-22 avionics and test instrumentation systems. GPS signal coverage indoors is needed to allow GPS enabled systems to be operated while the aircraft is physically unable to be moved outdoors.

Technical Information.

Locations:

- Two fixed antennas inside hangar facility at Lockheed Martin Aeronautics Co. Plant 10, Building 601, West Hangar (601T1/T2 respectively).

Longitude: W 118 07.195
Latitude: N 34 36.794

Longitude: W 118 07.172
Latitude: N 34 36.795

2. EQUIPMENT

All of the above sites will use the following equipment:

¹ The overall Palmdale Airfield is mostly USAF property. The AF designated their Palmdale facility “Plant 42” and segregated the facility into several physical “sites” that are used for specific purposes or programs, many of which are operated by contractors such as Lockheed Martin. Lockheed Martin also privately owns property associated with the Palmdale Airfield, which has been named “Plant 10” (not to be confused with Site 10 of USAF Production Plant 42).

Transmit Antenna Orientation: 180 degrees vertical, 360 degrees horizontal. All antennas are directional facing down toward the article under test.

Transmit Antenna Polarization: Right hand circular polarization (RHCP)

Frequencies: 1227.6 MHz (currently authorized), 1575.42 MHz (GPS L2/L1)

Emissions: 20M4W7D

Power at antenna: Table 1

TABLE 1		L1		
Reradiator Identifier	Maximum RF Power at the Transmitter Output Terminal	Maximum EIRP from the Antenna		
		dBm (EIRP)	Watts (EIRP)	Watts (ERP)
601T1	32.4E-12	-70.86	82.03E-12	50.00E-12
601T2	32.4E-12	-70.86	82.03E-12	50.00E-12

3. CONDITIONS OF LICENSE

For all the foregoing programs, the following conditions will apply.

The experimental period will last for two years or 24 months.

In order to ensure no GPS re-radiated signal adversely affects safety-of-life applications, Lockheed Martin will only transmit:

- Indoors;
- Such that no GPS re-radiated signal level greater than or equal to -140 dBm, measured 100 feet from the building perimeter will occur; and
- When testing an airplane indoors is considered necessary.

In addition:

- The “Stop Buzzer” emergency point of contact (POC) will be Rich Elersich (661) 572-3595, cell (661) 802-1152. The secondary POC will be Geva Frevert (661) 572-4978, cell 661-917-7451.
- If the POC changes, Lockheed Martin Aeronautics Company will immediately notify the FCC.
- The location of the GPS transmitters will be fixed and located in such a way that the entire area of potential interference from the GPS transmitters is under the control of Lockheed Martin personnel - the facility where the transmitters will be located is a “secure” facility where security personnel control ingress and egress.