

UNCLASSIFIED

RB Flight Test - Exhibit 001

-These frequencies have been coordinated with the Army MAG Representative

Frequency MHz	Power			Emission	Modulating Signal	Necessary Bandwidth (KHz)
(A) list each frequency separately	(B) max RF, output at transmitter terminals	(C) max effect radiated power	(D) insert mean or peak	(E) list each type of emission separately for each frequency	(F) max speed of keying in bauds, max audio mod freq, freq dev of carrier, pulse duration and rep rate	(G) describe how necessary bandwidth was determined
384 MHz	25W	25W	Peak	10K00F3E	5 kHz	Bn=2M
258 MHz	4W	4W	Peak	10K00F3E	5 kHz	Bn=2M
384 MHz	6.5 W	25 W	Peak	N0N		
258 MHz	6.5 W	25 W	Peak	N0N		
379.650 MHz	6.5 W	25 W	Peak	N0N		
379.850 MHz	6.5 W	25 W	Peak	N0N		
254 MHz	6.5 W	25 W	Peak	N0N		
262 MHz	6.5 W	25 W	Peak	N0N		

Transmitting Equipment

Symmetricalcom	Hail Mary 3	1
Senao base station	Star 2000	1
Senao handset	Star 2000	1

Points of Contact

Diane Honsaker, Project Test Lead, 303-932-4639, diane.honsaker@lmco.com
Tom Morrison, Technical Lead, 303-977-7173, thomas.r.morrison@lmco.com

UNCLASSIFIED