

Exhibit – Section 8.3.28 of NTIA Manual

Use of Fixed Devices That Re-Radiate Signals Received From the Global Positioning System

1. Individual authorization is for indoor use only, and is required for each device at a specific site.

Yes

2. Applications for frequency assignment should be applied for as an XT station class with a note indicating the device is to be used as an "Experimental RNSS Test Equipment for the purpose of testing GPS receivers" and describing how the device will be used.

Yes

3. Approved applications for frequency assignment will be entered in the GMF.

Yes

4. The maximum length of the assignment will be two years, with possible renewal.

Yes

5. The area of potential interference to GPS reception (e.g., military or contractor facility) has to be under the control of the user.

Yes

6. The maximum equivalent isotropically radiated power (EIRP) must be such that the calculated emissions are no greater than -140 dBm/24 MHz as received by an isotropic antenna at a distance of 100 feet (30 meters) from the building where the test is being conducted. The calculations showing compliance with this requirement must be provided with the application for frequency assignment and should be based on free space propagation with no allowance for additional attenuation (e.g., building attenuation.)

GPS Input Signal (Pr)	-130 dBm	(typical)
Antenna Gain (Gr)	3 dBi	
Amplifier Gain (Gamp)	55 dB	
Cable Loss (Lc)	-11.5 dB	(115 ft of C240 coaxial cable @ -10 dB/100 ft)
Re-radiating Antenna (Gt)	3 dBi	

GPS Transmit Power	-80.5 dBm	$(-130 + 3 + 55 - 11.5 + 3)$
--------------------	-----------	------------------------------

Path Loss at 100ft	-67 dB	$(20(\log 1575.42 \text{ Mhz} + \log 100 \text{ ft}) - 37)$
--------------------	--------	---

EIRP	-147.5 dBm / 24Mhz	$(-80.5 - 67)$
-------------	---------------------------	----------------------------------

7. GPS users in the area of potential interference to GPS reception must be notified that GPS information may be impacted for periods of time.

Yes

8. The use is limited to activity for the purpose of testing RNSS equipment/systems.

Yes

9. A "Stop Buzzer" point of contact for the authorized device must be identified and available at all times during GPS re-radiation operation of the device under any condition.

Leon Tseng, 315-456-4399