

FCC File # 0706-EX-ST-2006 [Reference Number: 4570], includes responses to 4574.				
1. Television channel number.	18	19	35	52
2. Antenna location site elevation above mean sea level in meters.	398	398	398	398
3. Overall tower height above ground level in meters.	8	8	8	8
4. Height of radiation center above ground level in meters.	406	406	406	406
5. Maximum effective radiated power in kilowatts.	0.02925	0.02925	0.04213	0.05734
6. Transmitter output power in kilowatts.	0.00014	0.00014	0.00014	0.00015
7. Verify that the antenna is nondirectional.	Antenna is directional	Antenna is directional	Antenna is directional	Antenna is directional
	Antenna 3 dB BW is 7 degrees, pointing West	Antenna BW is 7°, pointing West	Antenna BW is 7°, pointing West	Antenna BW is 7°, pointing West
0 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
10 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
20 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
30 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
40 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
50 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
60 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
70 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
80 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
90 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
100 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
110 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
120 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
130 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
140 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
150 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
160 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
170 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
180 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
190 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
200 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
210 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
220 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
230 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
240 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
250 degrees	-13 dBc (0.001466 kW)	-13 dBc (0.001466 kW)	13 dBc (0.002112 kW)	13 dBc (0.002874 kW)
260 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
270 degrees	0.02925 kW	0.02925 kW	0.04213 kW	0.05734 kW
280 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
290 degrees	-13 dBc (0.001466 kW)	-13 dBc (0.001466 kW)	13 dBc (0.002112 kW)	13 dBc (0.002874 kW)
300 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
310 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
320 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
330 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
340 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
350 degrees	-20 dBc (0.0002925 kW)	-20 dBc (0.0002925 kW)	-20 dBc (0.0004213 kW)	-20 dBc (0.0005734 kW)
8. If the emissions are digital, then report the out-of-band emission mask (simple or stringent).	N/A (analog)	N/A (analog)	N/A (analog)	N/A (analog)
9. If the emissions are analog, then report the frequency offset (zero, plus, minus or none).	zero	zero	zero	zero