

# Connected Vehicle Roadside Unit (RSU)

## Roadside Unit

The Connected Vehicle Roadside Unit provides wireless communications from roadside infrastructure to vehicle On Board Units.

The Roadside Unit operates on the 5.9 GHz Direct Short Range Communications (DSRC) band compatible with vehicle systems to provide very low latency required for high speed events, such as crash avoidance.

The Roadside Unit is packaged in a ruggedized weatherproof enclosure suitable for outdoor installation in all weather, including a standard power over Ethernet connection to the traffic signal controller requiring only a single CAT-5 or CAT-6 outdoor Ethernet cable for power and communications.

The Roadside Unit meets the U.S. Department of Transportation FHWA 4.1 specification including communications to vehicles, data security and Global Positioning System (GPS) reception for time of day and location.

In addition to USDOT requirements, the Roadside Unit includes a local Wi-Fi hot spot for remote maintenance or travel time applications and an optional LTE cellular backhaul for data upload / download.

The Roadside Unit also includes internal

data storage for intersection map geometry without need to replace controllers.

As an option, the Roadside Unit can be ordered with software to manage a number of Roadside Units from a central location using area maps.

## Key Features

- Meets USDOT FHWA 4.1 Roadside Unit specifications
- Hi-speed, low-latency DSRC to vehicle On Board units
- Browser based service interface for easy configuration, diagnosis and remote software update
- High security level ensured by following Siemens security initiative process
- Compact, pole-mounting for limited space requirements
- Robust NEMA6P enclosure and connectors for harsh environments
- Power over Ethernet connection to signal controller or cabinet network switch (Siemens ruggedized power over Ethernet injector available separately)
- GPS receiver for location and time
- Local Wi-Fi hot spot for communica-

tions to nearby smart devices such as laptops, tablets and smart phones for pedestrian and cyclist safety applications (ready for travel time applications)

- LTE cellular radio for long distance backhaul to central system
- Optional software to manage multiple Roadside Units from a central system
- Includes all antennas and mounting hardware



## Technical Details

- IEEE 802.11p 5.9 GHz Dual-Radio DSRC
- Receiver sensitivity of -97 dBm (802.11p)
- IEEE 1609.4, 1609.3 and IEEE 1609.2 security compliant
- Hardware Security Module for secure storage of V2x private keys and signature generation
- 2.4 GHz WiFi/Bluetooth hot spot to smart devices and for travel time applications
- GPS with 2.0 m CEP position accuracy and WAAS corrections support
- 2 x Ethernet with one Power over Ethernet for power supply
- LTE for cellular backhaul (plan not included)
- Browser based WebGUI for remote diagnosis and configuration
- SAE J2735 2016 message set incl. MAP, SPAT, BSM, TIM, RSA, RTCM, SRM, SSM
- Meets USDOT FHWA Version 4.1 Roadside Unit specification
- OmniAir certified
- Sealed weatherproof enclosure and connectors
- Internal storage for MAP geometries
- Translates proposed USDOT V2I Hub signal controller message to SAE J2735 SPaT wireless message to vehicles.
- ~8000 ft (2500 meter) range, open-field, line-of-sight

## Parts List

| RSU                           |                                                                                                    |              |
|-------------------------------|----------------------------------------------------------------------------------------------------|--------------|
| RSU with Standard Firmware    | Includes SPaT/MAP and TIM based applications                                                       | AAD17116-101 |
| RSU with TSP Firmware         | Includes SPaT/MAP and TIM based applications and Transit Signal Priority                           | AAD17116-104 |
| RSU with TMS Firmware         | Includes SPaT/MAP and TIM based applications and Triggered Message Sender enabling PCW and WWD     | AAD17116-105 |
| RSU with TSP and TMS Firmware | Includes SPaT/MAP and TIM based applications, Transit Signal Priority and Triggered Message Sender | AAD17116-106 |

| Accessories             |                                 |              |
|-------------------------|---------------------------------|--------------|
| POE                     | Power Over Ethernet Injector    | PXX08913-001 |
| Power Cable             | Power cable for POE             | PHT04515P001 |
| Surge Protection Device | Surge Protection Device for RSU | PXX08942-001 |



## CPU/Memory

- Dual core at 800 MHz for edge computing
- 1 GB RAM

## Interfaces

- 2 x DSRC/WAVE
- 2 x RJ45 10/100 MBit Ethernet
- 1 x 802.11 b/g/n Wifi & Bluetooth 4.0
- 1 x RS232
- 1 x LTE Cat4

## Mechanics

- Dimensions: 11" H x 12" W x 3" D  
27 H x 31 W x 8 D cm
- Weight: approx. 9 pounds
- RSU Shell: Cast Aluminum, Anodized

## Environmental

- Operating Temperature: -40 to 74°C  
-40 to +165°F
- Housing: Sealed, NEMA 6P

## Power

- Input Power: 48 V PoE+ (802.3at)

Siemens Industry, Inc.  
9225 Bee Cave Road  
Building B, Suite 101  
Austin, TX 78733

1.512.837.8300

Subject to change without prior notice  
Printed in USA  
© 2018 Siemens Industry, Inc.

The technical data presented in this document is based on an actual case or on as-designed parameters, and therefore should not be relied upon for any specific application and does not constitute a performance guarantee for any projects. Actual results are dependent on variable conditions. Accordingly, Siemens does not make representations, warranties, or assurances as to the accuracy, currency or completeness of the content contained herein. If requested, we will provide specific technical data or specifications with respect to any customer's particular applications. Our company is constantly involved in engineering and development. For that reason, we reserve the right to modify, at any time, the technology and product specifications contained herein.