

July 11, 2018

Nokia Bell Labs
US LLC

Address:
600 Mountain Ave
Murray Hill, NJ 07974

RE: Addition of Station and Antenna Registration: Directional Antenna Information
License Service Application, File No. 0141-EX-CM-2018 (modification to existing
experimental license, call sign WI2XFC, File No. 0122-EX-CR-2018)

This is the exhibit for the directional antennas. The same exhibit has been provided in the
already granted experimental license, call sign WI2XFC.

Fixed/Base Stations:

- Access Point (AP) will use multiple antennas:
 - No downtilt
 - No tilt in azimuth
 - Minimum azimuth beam width (-3dB to -3dB), 45 degrees
 - Maximum azimuth beam width (-3dB to -3dB), 90 degrees
 - Minimum elevation beam width (-3dB to -3dB), 8 degrees
 - Maximum elevation beam width (-3dB to -3dB), 22 degrees
 - Beam direction perpendicular to antenna array surface

User Devices:

- User Device (UD) will use multiple antennas
 - No downtilt
 - No tilt in azimuth
 - Minimum azimuth beam width (-3dB to -3dB), 45 degrees
 - Maximum azimuth beam width (-3dB to -3dB), 90 degrees
 - Minimum elevation beam width (-3dB to -3dB), 8 degrees
 - Maximum elevation beam width (-3dB to -3dB), 22 degrees
 - Beam direction perpendicular to antenna array surface

Nokia proposes to operate using BPSK, QPSK, 16QAM, 64QAM, and 256 QAM modulation.

Transmit bandwidths are: 400 and 800
MHz.

The primary emission designators are:
400MW7W
800MW7N

The equipment is configured to
operate at a Maximum Transmit
power of 47.8 Watts EIRP. Nokia
will vary the actual powers within the

maximums noted above to test coverage results.

New Station added to Application with the same parameters as the existing stations.

City – New York

State – New York

Address – 500 W. 120th Street

Latitude North 40 48 34

Longitude West 73 57 35

Yours sincerely,

Glenn Steitz

Senior Manager

Nokia Bell Labs

glenn.steitz@nokia.com

(973) 214-0028

