

Form 442

**Pivotal Commware
Application for Conventional Experimental Authority
For 24 GHz and Upper 37 GHz Bands**

Attachment 1

Narrative Statement

Pivotal Commware (Pivotal) is developing Holographic Beam Forming (HBF) antenna technology that will improve the capacity, coverage and throughput of wireless networks.

Pivotal seeks a conventional experimental authorization to undertake testing and perform demonstrations of its HBF technology in the following bands:

- 24.25 – 24.45, and 24.75 – 25.25 GHz (24 GHz band)
- 37.6 – 38.6 GHz (Upper 37 GHz band)

Pivotal plans to undertake such testing at various fixed locations around the United States. Pivotal plans to test within spectrum already licensed to a service provider, in conjunction with the licensee or with prior consent of the licensee.

The technical details of the testing are set forth below.

Transmit equipment to be used, including name of manufacturer, model and number of units.

Pivotal Commware Model "Pivotal 5G," 24 GHz band device, 20 units.

Pivotal Commware Model "Pivotal 5G," 37 GHz band device, 20 units.

Maximum effective radiated power (ERP) or equivalent isotropically radiated power (EIRP).

Maximum (peak) EIRP will be +40 dBm (10 dBW), or 10 Watts, which translates to ERP of +37.85 dBm (7.85 dBW), or 6.1 Watts.

Emission designators (see §2.201 of this chapter) or describe emission (bandwidth, modulation, etc.)

100MG7W

Additional Information

Frequency tolerance: 0.001%

Width of transmit beam in degrees at half-power point: 5 degrees in azimuth and 20 degrees in elevation for broadside scan; 10 degrees in azimuth and 30 degrees in elevation for scan 60 degrees.

Width of receive beam in degrees at half-power point: same as transmit

Antenna gain (maximum): 20 dBi.

Polarization: Linear

Stop buzzer POC

Mersad Cavcic – 206-369-7682