

**United States of America
FEDERAL COMMUNICATIONS COMMISSION
EXPERIMENTAL
RADIO STATION CONSTRUCTION PERMIT
AND LICENSE**

EXPERIMENTAL

(Nature of Service)

XT FX

(Class of Station)

WK2XBV

(Call Sign)

0119-EX-CR-2021

(File Number)

NAME SkyWest Airlines INC

Subject to the provisions of the Communications Act of 1934, subsequent acts, and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions and requirements set forth in this license, the licensee hereof is hereby authorized to use and operate the radio transmitting facilities hereinafter described for radio communications in accordance with the program of experimentation described by the licensee in its application for license.

Operation: In accordance with Sec. 5.3(j) of the Commission's Rules

Station Locations

- (1) Salt Lake City (SALT LAKE), UT - NL 40-47-37; WL 111-59-09
- (2) Salt Lake City (SALT LAKE), UT - NL 40-47-37; WL 111-59-15
- (3) Salt Lake City (SALT LAKE), UT - NL 40-47-39; WL 111-59-15

Frequency Information

Salt Lake City (SALT LAKE), UT - NL 40-47-37; WL 111-59-09

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	2M04W7D	19.2 pW (ERP)	0.01 %

Salt Lake City (SALT LAKE), UT - NL 40-47-37; WL 111-59-15

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	2M04W7D	19.2 pW (ERP)	0.01 %

This authorization effective April 01, 2021 and
will expire 3:00 A.M. EST April 01, 2023

**FEDERAL
COMMUNICATIONS
COMMISSION**



Frequency Information

Salt Lake City (SALT LAKE), UT - NL 40-47-39; WL 111-59-15

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	2M04W7D	19.2 pW (ERP)	0.01 %

Special Conditions:

- (1) The occupied bandwidth of the emission shall not extend beyond the band limits set forth above.
- (2) Licensee should be aware that other stations may be licensed on these frequencies and if any interference occurs, the licensee of this authorization will be subject to immediate shut down.
- (3) GPS re-radiators are limited to a maximum EIRP value that will result in power levels not to exceed a power spectral density of -140 dBm/24 MHz measured at a distance of 100 ft from the building where the test is being conducted. Any malfunction, misalignment, or tampering of the equipment or its location which results in an increased power spectral density outside the building could cause harmful radio frequency interference to GPS receivers, including those in aircraft and/or ground based facilities.
- (4) The designated point-of-contact to terminate transmissions if interference occurs is Paul Accordino 435-634-3492 paccordino@skywest.com
- (5) The test equipment shall only be used indoors and shall be under the control of the licensee.
- (6) Licensee shall post signs on doors to the test area notifying that, "GPS re-radiator is in use and the GPS information you receive may be in error."
- (7) Authorization is for indoor use only.
- (8) The area of potential interference to GPS reception has to be under the control of the user.
- (9) Operation is limited to activity for the purpose of testing radio navigation satellite service (RNSS) equipment and systems.
- (10) GPS users in the area of potential interference to GPS reception must be notified that GPS information may be impacted for periods of time.
- (11) GPS re-radiators must operate in accordance with Section 8.3.28 of the NTIA Manual. Power spectral density of the signal should be very well controlled beyond the building.