

NTIA Space record data form

NTIA requires the following data for space related experiments using government shared spectrum. For each transmit frequency, please provide the data for both ends of the transmit-receive link. Use Part A to describe the satellite to ground information. Part B is for all ground to space transmit links.

Part A: Space to Earth Downlink Data

Satellite Transmitter Data (Required for Each Frequency)

Transmit Frequency: UHF: 400.15-401 MHz		
Satellite Name: Protostar		
Data Field	Data Answer	Description/Comments
Transmit Power (PWR)	PWR = 4W	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	60 kHz	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth	60 kHz	
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	GFSK	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	9.6 kbps	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____	
Total Symbol Rate	9.6 kbps	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.
Does transmitter have a beacon mode?	Yes ☐ No ☒	BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE.

If transmitter has a beacon mode, can the beacon be commanded off?	Yes ☒ No ☐	
Transmit Antenna Polarization (XAP)	XAP = L	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Transmit Antenna Dimension (XAD)	XAD = 03G360B	NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B
Type of satellite (State = SPCE) (City = Geo or Nongeo)	Type = NONGEOSTATIONARY	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>.57</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = 97.5IN00510AP00510PE001.58H01NRT01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>10:30</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Earth Station Data (Receiver) at Each Earth Station Location		
State (RSC)	RSC = Alaska	
City Name (RAL)	RAL = Deadhorse	
Latitude (DDMMSS)	Lat = 70° 12' 43.1"	
Longitude (DDDMMSS)	Lon = -148° 26' 13.7"	

Receive Antenna Polarization (RAP)	RAP = L	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = V05	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN <u>16</u> , BEAMWIDTH <u>30</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>10</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>18</u> , RAD01 16G030B001-360A00010H018	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER <u>n/a</u> , ANTENNA EFFICIENCY <u>n/a</u>	
Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☒ Mission Payload Data ☒	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes:		
Earth Station Data (Receiver) at Each Earth Station Location		
State (RSC)	RSC = Norway	
City Name (RAL)	RAL = Tromsø	
Latitude (DDMMSS)	Lat = 69° 37' 47.9994"	
Longitude (DDDMMSS)	Lon = 18° 56' 24"	

Receive Antenna Polarization (RAP)	RAP = L	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = V05	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN <u>18</u> , BEAMWIDTH <u>20</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>106</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>5</u> , RAD01 18G020B001-360A00106H005	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____,	
Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☒ Mission Payload Data ☒	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes:		
Earth Station Data (Receiver) at Each Earth Station Location		
State (RSC)	RSC = Alaska	
City Name (RAL)	RAL = Fairbanks	
Latitude (DDMMSS)	Lat = 64° 51' 18.08"	
Longitude (DDDMMSS)	Lon = -147° 41' 10.63"	

Receive Antenna Polarization (RAP)	RAP = L	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = V05	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN <u>16</u> , BEAMWIDTH <u>30</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>136</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>18</u> , RAD01 16G030B001-360A00136H018	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> ,	
Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☒ Mission Payload Data ☒	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes:		
Earth Station Data (Receiver) at Each Earth Station Location		
State (RSC)	RSC = South Africa	
City Name (RAL)	RAL = Pretoria	
Latitude (DDMMSS)	Lat = -25° 51' 39.6"	
Longitude (DDDMMSS)	Lon = 28° 27' 10.7994"	

Receive Antenna Polarization (RAP)	RAP = L	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = V05	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN <u>16</u> , BEAMWIDTH <u>30</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>1390</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2</u> , RAD01 16G030B001-360A01390H002	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u>	
Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☒ Mission Payload Data ☒	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes:		
Earth Station Data (Receiver) at Each Earth Station Location		
State (RSC)	RSC = Portugal	
City Name (RAL)	RAL = Santa Maria, Azores	
Latitude (DDMMSS)	Lat = 36° 59' 52.7994"	
Longitude (DDDMMSS)	Lon = -25° 8' 13.2"	

Receive Antenna Polarization (RAP)	RAP = L	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = V05	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN <u>15</u> , BEAMWIDTH <u>20</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____, RAD =	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____,	
Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☒ Mission Payload Data ☒	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes:		
Transmit Frequency: X-Band: 8025-8400 MHz		
Satellite Name: Protostar		
Data Field	Data Answer	Description/Comments
Transmit Power (PWR)	PWR = 1.57 W	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT

Necessary Bandwidth	50 MHz	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	DVB-S2	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate		INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☒ No ☐ FEC Type: _____, FEC Rate: _____,	
Total Symbol Rate		DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.
Does transmitter have a beacon mode?	Yes ☒ No ☐	BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE.
If transmitter has a beacon mode, can the beacon be commanded off?	Yes ☒ No ☐	
Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Transmit Antenna Dimension (XAD)	XAD = 07G045B	NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B
Type of satellite (State = SPCE) (City = Geo or Nongeo)	Type = NONGEOSTATIONARY	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).

For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>.57</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = 97.5IN00510AP00510PE001.58H01NRT01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>10:30</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Earth Station Data (Receiver) at Each Earth Station Location		
State (RSC)	RSC = Iceland	
City Name (RAL)	RAL = Blönduós	
Latitude (DDMMSS)	Lat = 65° 38' 52.7994"	
Longitude (DDMMSS)	Lon = -20° 14' 16.7994"	
Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = V05	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN <u>47</u> , BEAMWIDTH <u>0.60</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>53</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.50</u> , RAD01 47G001B001-360A00053H003	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____,	

Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☒ Mission Payload Data ☒	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes:		
Earth Station Data (Receiver) at Each Earth Station Location		
State (RSC)	RSC = New Zealand	
City Name (RAL)	RAL = Awarua	
Latitude (DDMMSS)	Lat = -46° 31' 40.7994"	
Longitude (DDDMMSS)	Lon = 168° 22' 44.3994"	
Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = V05	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN <u>47</u> , BEAMWIDTH <u>0.60</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>8.00</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.20</u> , RAD01 47G001B001-360A00008H002	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____,	

Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☒ Mission Payload Data ☒	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes:		
Earth Station Data (Receiver) at Each Earth Station Location		
State (RSC)	RSC = Chile	
City Name (RAL)	RAL = Punta Arenas	
Latitude (DDMMSS)	Lat = -53° 2' 27.5994"	
Longitude (DDMMSS)	Lon = -70° 50' 49.1994"	
Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = V05	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN <u>47</u> , BEAMWIDTH <u>0.60</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>36.00</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>3.20</u> , RAD01 47G001B001-360A00036H003	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____,	

Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☒ Mission Payload Data ☒	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes:		

Part B: Ground Stations, Earth to Space link data:

Earth Station Transmitter Data (Required for Each Frequency at Each Earth Station Location)

Transmit Frequency: S-Band: 2025-2110 MHz		
State (XSC)	XSC = Norway	
City Name (XAL)	XAL = Tromsø	
Latitude (DDMMSS)	Lat = 69° 37' 47.9994"	
Longitude (DDDMMSS)	Lon = 18° 56' 24"	
Transmit Power (PWR)	PWR = 25.1W	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	SB1: 300 kHz SB2: 5000 kHz	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	BPSK	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	120 kbps	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____,	
Total Symbol Rate	120 ksps	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.
Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ01 V05	THE EARTH STATION TRANSMITTER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (XAZ), V00 TO V90, EXAMPLE, XAZ01 V00

Transmit Antenna Dimensions (XAD)	ANTENNA GAIN <u>34</u> , BEAMWIDTH <u>2.71</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>106</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>5</u> , <u>XAD01 34G003B001-360A00106H005</u>	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: XAD01 16G030B001-360A00357H006
Transmit Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____,	
Number of Satellite Contacts Supported Per Day	<u>Up to 3-6 per station</u>	NUMBER OF TIMES THE EARTH STATION WILL COMMUNICATE WITH THE SATELLITE IN THE EARTH TO SPACE DIRECTION (UPINKS) EACH DAY
Expected Duration of Each Contact	<u>5-10 min</u>	AVERAGE DURATION OF EACH CONTACT
Satellite Receive Specifications		
Receive Antenna Polarization (RAP)	RAP = <u>R</u>	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = <u>EC</u>	NB= NARROWBEAM EC = EARTH COVERAGE
Receive Antenna Dimension (RAD)	ANTENNA GAIN _____, BEAMWIDTH _____, RAD =	NTIA FORMAT(RAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH RAD01 16G030B
Type of satellite (State = SPCE) City = Geo or Nongeo	Type = <u>NONGEOSTATIONARY</u>	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).

For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>.57</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB= <u>97.5IN00510AP00510PE001.58H01NRT01</u>	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>10:30</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Transmit Frequency: <u>S-Band: 2025-2110 MHz</u>		
State (XSC)	XSC = <u>Alaska</u>	
City Name (XAL)	XAL = <u>Deadhorse</u>	
Latitude (DDMMSS)	Lat = <u>70° 12' 42.0"</u>	
Longitude (DDDMMSS)	Lon = <u>148° 24' 43.0"</u>	
Transmit Power (PWR)	<u>PWR = 30.0W</u>	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	<u>SB1: 300 kHz</u> <u>SB2: 5000 kHz</u>	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	<u>BPSK</u>	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	<u>120 kbps</u>	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____,	
Total Symbol Rate	<u>120 ksps</u>	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.

Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ01 V05	THE EARTH STATION TRANSMITTER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (XAZ), V00 TO V90, EXAMPLE, XAZ01 V00
Transmit Antenna Dimensions (XAD)	ANTENNA GAIN <u>40.4</u> , BEAMWIDTH <u>1.7</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>10</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>1.5</u> , XAD01 40G002B001-360A00010H002	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: XAD01 16G030B001-360A00357H006
Transmit Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER <u>6.0</u> , ANTENNA EFFICIENCY <u>65%</u>	
Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE EARTH STATION WILL COMMUNICATE WITH THE SATELLITE IN THE EARTH TO SPACE DIRECTION (UPINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Satellite Receive Specifications		
Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Receive Antenna Dimension (RAD)	ANTENNA GAIN _____, BEAMWIDTH _____, RAD =	NTIA FORMAT(RAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH RAD01 16G030B
Type of satellite (State = SPCE) City = Geo or Nongeo	Type = NONGEOSTATIONARY	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY

For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB= <u>97.5IN00510AP00510PE001.58H01NRT01</u>	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>10:30</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Transmit Frequency: S-Band: 2025-2110 MHz		
State (XSC)	XSC = South Africa	
City Name (XAL)	XAL = Pretoria	
Latitude (DDMMSS)	Lat = -25° 51' 39.6"	
Longitude (DDMMSS)	Lon = 28° 27' 10.7994"	
Transmit Power (PWR)	PWR = 30.0W	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	SB1: 300 kHz SB2: 5000 kHz	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	BPSK	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	120 kbps	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____,	
Total Symbol Rate	120 ksps	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.

Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ01 V05	THE EARTH STATION TRANSMITTER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (XAZ), V00 TO V90, EXAMPLE, XAZ01 V00
Transmit Antenna Dimensions (XAD)	ANTENNA GAIN <u>40.4</u> , BEAMWIDTH <u>1.7</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>1390</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>1.5</u> , XAD01 40G002B001-360A01390H002	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: XAD01 16G030B001-360A00357H006
Transmit Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER <u>6.0</u> , ANTENNA EFFICIENCY <u>65%</u>	
Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE EARTH STATION WILL COMMUNICATE WITH THE SATELLITE IN THE EARTH TO SPACE DIRECTION (UPINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Satellite Receive Specifications		
Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Receive Antenna Dimension (RAD)	ANTENNA GAIN _____, BEAMWIDTH _____, RAD =	NTIA FORMAT(RAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH RAD01 16G030B
Type of satellite (State = SPCE) City = Geo or Nongeo	Type = NONGEOSTATIONARY	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY

For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB= <u>97.5IN00510AP00510PE001.58H01NRT01</u>	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>10:30</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Transmit Frequency: <u>S-Band: 2025-2110 MHz</u>		
State (XSC)	XSC = <u>Portugal</u>	
City Name (XAL)	XAL = <u>Santa Maria, Azores</u>	
Latitude (DDMMSS)	Lat = <u>36° 59' 51.1"</u>	
Longitude (DDDMMSS)	Lon = <u>-25° 8' 14.2"</u>	
Transmit Power (PWR)	PWR = <u>31.62 W</u>	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	<u>SB1: 300 kHz</u> <u>SB2: 5000 kHz</u>	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	<u>BPSK</u>	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	<u>120 kbps</u>	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____	
Total Symbol Rate	<u>120 ksps</u>	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.

Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ01 V05	THE EARTH STATION TRANSMITTER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (XAZ), V00 TO V90, EXAMPLE, XAZ01 V00
Transmit Antenna Dimensions (XAD)	ANTENNA GAIN <u>35.00</u> , BEAMWIDTH <u>2.76</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>195</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> , XAD01 35G003B001-360A00195H002	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: XAD01 16G030B001-360A00357H006
Transmit Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____,	
Number of Satellite Contacts Supported Per Day	Up to 3-6	NUMBER OF TIMES THE EARTH STATION WILL COMMUNICATE WITH THE SATELLITE IN THE EARTH TO SPACE DIRECTION (UPINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Satellite Receive Specifications		
Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Receive Antenna Dimension (RAD)	ANTENNA GAIN _____, BEAMWIDTH _____, RAD =	NTIA FORMAT(RAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH RAD01 16G030B
Type of satellite (State = SPCE) City = Geo or Nongeo	Type = NONGEOSTATIONARY	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY

For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB= <u>97.5IN00510AP00510PE001.58H01NRT01</u>	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>10:30</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Transmit Frequency: <u>S-Band: 2025-2110 MHz</u>		
State (XSC)	XSC = <u>Iceland</u>	
City Name (XAL)	XAL = <u>Blönduós</u>	
Latitude (DDMMSS)	Lat = <u>65° 38' 52.7994"</u>	
Longitude (DDMMSS)	Lon = <u>-20° 14' 16.7994"</u>	
Transmit Power (PWR)	PWR = <u>31.62 W</u>	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	<u>SB1: 300 kHz</u> <u>SB2: 5000 kHz</u>	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	<u>BPSK</u>	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	<u>120 kbps</u>	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____,	
Total Symbol Rate	<u>120 ksps</u>	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.

Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ01 V05	THE EARTH STATION TRANSMITTER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (XAZ), V00 TO V90, EXAMPLE, XAZ01 V00
Transmit Antenna Dimensions (XAD)	ANTENNA GAIN <u>35.00</u> , BEAMWIDTH <u>2.76</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>53.0</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.50</u> , XAD01 35G003B001-360A00053H003	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: XAD01 16G030B001-360A00357H006
Transmit Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____,	
Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE EARTH STATION WILL COMMUNICATE WITH THE SATELLITE IN THE EARTH TO SPACE DIRECTION (UPINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Satellite Receive Specifications		
Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Receive Antenna Dimension (RAD)	ANTENNA GAIN _____, BEAMWIDTH _____, RAD =	NTIA FORMAT(RAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH RAD01 16G030B
Type of satellite (State = SPCE) City = Geo or Nongeo	Type = NONGEOSTATIONARY	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY

For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB= <u>97.5IN00510AP00510PE001.58H01NRT01</u>	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>10:30</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Transmit Frequency: <u>S-Band: 2025-2110 MHz</u>		
State (XSC)	XSC = <u>New Zealand</u>	
City Name (XAL)	XAL = <u>Awarua</u>	
Latitude (DDMMSS)	Lat = <u>-46° 31' 40.7994"</u>	
Longitude (DDMMSS)	Lon = <u>168° 22' 44.3994"</u>	
Transmit Power (PWR)	PWR = <u>31.62 W</u>	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	<u>SB1: 300 kHz</u> <u>SB2: 5000 kHz</u>	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	<u>BPSK</u>	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	<u>120 kbps</u>	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____	
Total Symbol Rate	<u>120 ksps</u>	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.

Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ01 V05	THE EARTH STATION TRANSMITTER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (XAZ), V00 TO V90, EXAMPLE, XAZ01 V00
Transmit Antenna Dimensions (XAD)	ANTENNA GAIN <u>35.00</u> , BEAMWIDTH <u>2.76</u> , AZIMUTHAL RANGE <u>001-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>8.0</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.20</u> , XAD01 35G003B001-360A00008H002	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: XAD01 16G030B001-360A00357H006
Transmit Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____,	
Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE EARTH STATION WILL COMMUNICATE WITH THE SATELLITE IN THE EARTH TO SPACE DIRECTION (UPINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Satellite Receive Specifications		
Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Receive Antenna Dimension (RAD)	ANTENNA GAIN _____, BEAMWIDTH _____, RAD =	NTIA FORMAT(RAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH RAD01 16G030B
Type of satellite (State = SPCE) City = Geo or Nongeo	Type = NONGEOSTATIONARY	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY

For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB= <u>97.5IN00510AP00510PE001.58H01NRT01</u>	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>10:30</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Transmit Frequency: <u>S-Band: 2025-2110 MHz</u>		
State (XSC)	XSC = <u>Chile</u>	
City Name (XAL)	XAL = <u>Punta Arenas</u>	
Latitude (DDMMSS)	Lat = <u>-53° 2' 27.5994"</u>	
Longitude (DDMMSS)	Lon = <u>-70° 50' 49.1994"</u>	
Transmit Power (PWR)	PWR = <u>31.62 W</u>	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	<u>SB1: 300 kHz</u> <u>SB2: 5000 kHz</u>	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	<u>BPSK</u>	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	<u>120 kbps</u>	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____,	

Total Symbol Rate	120 kbps	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.
Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ01 V05	THE EARTH STATION TRANSMITTER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (XAZ), V00 TO V90, EXAMPLE, XAZ01 V00
Transmit Antenna Dimensions (XAD)	ANTENNA GAIN 35.00, BEAMWIDTH 2.76, AZIMUTHAL RANGE 001-360, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS 36.0, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS 3.2, XAD01 35G003B001-360A00036H003	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: XAD01 16G030B001-360A00357H006
Transmit Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____,	
Number of Satellite Contacts Supported Per Day	Up to 3-6 per station	NUMBER OF TIMES THE EARTH STATION WILL COMMUNICATE WITH THE SATELLITE IN THE EARTH TO SPACE DIRECTION (UPINKS) EACH DAY
Expected Duration of Each Contact	5-10 min	AVERAGE DURATION OF EACH CONTACT
Satellite Receive Specifications		
Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Receive Antenna Dimension (RAD)	ANTENNA GAIN _____, BEAMWIDTH _____, RAD =	NTIA FORMAT(RAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH RAD01 16G030B

Type of satellite (State = SPCE) City = Geo or Nongeo	Type = NONGEOSTATIONARY	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB= 97.5IN00510AP00510PE001.58H01NRT01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>10:30</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)